ALAN DONAKER SURVEYING

Alan Donaker, P.S. 19849 TR 383

Walhonding, OH 43843

Fax: (740) 327-1083 Phone: (740) 327-7001

T-1

Being 46.485 acres more or less, in Lots 19, 20, 21 and 22, Adams First Addition Plat Book 2, page 6, First Quarter, Township 3 North, Range 8 West, United States Military Lands, in the Township of Cass, in the County of Muskingum, in the State of Ohio, conveyed to Carol Sue Howard aka Carol S., DR 2677-23 (part, tract 1), DR 1093-547 (part) and DR 851-345 (part), Parcel No. 10-08-41-37-000 (part) and more particularly described as follows:

Commencing at a stone of record at the Northeast corner of Lot 1, Adams First Addition Plat Book 2, page 6:

thence, with the West line of the Second Quarter of T-3N, R7W, S. 01° 31' 22" W. a distance of 3096.01' to a 5%" rebar found, said rebar being the TRUE POINT OF BEGINNING;

thence, with the West line of the Second Quarter of T-3N, R7W and the property line of Jane A. Siegrist, Trustee, DR 1553-918, the following 2 courses:

- 1. thence, S. 01° 31' 22" W. a distance of 107.67' to a axle found;
- 2. thence, S. 01° 31' 22" W. a distance of 1943.02' to a 2" pipe found;

thence, with the property line of Ohio Rail Development Commission, DR 2397-658, the following 2 courses:

- 1. thence, S. 76° 09' 02" W. a distance of 1360.41' to a 5%" rebar found;
- 2. thence, N. 13° 50' 58" W. a distance of 50.00' to a 2" square bar found (with +);

thence, through the property of Carol Sue Howard aka Carol S., DR 2677-23, DR 1093-547 and DR 851-345, the following 4 courses:

- 1. thence, N. 00° 56' 56" E. a distance of 305.96' to a 5%" rebar set;
- 2. thence, N. 07° 16' 10" E. a distance of 158.01' to a 5%" rebar set;
- 3. thence, N. 16° 08' 34" E. a distance of 311.15' to a 5/8" rebar set;
- 4. thence, S. 87° 56' 17" W. a distance of 74.48' to a \(\frac{5}{8} \)" rebar set;

thence, with the East line of Muskingum County Commissioners, DR 209-375, North Dresden Road, the following 6 courses:

- 1. thence, with a curve to the left, the curve data for which is: D. = 19° 53' 21", R. = 742.98', L. = 257.91', Ch. B. = N. 30° 36' 31" E., Ch. L. = 256.62' to a concrete monument found;
- 2. thence, N. 20° 39' 51" E. a distance of 124.24' to a concrete monument found;
- 3. thence, with a curve to the right, the curve data for which is: D. = 14° 28' 16", R. = 1092.37', L. = 275.90', Ch. B. = N. 27° 53' 59" E., Ch. L. = 275.17' to a 5%" rebar set;
- 4. thence, N. 35° 08' 08" E. a distance of 236.45' to a concrete monument found;
- 5. thence, with a curve to the right, the curve data for which is: D. = 17° 21' 51", R. = 925.39', L. = 280.45', Ch. B. = N. 43° 51' 53" E., Ch. L. = 279.38' to a concrete monument found;
- 6. thence, N. 52° 30' 00" E. a distance of 434.32' to a point;

thence, with the property line of State of Ohio, DR 2046-774, the following 4 courses:

- 1. thence, S. 44° 43' 43" E. a distance of 69.68' to a \%" rebar found;
- 2. thence, N. 54° 10' 31" E. a distance of 269.40' to a ¾" pipe found; 3. thence, N. 39° 42' 29" E. a distance of 111.95' to a ¾" pipe found;
- 4. thence, N. 14° 04' 13" E. a distance of 138.57' to the TRUE POINT OF BEGINNING, containing 46.485 acres, more or less, including public road right-ofway and is subject to all easements, rights-of-way, or restrictions, whether recorded or implied.

Bearings are based on DR 2677-23 and are for angular calculations only.

All 5/8" rebars set are 30" long with plastic cap marked "AMD 8050".

Pertinent Documents: Tax Map and all Deeds shown

Surveys by: Peter L. Dinan

Description and plat by Alan Donaker, Professional Surveyor, #8050, from a survey of the premises on May 14 in the year of our Lord Two Thousand Eighteen.

MOT RECORDABLE



