## Linn Engineering, Inc.

*Civil Engineering Consultants* 740-452-7434 • 1-800-991-7434 • FAX 740-452-5198 534 Market Street • P.O. Box 2086 • Zanesville, Ohio 43702-2086

## Gossman and Lowe - Plat 21

Situated in the State of Ohio, County of Muskingum, Township of Falls and bounded and described as follows:

Being a part of lands now owned by C. Gossman and S. Lowe (DR 1157-87) and being more particularly bounded and described as follows:

Beginning for reference at an iron pipe found on the northeast corner of Lot 3 of Edmund Brush Subdivision as designated and delineated on Muskingum County Plat Book 1, Page 208;

thence along the south line of lands now owned by Zanesville Board of Education (DR 876-193) South 60 degrees 46 minutes 36 seconds West for a distance of 280.50 feet to an iron pin to be set after construction and the principal place of beginning, passing iron pins set at 203.88 feet and 231.50 feet;

thence along the west line of lands now owned by Sarel Offinger (DR 1101-113) South 13 degrees 10 minutes 23 seconds East for a distance of 36.40 feet to an iron pin found on the northeast corner of lands now owned by N. and A. Sheets (DR 1129-539);

thence along said Sheets' north line South 52 degrees 32 minutes 09 seconds West for a distance of 36.51 feet to an iron pin to be set after construction;

thence through lands now owned by C. Gossman and S. Lowe (DR 1157-87) North 01 degrees 14 minutes 53 seconds East for a distance of 46.66 feet to an iron pin to be set after construction on the south line of lands now owned by Beitzel Family Limited Partnership (DR 1125-794); thence along said Beitzels' south line the following two compares

thence along said Beitzels' south line the following two courses:

- 1) North 60 degrees 46 minutes 36 seconds East for a distance of 3.38 feet to an iron pin found;
- 2) North 60 degrees 46 minutes 36 seconds East for a distance of 19.16 feet to the principal place of beginning;

containing 0.02 acres, more or less, subject to all legal road right of ways and applicable easements, written or implied.

Bearings are based on NAD 83, South Zone, Ohio State Plane Coordinate System, as per GPS Observations of Muskingum County GPS Monuments.

Iron pins set are 5/8 inch diameter by 30 inch long rebar with plastic identification caps.

This description is written from a survey completed on May 8, 2003 by Jack D. Newcome, Reg. No. 7321.

OFFICE COPY Jack D. Neu RECORDABLAE 18/03 Reg NO 1321

DESCRIPTION APPROVED

Parcel No. Part of: 17-17-79-01-12-000 (0.02 ac.)

ADDRESS NIA

