## BOWMAN SURVEYING 38 N. 4<sup>TH</sup> STREET, RM. 103 ZANESVILLE, OHIO PH./FAX (740) 454-0496

## SURVEY DESCRIPTION FOR Mariorie Hanna

ALL OF AUDITORS PARCELS 23-60-11-20-000 (79.347 ACRES) 23-60-12-22-000 (0.164 ACRES)

Situated in sections 11 and 12, T-2, R-5, Highland Township, Muskingum County, Ohio. Being the remaining lands of Marjorie Hanna conveyed in deed book 314 page 639 of the Muskingum County Deed records, and being described as follows;

Beginning at an iron pin found marking the Southeast corner of the Southwest Quarter of Section 11;

- Thence, N.87°06'06"W. a distance of 2,617.91 feet along the South line of said quarter section line to a found iron pin on the Southwest corner of said quarter section;
- Thence, N.02°09'55"E. a distance of 27.47 feet along the West line of said quarter section to a point in the center of Lower Bloomfield Road;
- Thence, N.30°39'11"W. a distance of 150.68 feet along the center of said road to a point on the Southwest corner of the lands, now or formerly, owned by R. Williams (993/462);
- Thence, N.61°17'17"E. a distance of 396.83 feet along said Williams lands to a found iron pin, passing a set iron pin at 30.00 feet, passing the west line of the Southwest quarter of section 11 at 95.15 feet;
- Thence, N.16°38'28"W. a distance of 130.74 feet along said Williams lands to a found iron pin;
- Thence, N.88°37'09"W. a distance of 216.79 feet along said Williams lands to a found iron pin on the West line of said quarter section;
- Thence, N.02°09'55"E. a distance of 865.22 feet along said Williams lands to a found iron pin;
- Thence, S.86°48'18"E. a distance of 2,626.61 feet along the south lines of C. McQuain (707/214) and C. & K. McQuain (1518/74) to a found iron pin on the East line of said quarter section;
- Thence, S.02°31'52"W. a distance of 1,330.08 feet along said quarter section line to the point of beginning.

The above described parcel contains 79.511 acres, more or less, (0.164 acres in section 12 and 79.347 acres in section 11) and is subject to all legal easements and right of ways. All set rebars are 5/8" x 30" rebars with plastic I.D. caps. North is based upon an assumed meridian.

Description was prepared from an actual survey by Bowman Surveying, Stephen M. Bowman, P.S.#7135. January 15, 2004.

OFFICE COPY
NOT RECORDABLE

DESCRIPTION APPROVED
FOR AUDITORIS TRANSFER
BY 12/2007

