

DIVISION OF ENGINEERING & SURVEYING

> 367 Bouth 30th Suite D Heath, Ohio 43956 614-522-8417

38-20-03-32 10200 NORTH RIUGE DA

Situated in the State of Ohio, County of Muskingum, Township of Madison.

Being a part of Quarter Township 3, Township 3, Range 7 and a part of

Quarter Township 4, Township 3, Range 8 bounded and described as follows:

Commencing at a stone found at the Southwest Corner of Quarter Township 3, Township 3, Range 7; thence along the range line North  $2^{\circ}$  25' 25" East 4890,40 feet to an iron pin and the true place of beginning of the premises herein intended to be described; thence continuing along said range line North 20 25' 25" East 370.92 feet to an iron pin; thence North 87° 32' 49" West 920.07 feet along an existing fence to a post; thence North 26° 56' 11" East 400 feet to an iron pin; thence North 63° 03' 49" West 161.84 feet to a point on the low water mark of the Muskingum River; Thence along said low water mark and the meanderings thereof North 290 30' 45" East 1044.95 feet to a point; thence North 89° 59' 01" EAst 559.75 feet to a point in the center of State Route 666' thence along said centerline North 10° 19' 42" East 120.20 feet to a point; thence leaving said centerline South 620 12' 06" East 125.20 feet to an 1ron pin; thence North 27° 59' 06" East 150.30 feet to an iron pin; thence North 34° 35' 34" East 155.19 feet to an 1ron pin; thence North 32° 29' 05" West 119.27 feet to a point; thence South 65° 14' 54" West 273.26 feet to a point in the center of State Route 666; thence along said road the following four (4) courses and distances, North 43° 28' 06" West 116.66 feet to a point; thence North 51° 11' 19" West 72.10 feet to a point; thence North 43° 20' S4" West 80 feet to a point; thence North 110 49' 58" West 80.61 feet to a point; thence leaving said centerline South 15° 43' 30" West 62,10 feet. to an old iron fence post; thence North 340 24' 03" West 84.31 feet to the low water mark of the Muskingum River; thence up the low water mark and the meanderings thereof North 190 36' 38" East 793.25 feet to a point; thence South 82° 09' 54" East 2857.04 feet to an iron pin; thence South 2° 04' 37" West 2775.67 feet to an iron pin; thence South 89° 44' 45" West 555.87 to a large tree with fence in it; thence North 83° 16' 15" West 92.86 feet to a large tree with a fence in it; thence South 83° 24' 12" West 248.20 feet to a large tree with fence in it; thence South 85°

00' 27" West 369.65 feet to a large blazed tree; thence North 86° 49' 11" West 298.29 feet to a 36 inch blazed tree; thence North 85° 45' 17" West 189.49 feet to a 24 inch blazed tree; thence North 80° 05' 52" West 192.17 feet to a 24 inch blazed tree; thence North 87° 21' 13" West 674.76 feet to the place of beginning.

Containing 198.5242 acres, subject to all legal road right-of-way.

The bearings in this description are based on the line between Range 7 and 8 being North  $2^{\rm O}$  25' 25" East as established by Max Groves Reg. Surveyor No. 5792.

This description was prepared by The Hitchens Corporation, Division of Engineering and Surveying, from a survey made by same during Sept., 1986

lars Mark Harden ARL Eurveyor #4623

OL 1/2/21

