Survey Description

SNR NA

for Daniel E. and Lisa D. Clark Tract I

Situated in the Township of Monroe, County of Muskingum, State of Ohio and being 58.691 acres in Lot 11 of the Third Quarter of Township 3 north Range 5 west of the United States Military District and being more particularly described as follows,

BEGINNING at a marked stone found at the northwest corner of said Lot 11 thence with the north line of said lot 11 and with the lands of Tony B. McClain as recorded in official records volume 1514 page 406 the next two calls,

1) S 87° 57' 51" E a distance of 1240.00 feet to an iron pin set.

2) S 87° 57' 51" E a distance of 1311.05 feet to a point in the center of State Route 93 having passed through an iron pin set at 1266.05 feet thence with said road and with the lands of Berl E. and Barbara K. Cavinee as recorded in official records volume 1535 page 224 S 32° 03' 55" W a distance of 103.32 feet to a point thence continuing with the center of said State Route 93 and with a line through the lands of Daniel E. and Lisa D. Clark as recorded in official records volume 1140 page 954 the next nine calls,

1) S 32° 03' 55" W a distance of 395.28 feet to a point.

2) thence with a tangent curve to the left having the following properties, $Delta = 26^{\circ} 29' 41''$, Radius = 560.90 feet and a chord that bears S 18° 49' 04" W a distance of 257.07 feet to a point, said point being referenced by an iron pin set which bears S 84° 25' 46" E a distance of 30.00 feet.

3) S 05° 34' 14" W a distance of 32.75 feet to a point.

4) thence with a tangent curve to the right having the following properties, Delta = 91° 58' 28", Radius = 367.17 feet and a chord that bears S 51° 33' 28" W a distance of 528.13 feet to a point, said point being referenced by an iron pin set which bears S 07° 32' 42" W a distance of 15.00 feet.

5) N 82° 27' 18" W a distance of 712.75 feet to a point, said point being referenced by an iron pin set which bears N 07° 32' 42" E a distance of 20.00 feet.

6) thence with a tangent curve to the left having the following properties, Delta = $41^{\circ} 13' 25''$, Radius = 738.15 feet and a chord that bears S 76° 55' 59" W a distance of 519.71 feet to a point.

7) S 56° 19' 17" W a distance of 89.17 feet to a point, said point being referenced by an iron pin set which bears S 33° 40' 43" E a distance of 30.00 feet.

8) thence with a tangent curve to the left having the following properties, Delta = 30° 18' 25", Radius = 1183.13 feet and a chord that bears S 41° 10' 04" W a distance of 618.55 feet to a point, said point being referenced by an iron pin set which bears S 63° 59' 08" E a distance of 30.00 feet.

9) S 26° 00' 52" W a distance of 119.30 feet to a point thence leaving said road and with the lands of Bethany King as recorded in official records volume 1509 page 587 N 89° 08' 56" W a distance of 36.38 feet to a one inch iron pipe found thence with the lands of George Dent as recorded in official records volume 1855 page 199 the next four calls,

1) N 26° 45' 15" E a distance of 117.34 feet to a one inch iron pipe found.

- 2) N 30° 10' 02" E a distance of 167.66 feet to a one inch iron pipe found.
- 3) N 33° 02' 52" E a distance of 55.31 feet to an axle found.

4) N 83° 07' 19" W a distance of 220.54 feet to a one inch iron pipe found thence with the west line of said Lot 11 and with the lands of Berl E. Cavinee as recorded in official records volume 1920 page 658 N 01° 58' 24" E a distance of 1441.45 feet to the **BEGINNING** and containing 58.691 acres and being a part of the property conveyed in official records volume 1140 page 954 and being a part of auditors parcel # 42-50-03-24.

Subject to all leases or easements of record. Iron pins set are 5/8 inch rebar, 30 inches long capped "GARDNER PS-6884". Bearings are based on the grid meridian of the Ohio state plane south coordinate zone as determined by GPS observations. A survey of the above described property was made on April 7, 2005 by Steven L. Gardner, registered surveyor #6884.

APPROVED FOR CLOSURE 17-2005

EXEMPT FROM NNING COMMISSION naws

