Donna Carson to Todd Carson 7/3/91

Situated in the State of Ohio, County of Muskingum, Township of Newton, Township 15, Range 14, part of the Northeast Quarter of Section 19, part of Moore's Subdivision, Recorded in Plat Book 4, Page 147, bounded and described as follows:


Commencing at a concrete monument found on the West line of the Northeast Quarter of Section 19 from which the Southwest corner of the Northeast Quarter of Section 19 bears South 5° 40′ 00″ East 483.31 feet, passing the second monument at 123.00 feet; thence North 28° 48′ 48″ feet 349.28 feet to an iron pin found at the Southwest corner of Lot 4 of said Moore's Subdivision; thence along the South line of said subdivision North 39° 58′ 00″ East 175.79 feet to an iron pin set, the place of beginning; thence North 35° 57′ 56″ West 136.71 feet to an iron pin set on the North line of Lot 2; thence along the South line of a 12.00 foot wide alley North 39° 11′ 48″ East 86.06 feet to an iron pin set at the Northeast corner of Lot 1; thence South 30° 39′ 00″ East 141.80 feet along a 12.00 foot wide alley to an iron pin set; thence along the North line of Maysville Pike South 39° 58′ 00″ West 72.21 feet to the place of beginning, containing 0.241 acres more or less. Being Lot 1 ≈ 0.186 acres and 0.055 acres of Lot 2.

Being all of Parcel No. 47-47-56-01-01-000 and part of Parcel No. 47-47-56-01-02-000.

Bearings are based on the West line of the Northeast Quarter of Section 19 bearing North $05^{\rm O}$ ${\rm d}0^{\rm o}$ $00^{\rm o}$ West.


From pins set are No. 5 reinforcing bars 30 inches long with plastic L. D. caps.

Deed Reference: Deed Vol. 631, Page 202 and Deed Vol. 634, Page 5.



DESCRIPTION APPROVED FOR AUDITOR'S TRANSFER

7-8-9/



47-5601-03 001 47-5601-02 001

Donna Carson Etal. 7/3/91

Situated in the State of Chio, County of Muskingum, Township of Newton, Township 15, Range 14, part of the Northeast Quarter of Section 19, part of Moore's Subdivision, Recorded in Plat Book 4, Page 147, bounded and described as follows:

Commencing at a concrete Monument found on the West Line of the Northeast Quarter of Section 19 from which the Southwest corner of the Northeast Quarter of Section 19 bears South 5° 40′ 00° East 483.31 feet, passing the second concrete monument at 123.00 feet; thence North 28° 48′ 48″ that 349.28 feet to an iron pin found at the Southwest corner of Lot 1 of said Moore's Addition; thence along the South line of Lot 4′North 39° 58′ 00″ East 62.00 feet to an iron pin set at the Southwest corner of Lot 3, the place of beginning; thence North 29° 03′ 51″ West along Bell Telephone and the West Line of Lot 3 140.62 feet to an iron pin found; thence North 39° 11′ 48″ East along a 13.00 feet to an iron pin set, thence South 38° 57′ East 13. If feet to an iron pin set, thence South 38° 57′ East 13. If feet to an iron pin set on the South line of Lot 2 and the North line of Maysville Pike; thence along Maysville Pike South 39′ 58′ 00″ West H3.79 feet to the place of beginning, passing the Southwest corner of Lot 2 at 51.79 feet, containing 0.318 acres more or loss. Being Lot 3 : 0.186 acres and 0.132 acres of Lot 2.

Bearings are based on the West line of the Northeast Quarter of Section 19 bearing North $5^{\rm O}$ $40^{\rm O}$ $00^{\rm o}$ West.

From pins set are No. 5 reinforcing bars 30 inches long with plastic L. D. caps.

All of Parcel No. 47-47-56-01-03-000 and part of Parcel No. 47-47-56-01-02-000.

Deed Reference: Deed Vol. 631, Page 202 and Deed Vol. 634, Page 5.



R. L. Daniels Registered Surveyor No. 5410

DESCRIPTION APPROVED FOR AUDITOR'S TRANSFER

7-48-91