56-40-01-06-001 Linn Engineering, Inc. 7195 SAFLAUGH P.D



Civil Engineering Consultants 614-452-7434 · FAX 614-452-5198 534 Market Street • P.O. Box 2671 • Zanesville, Ohio 43702-2671

Situated in State of Ohio, Muskingum County, Salem Township, bounded and described as follows:

Being a part of Lot 3 and 4 of the Pirst Quarter Township, Township 2 North, Range 6 West of the United State Military Lands and being a part of the lands now owned by Craig and Dirk George as recorded in Muskingum County Deed Record 1100-591 and being more particularly described as follows:

Beginning for reference at the sonthwest corner of Lot 3 of the First Quarter Township, Township 2 North, Range 6 West of the United State Military Lands;

thence along the south line of said Lot 3 South 83 degrees 30 minutes 00 seconds East 1227.01 feet to the southeast corner of lands now owned by R. Ault (Deed Record 604-194) and the centerline of Township Road 180 (Sarbangh Road);

thence along said Ault's east line and said centerline North 01 degrees 00 seconds 12 minutes West 277.38 feet to the northeast corner of said Ault's lands;

thence along the centerline of Sarbaugh Road (TR-180) the following three courses:

- 1) North 07 degrees 35 minutes 15 seconds East 210.90 feet;
- 2) North 09 degrees 40 minutes 44 seconds East 302.73 feet;
- 3) North 11 degrees 23 minutes 29 seconds East 222.03 feet to the principal place of beginning;

thence North 77 degrees 26 minutes 27 seconds West 261.04 feet to an iron pin set, passing an iron pin set at 25.00 feet;

thence North 16 degrees 48 minutes 46 seconds West 587.86 feet to an iron pin set;

thence North 83 degrees 36 minutes 31 seconds East 474.22 feet to the centerline of said Sarbaugh Road, passing a point on the north line of Lot 3 at 293.25 feet, and passing an iron pin set at 453.82 feet;

thence along the centerline of said Sarbaugh Road (TR-180) the following four courses:

- South 01 degrees 39 minutes 44 seconds East 134.19 feet, passing a point on the north line of Lot 3 at 40.66 feet;
- 2) South 02 degrees 56 minutes 22 seconds West 321.90 feet;
- 3) South 06 degrees 43 minutes 38 seconds West 118.49 feet;
- 4) South 11 degrees 23 minutes 29 seconds West 100.99 feet to the principal place of beginning;

containing 5.34 acres, more or less, subject to all applicable right of ways and easements, written or implied.

Iron pins set are 5/8 inch diameter by 30 inch long rebar with plastic identification caps.

This description is written based on an actual field survey complet October 3, 1997 by Jack Newcome, Reg. No. 7321.

Jack D. Netcom Reg. No. 700

PARCEL NO:

Part of: 56-56 60-01-06-000 (5.26 ac.) Part of: 56-56 00-01-03-000 (0.08 ac.)



DESCRIPTION APPROVED FOR AUDITORS (TRANSFER
FOR AUDITORS ARANSFER
10-20-97

