

66-01-05-08-002 A

6. **S 85 degrees 55'16" E a distance of 835.04 feet** through the lands of said Alan L. and Lois M. Miller and along the centerline of said road to a railroad spike set;
7. **S 87 degrees 38'02" E a distance of 156.60 feet** through the lands of said Alan L. and Lois M. Miller and along the centerline of said road to a railroad spike set;
8. **S 07 degrees 46'44" W a distance of 245.92 feet** through the lands of said Alan L. and Lois M. Miller to an iron pin set passing over an iron pin set at a distance of 22.50 feet;
9. **S 35 degrees 35'04" W a distance of 239.07 feet** through the lands of said Alan L. and Lois M. Miller to an iron pin set;
10. **S 02 degrees 47'30" W a distance of 474.01 feet** through the lands of said Alan L. and Lois M. Miller to an iron pin set;
11. **N 87 degrees 32'20" W a distance of 1504.18 feet** along the quarter section line to the TRUE PLACE OF BEGINNING.

This parcel contains 33.387 acres and is subject to all highways, easements, and restrictions of record.

Bearings from – Grid North, Ohio State Plane Coordinate System, South Zone, NAD 83.

All iron pins set are 5/8 inch rebars with plastic identification cap marked "Galbraith 8703".

This survey was made and description prepared by Caleb Jerome Galbraith P.S. 8703. on April 3, 2020.

**OFFICE COPY
NOT RECORDABLE**

DESCRIPTION

APPROVED

By: *C. J. Galbraith*
5/14/20

