- 6. N 87 degrees 18'41" W a distance of 663.18 feet along the section line to a point witnessed by a 5/8 inch rebar found N 03 degrees 52'58" E a distance of 8.17 feet;
- 7. N 86 degrees 07'48" W a distance of 321.14 feet through the lands of said Frank D. Williams and Lillie A. Williams to a point witnessed by an iron pin set N 86 degrees 07'48" W a distance of 0.66 feet;
- 8. S 82 degrees 32'42" W a distance of 37.63 feet through the lands of said Frank D. Williams and Lillie A. Williams to a point on the section line;
- 9. N 87 degrees 18'41" W a distance of 93.69 feet along the section line to the TRUE PLACE OF BEGINNING.

This parcel contains 0.421 acres and is subject to all highways, easements, and restrictions of record.

To go to adjoiner only, Not to be used as a separate building site or transferred as an independent parcel in the future without planning commission approval in accordance with applicable subdivision regulations.

Bearings from - Grid North, Ohio State Plane Coordinate System, South Zone, NAD 83.

All iron pins set are 5/8 inch rebars with plastic identification cap marked "Galbraith 8703".

This survey was made and description prepared by Caleb Jerome Galbraith P.S. 8703. on June 3, 2021 FICE COPY

DESCRIPTION

By: 126/20hu

CALEB
JEROME
GALBRAITH
S-8703

PEGISTERED

SSIONAL SURVIVE