25-16-01-16-003

+- 12.82 Acres Adjoiner Split of Jinx Thompson's Lands in Hopewell Township

L

Situated in the State of Ohio, County of Muskingum, Township of Hopewell, Quarter Township 1, and being part of Lot 16, and Lot 17, Township 1, Range 9, United States Military Lands, and being part of the lands presently owned by Jinx A. Thompson, as per Official Record 2790 Page 925, and being more particularly described as follows:

Beginning for reference at an iron pin found at the southwest corner of Lot 16, Township 1, Range 9, United States Military Lands;

Thence along the south line of said Lot 16, and through the lands presently owned by Rex and Cassandra Smith, (OR 2795-516), South 87 degrees 28 minutes 45 seconds East, 1732.55 feet to an iron pin found on a south corner of lands presently owned by Jinx A. Thompson, (OR 2790-925), and the principal place of beginning;

Thence along the west line of said Thompson lands, and the east line of lands presently owned by Rex and Cassandra Smith, (OR 2795-516), North 55 degrees 51 minutes 31 seconds West, 726.47 feet to a point in the centerline of a 60 feet wide Ingress, Egress, and Utility easement, and being on the south line of lands presently owned by Shela M. Colegrove, (OR 2813-54), passing an iron pin found at 672.83 feet;

Thence along the south line of said Colegrove lands, and the centerline of said easement, the following two courses:

- 1.) South 89 degrees 51 minutes 41 seconds East, 62.35 feet to a point from which iron pins were found, North 05 degrees 33 minutes 29 seconds West, 30.15 feet, and South 05 degrees 33 minutes 29 seconds East, 30.15 feet;
- 2.) North 78 degrees 44 minutes 00 seconds East, 587.70 feet to a point on the southwest corner of lands presently owned by Jinx A. Thompson, (OR 2790-925), from which an iron pin found bears North 07 degrees 06 minutes 16 seconds East, 32.48 feet;

Thence continuing along the centerline of said easement, North 74 degrees 37 minutes 33 seconds East, 1016.47 feet to an iron pin set, on the west line of lands presently owned by the U.

- S. A.,(DR 494-235), passing the centerline of Pleasant Valley Road, (Co. Rd. 47) at 981.18 feet; Thence along the west lines of the U. S. A. the following nine courses:
- 1.) South 31 degrees 30 minutes 59 seconds West, 327.41 feet to a monument found, passing the centerline of Pleasant Valley Road at 92.83 feet;
- 2.) South 61 degrees 06 minutes 34 seconds West, 196.83 feet to an iron pin found;
- 3.) South 89 degrees 19 minutes 41 seconds East, 41.86 feet to a monument found;
- 4.) South 60 degrees 42 minutes 50 seconds West, 36.82 feet to a monument found;
- 5.) South 12 degrees 28 minutes 12 seconds West, 55.67 feet to a monument found;
- 6.) South 86 degrees 30 minutes 05 seconds West, 14.26 feet to a monument found;
- 7.) South 50 degrees 12 minutes 51 seconds West, 106.24 feet to an iron pin found;
- 8.) South 78 degrees 31 minutes 39 seconds West, 118.26 feet to an iron pin found;
- 9.) South 73 degrees 02 minutes 08 seconds East, 219.23 feet to a monument found on a north corner of lands presently owned by George V. Thompson, (OR 2620-879);

Thence along the north lines of said Thompson lands the following two courses:

1.) South 85 degrees 03 minutes 53 seconds West, 228.09 feet to an iron pin found;

25-16-01-16-003 A

2.) South 38 degrees 56 minutes 07 seconds West, 233.80 feet to an iron pin found on the most easterly corner of said Smith lands;

Thence along said Smith lands, North 87 degrees 28 minutes 44 seconds West, 295.83 feet to the principal place of beginning, containing 12.82 acres, more or less, and being part of Auditor's Parcel Numbers 25-16-01-16-000 +- 12.10 Acres, and 25-20-01-23-000 +- 0.72 Acres.

Appended to an subject to the above described tract is a reciprocating sixty feet wide, Ingress, Egress, and Utility Easement, the centerline of said easement being the north lines of the above described tract. For a complete description of said easement, see Official Record 2795-516, or Official Record 2813-54.

Note: The above described tract is not to be used as a separate building site or transferred as an independent parcel in the future without planning commission approval in accordance with applicable subdivision regulations.

Subject to all legal recorded easements and right of ways.

Iron pins set are 5\8 inch rears, 30 inches long, with plastic identification caps.

Bearings are based on the Ohio State Plane Coordinate System, NAD 83, South Zone, Grid North, as per GPS observations.

This description is written based on a field survey completed in Oct. 12, 2018 by Jack D. Newcome, Reg. No. 7321.

DESCRIPTION
APPROVED
By:

MUSKINGUM COUNTY
PLANNING COMMISSION DIRECTOR

Date

10-12-18

Date

10-12-18

Date

Date

10-12-18

Date

APPROVED SITUATED IN: MUSKINGUM COUNTY State of Ohio, County of Muskingum, Township of Hopewell, Quarter Township 1, and being part PLANNING COMMISSION DIRECTOR of Lot 16, and Lot 17, Township 1, Range 9, United States Military Lands 10 Jinx A. Thompson BASIS OF BEARINGS Date OR 2790-925 U. S. A. Fee Paid DR 494-235 Bearings are based on the Ohio State Plane Coordinate System, NAD 83, South Centerline of Pleasant Vailey Road Zone, Grid North, as per GPS 25-20-01-23-000 (Co. Rd. 47) R\W 40' observations. Shela M. Colegrove 60 ft. Wide, Ingress, OR 2813-54 35.29 REFERENCES Egress, and Utility Easement\ OR 2790-925 OR 2557-812 92.83 N 07°08'16"E N-74°37'33"E. DR 494-235 S 31°30'59"W 25-16-01-16-000 Dillon Topo -234.58 Maps U. S. A. N 05°33'29"W S 89°51'41"E N 78944'00"E DR 494-235 62.35 S 61°06'34"W PARCEL NO.S 196.83 Southwest. Part of: 25-16-01-16-000 +- 12.10 Acres 53.64 30.15 Part of: 25-20-01-23-000 +- 0.72 Acres Corner Rex and of Lot 16 (+- 0.03 Acres in R\W of Co. Rd. 47) Cassandra Smith S 38°56'07"W U. S. A. OR 2795-516 233.80 DR 494-235 \S 85°03'53"W 1732.55 LO1 16 N 87°28'44 S 87°28'45"E 228,09 Lot 25 Not to be used as a separate building 295.83 site or transferred as an independent Jinx A. Thompson parcel in the future without planning 25-30-13-03-000 LEGEND commission approval in accordance OR 2790-925 George V. Thompson with applicable subdivision regulations. OR 2620-879 +- 12.82 Acres Railroad Spike Set Iron Pin Found Stone Found JACK D. NEWCOME S-7321 SGISTERE SONAL SURJANIAN SONA DESCRIPTION Axle Found Iron Pipe Found Railroad Spike Found COURSE BEARING DISTANCE Iron Pin Set, 5/8" rebar S 89°19'41"E 41.86 Monument Found L-2 S 60°42'50"W 36.82 L-3 S 12°28'12"W 55.67 L-4 S 86°30'05"W 14.26 L-5 S 50° 12'51"W 106,24 118,26 L-6 S 78°31'39"W L-7 S 73°02'08"E 219.23 Newcome Surveying Company Jack D. Newcome Date 6515 Ballard Road Reg. Surveyor No. 7321 Nashport, Ohio Graphic Scale in Feet 1"= 400"

740-452-5796