## Re-Survey of Beatrice A. Blizzard Lands in Frazeysburg, Ohio

Situated in the State of Ohio, County of Muskingum, Township of Jackson, Village of Frazeysburg, Part of the Southeast Quarter of Section 19, Township 3, Range 9, United States Military Lands, and being all the lands presently owned by Beatrice A. Blizzard as per Official Record 2001, Page 565, and being more particularly described as follows:

Beginning for reference at the southeast corner of Lot 5, of Beard Subdivision, (Plat Book 9, Page 60);

Thence, (by H. Derwacter's survey), North 86 degrees 00 minutes 50 seconds West, 1048.93 feet to iron pin found;

Thence, (by H. Derwacter's survey), along the south line of Canal Street, South 43 degrees 47 minutes 01 seconds West, 817.59 feet to a point;

Thence, (by H. Derwacter's survey), continuing along the south line of Canal Street, South 45 degrees 24 minutes 48 seconds West, 164.80 feet to a point, from which an iron pin found bears North 34 degrees 13 minutes 16 seconds West, 8.98 feet, and being the principal place of beginning;

Thence along the west line of lands presently owned by Steven D. and Christine L. Wolford, (DR 1018-485), South 34 degrees 13 minutes 16 seconds East, 160.00 feet to an axle found on a corner of lands presently owned by Betty L. Myers, Family Living Trust, (OR 2193-874);

Thence along the north line of said Myers lands, South 45 degrees 24 minutes 48 seconds West, 75.18 feet to an axle found on the southeast corner of lands presently owned by Williams Management Group Inc.,(OR 1522-967);

Thence along the east line of said Williams Management Group Inc., (OR 1522-967), North 34 degrees 09 minutes 25 seconds West, 160.00 feet to a point, from which a railroad spike found bears North 20 degrees 34 minutes 58 seconds East, 1.29 feet;

Thence along the south line of Canal Street, North 45 degrees 23 minutes 19 seconds East, 75.00 feet to the principal place of beginning, containing 0.27 acres, more or less, and being all of Auditor's Parcel Number 29-62-03-15-000.

Subject to all legal recorded easements and right of ways.

Iron pins set are 5\8 inch rebars, 30 inches long, with plastic identification caps.

Bearings are based on the Ohio State Plane Coordinate System, NAD 83, South Zone, Grid North as per GPS observations.

This description is written based on a field survey completed Nov. 28, 2017 by Jack D. Newcome, Reg. No. 7321.

DESCRIPTION

Date

