

SITUATED IN:

State of Ohio, County of Muskingum, Township of Monroe, and being part of the West Half of the Northeast Quarter of Section 12, Township 3, Range 5, United States Military Lands

BASIS OF BEARINGS

Bearings are based on the Ohio State Plane Coordinate System, NAD 83, South Zone, Grid North, as per GPS observations.

REFERENCES

All deed records shown on this plat, and adjoining surveys of the area.

Iron Pin Found at the northeast corner of the West Half of the Northeast Quarter of the Section 12, T 3, R 5, U.S.M.L.

PARCEL NO.

All of: 42-60-12-02-000 +-52.18 Acres

COURSE	BEARING	DISTANCE
L-1	N 39°12'32"W	50.17'
L-2	N 01°57'14"E	30.04'
L-3	S 35°33'45"E	82.03'

Otsego Company LTD
OR 2077-288

Michael D. Shields
OR 2446-103



Otsego Company LTD
OR 2077-288
Part of Tract Two
+- 52.18 Acres

Holmes Limestone Company
DR 1151-674

Otsego Company LTD
OR 2077-288

LEGEND

- △ Railroad Spike Set
- Iron Pin Found
- ⊞ Stone Found
- Axle Found
- Iron Pipe Found
- ▲ Railroad Spike Found
- ⊙ Iron Pin Set, 5/8" rebar 30" Long
- ⊠ Monument Found

DESCRIPTION
APPROVED

By: MW 12-6-2022

Mark E. Watson, and
Carol S. Bisonnette
Watson
OR 2041-359

N 88°06'36"W 1312.27'

Otsego Company LTD
OR 2077-288

Holmes Limestone Company
DR 1151-674



OFFICE COPY
NOT RECORDABLE

Reg. Surveyor No. 7321

Newcome Surveying Company
6515 Ballard Road
Nashport, Ohio
740-402-0790