

C4	C5
R=977.57'	R=1700.98'
A=38.87'	A=210.43'
Ch=S 12°08'46" W	Ch=S 19°40'27" W
Lc=38.87'	Lc=210.30'

SCHMACK BIOMASS OF
ZANESVILLE, LLC
OR 2249-229

MAYSVILLE REGIONAL
WATER DISTRICT
OR 1854-529
47-70-20-16-000

C1	C2	C3
R=1990.55'	R=1760.98'	R=1037.57'
A=100.98'	A=263.33'	A=51.45'
Ch=N 54°16'20" E	Ch=N 20°21'56" E	Ch=N 11°56'50" E
Lc=100.97'	Lc=263.08'	Lc=51.44'

MAYSVILLE REGIONAL
WATER DISTRICT
OR 1854-529
47-66-01-01-000

P.P.O.B.
IRON PIN SET
3.133 ACRE TRACT

MAYSVILLE REGIONAL
WATER DISTRICT
OR 1854-529
Part: 47-70-20-16-000
±3.133 ac.

MAYSVILLE REGIONAL
WATER DISTRICT
OR 1854-529
47-70-20-16-000

MAYSVILLE REGIONAL
WATER DISTRICT
OR 1854-529
All: 47-70-20-16-001
±0.500 ac.

MAYSVILLE REGIONAL
WATER DISTRICT
OR 1854-529
47-66-01-01-001

MAYSVILLE REGIONAL
WATER DISTRICT
OR 1854-529
Part: 47-70-20-16-000
±5.483 ac.

APPROVED
MUSKINGUM COUNTY
PLANNING COMMISSION DIRECTOR

Fee Paid

Date

LINE	BEARING	DISTANCE
L1	S 09°31'33" W	90.16'
L2	S 12°47'32" W	15.41'
L3	S 11°41'05" W	32.53'
L4	S 10°41'27" W	97.26'
L5	S 06°35'09" W	16.38'
L6	S 03°48'38" W	16.93'
L7	S 00°32'45" W	16.45'
L8	S 02°09'56" E	32.98'
L9	S 02°59'25" E	32.69'
L10	S 00°26'18" E	16.13'
L11	S 01°09'55" W	31.47'
L12	S 06°05'29" W	31.36'
L13	S 20°58'24" W	31.22'
L14	S 21°42'32" W	49.97'
L15	S 15°32'06" W	13.74'
L16	S 02°49'33" W	42.97'
L17	S 20°42'05" W	26.62'
L18	S 13°26'35" W	16.54'
L19	S 01°40'14" W	48.39'
L20	S 02°11'27" E	51.07'
L21	S 05°33'43" E	62.45'
L22	S 08°13'03" E	46.61'
L23	S 02°34'37" E	13.42'
L24	S 00°04'20" W	43.20'
L25	S 07°11'28" E	31.07'
L26	S 00°13'40" W	15.71'
L27	S 26°14'50" W	29.47'
L28	S 15°26'43" W	47.82'
L29	S 07°35'04" W	14.58'
L30	S 03°46'15" E	14.11'
L31	S 08°42'02" E	30.86'
L32	S 04°53'14" E	28.44'
L33	S 03°58'17" W	12.54'
L34	S 12°13'54" W	15.72'
L35	S 22°03'30" W	13.64'
L36	S 38°27'04" W	13.73'
L37	S 55°10'08" W	31.28'
L38	S 56°51'58" W	13.16'
L39	S 45°30'28" W	14.64'
L40	S 37°57'16" W	15.29'
L41	S 31°08'57" W	16.91'
L42	S 18°57'08" W	15.87'
L43	S 14°05'56" W	30.62'
L44	S 32°39'25" W	15.35'
L45	S 35°13'55" W	31.26'
L46	S 31°43'45" W	15.83'
L47	S 19°28'18" W	16.16'
L48	S 04°58'56" W	16.77'
L49	S 00°45'20" E	16.57'
L50	S 10°47'20" E	16.70'
L51	S 22°07'38" E	17.61'
L52	S 26°22'54" E	88.44'
L53	S 16°32'16" E	19.74'
L54	S 00°31'07" E	36.35'
L55	S 21°37'01" W	34.39'
L56	S 12°17'52" W	48.90'
L57	S 25°53'51" W	37.09'
L58	S 22°18'20" W	21.72'
L59	S 13°16'02" W	24.45'
L60	S 19°09'03" W	127.00'

PARCEL NUMBER

All of: 47-70-20-16-001 ± 0.500 ac.
Part of: 47-70-20-16-000 ± 5.483 ac.
Part of: 47-70-20-16-000 ± 3.133 ac.

SITUATED IN


the Southwest Quarter of Section 20,
T-15, R-14, Congress Lands East of
the Scioto River, Newton Township,
Muskingum County, Ohio.

LEGEND

- Iron Pin Set, 5/8" rebar w/cap
- Iron Pin Found
- ◆ Concrete Monument Found w/iron pin
- ◆ Drill Steel Found
- △ PK Nail Set

BASIS OF BEARINGS

Bearings are based on NAD 83,
Ohio State Plane Coordinate
System, South Zone, Grid South,
as per GPS observations made on
November 8, 2018.



**OFFICE COPY
NOT RECORDABLE**

Timothy H. Linn, PS
Reg. Surveyor No. 7113

Date

DESCRIPTION
APPROVED
By: *[Signature]*

Revision	Description	Date
Drawn by: JAP		
Checked by: THL		
Scale: 1"=200'	Sheet No. 1 of 1	

MAYSVILLE REGIONAL WATER DISTRICT
SOUTHWEST QTR. SECTION 20
NEWTON TOWNSHIP

Linn Engineering, Inc. 740-452-7434
Civil Engineering Consultants
P.O. Box 2086 Zanesville, Ohio 43702-2086

Reduced copy, not to scale, Larger
copy available in the Muskingum
County Engineer's Map Dept.