Biedenbach Engineering, Inc.

3975 East Pike Zanesville, OH 43701 Civil Engineering and Land Surveying

Telephone (740) 453-4850 Fox (740) 450-1000 E-mail bledenbuch (9ee.nel

CARDL GOPF ALL
AUDITORS PARCEL NUMBER 73-73-36-01-12-000 (PART)-36.578 ACRES
AUDITORS PARCEL NUMBER 73-73-36-01-14-000 (PART)-10.212 ACRES

BEING A PART OF THE NORTHEAST QUARTER AND THE SOUTHEAST QUARTER OF SECTION 14. TOWNSHIP 12, RANGE 13, OF THE CONGRESS LANDS EAST OF THE SCIOTO RIVER, WAYNE TOWNSHIP, MUSKINGUM COUNTY, OHIO AND BEING FURTHER DESCRIBED AS FOLLOWS:

COMMENCING AT THE NORTHWEST CORNER OF THE SAID SOL/THEAST QUARTER OF SECTION 14;

THENCE WITH THE NORTH LINE OF THE SAID SOLVEPAST QUARTER NORTH BY DEGREES 36 MINUTES 55 SECONDS EAST 732.02 FEET TO AN EXISTING IRON PIN (5/8 INCH REBAR), SAID IRON PIN BEING THE PLACE OF BEGINNING OF THE TRACT HEREIN INTENDED TO BE DESCRIBED;

THENCE CONTINUING WITH THE SAID NORTH LINE, NORTH 89 DECREES 56 MINUTES 55 SECONDS EAST 593.77 FEET TO AN EXISTING IRON PIN (5/8 INCH REBAR):

THENCE LEAVING THE SAID NORTH LINE AND WITH THE EAST LINE OF TRACTS CONVEYED TO J. AND S. McFERREN (DEED VOLUME 577, PAGE 596) AND H. AND E. RITTBERGER (DEED VOLUME 437, PAGE 459), NORTH OF DEGREES OF MINISTES 19 SECONDS WEST 1355.68 FEET TO A POINT, PASSING AN EXISTING IRON PIN (5/8 INCH REBAR) AT 353,92 FEET AND AN EXISTING IRON PIN (5/8 INCH REBAR) AT 1331.48 FEET;

THENCE WITH THE SOUTH LINES OF TRACT'S CONVEYED TO W. HAYES (DEED VOLUME 806, PAGE 26), K. MAIJIZ (DEED VOLUME 1004, PAGE 423) AND F. AND C. SCHNEIDER (DEED VOLUME 1023, PAGE 441), NORTH 89 DEGREES 51 M(NUTES 50 SECONDS EAST 1315.48 FEET TO AN EXISTING IRON PIN (5/8 INCH REBAR), PASSING EXISTING IRON PINS (5/8 INCH REBAR) AT 426.60 AND 872.63 FEET;

THENCE WITH THE EAST LINE OF SECTION 14, SOUTH 00 DEGREES 35 MINUTES 00 SECONDS EAST 950.89 FEET TO AN IRON PIN SET;

THENCE WITH THE NORTH LINE OF A 5.001 ACRE TRACT, SOUTH 89 DEGREES 25 MINUTES 00 SECONDS WEST 484.92 FEET TO AN IRON PIN SET:

THENCE WITH THE WEST LINE OF THE SAID 5.001 ACRE TRACT AND A 3.143 ACRE TRACT, SOUTH 00 DEGREES 35 MINUTES 60 SECONDS EAST 729.52 FEET TO A POINT IN THE CENTER OF TOWNSHIP ROAD 449 (ELLERMAN ROAD), PASSING AN IRON PIN SET (5/8 INCH REBAR) AT 699.52 FEET;

THENCE WITH THE CENTER OF SAID ROAD THE NEXT 8 COURSES AND DISTANCES:

- I. SOUTH 89 DEGREES 24 MINUTES 20 SECONDS WEST 556.09 FEET TO A POINT,
- 2. SOUTH 89 DEGREES 56 MINUTES 54 SECONDS WEST 205.91 FEET TO A POINT,
- 3. NORTH 88 DEGREES 17 MINUTES 03 SECONDS WEST 52.32 FEET TO A POINT,
- 4. NORTH 85 DEGREES 04 MINUTES 45 SECONDS WEST 48.20 FEET TO A POINT,
- NORTH 82 DEGREES 44 MINUTES 34 SECONDS WEST 283.54 FEET TO A POINT,
 NORTH 79 DEGREES 06 MINUTES 45 SECONDS WEST 58.53 FEET TO A POINT,
- 7. NORTH 69 DEGREES 14 MINUTES 39 SECONDS WEST 78.27 FEET TO A POINT,
- 8. NORTH 57 DEGREES 41 MINUTES 47 SECONDS WEST 199.03 FEET TO A POINT,

THENCE LEAVING THE SAID ROAD AND WITH THE EAST LINE OF A 6.009 ACRE TRACT CONVEYED TO C. BAUGHMAN (DEED VOLUME 1050, PAGE 52B), NORTH 00 DEGREES 26 MINUTES 38 SECONDS EAST 145.20 FEET TO THE PLACE OF BEGINNING, PASSING AN EXISTING IRON PIN (5/8 INCH REBAR) AT 25.05 FEET.

CONTAINING 46.790 MORE OR LESS ACRES TOTAL WITH 10.212 MORE OR LESS ACRES IN THE SOUTHEAST QUARTER AND 36.578 MORE OR LESS ACRES IN THE NORTHEAST QUARTER. SUBJECT TO ALL LEGAL ROAD RIGHT OF WAYS OF TOWNSHIP ROAD 449 (ELLERMAN ROAD) AND ALL OTHER APPLICABLE EASEMENTS.

ALL IRON PINS SET ARE 5/8 INCH X 30 INCH REBAR WITH PLASTIC IDENTIFICATION CAPS (BIEDENBACH PS:1718-PS:6923).

THE BEARINGS ARE BASED ON THE PREVIOUS SURVEY OF 135.341 MORE OR LESS ACRES CONVEYED TO CAROL GOFF (DEED VOLUME 1144, PACE 905).

1 HEREBY CERTIFY TO THE BEST OF MY KNOWLEDGE AND BELIEF THE SURVEY AND DESCRIPTION TO BE CORRECT AS PREPARED BY ME, THIS 23RD DAY OF OCTOBER 2001.

OFFICE COPY ME, THIS 23RD DAY OF OCTOBER 2001.

MINITED U. MCTOLS
REGISTERED SURVEYOR 6923

POR AUDITOR'S TRANSFER

10-20-2001

SURVEY FOR CAROL GOFF AUDITORS PARCEL NUMBER 73-73-36-01-12-000 (ALL) - 36.578 ± ACRES 73-73-36-01-14-000 (PART) - 10.212 ± ACRES BEING A PART OF THE NORTHEAST QUARTER AND THE SOUTHEAST QUARTER OF SECTION 14, TOWNSHIP 12, RANGE 13. OF THE CONGRESS LANDS EAST OF THE SCIOTO RIVER, WAYNE TOWNSHIP, MUSKINGUM BEARINGS ARE BASED ON THE PREVIOUS SURVEY OF 135.341 MORE OR LESS ACRES CONVEYED TO CAROL GOFF (DEED VOLUME 1144, PAGE 905). G. & T. NEWSOM VOL. 1084, PG. 391 WAYNE F VOL. 806. 1315.48 N₁89°51'50"E. 800 446.03 442.65 426.60 C. SCHNEIDER 949, PG. 202 B" REBAR $\frac{6}{4}$ LIN<u>E</u> DATA 8/9 DISTANCE No. BEARING 950.89 556.09 HARRY F. & EVELYN S.89 24'20 W. 1355.88 RITTRERGER S.89 56 54 W. 205.91 701 VOL. 437, PG. 459 3 N.88°17'03°W. 52.32 00°35'00'E. N.85°04'45"W. 48.20 4 N.82 44 34 W. 283.54 5 N.79'06'45 W. 58.53 9 N.69 14 39 W. 78.27 N.57 41 47 W. 199.03 7 SECTION 00.00 N.00°26'38 E. 145.20 JAMES L. & EILEEN B. ROBERT ELLERMAN VOL. 1111, PG. 483 S.89°25'00 MeFERREN 484.92 VOL. 577, PG. 596 AREA ! 46.790 ± ACRES (TOTAL) 35'00'E. P.O.B., N.89°56'55 E. MID SECTION LINE N.89*56'55"E. 732.02" 90 5/8" REBAR -120.15628 ທ 25.05 8 BAUCHHAN 1050, PG. 6 Ç TOWNSHIP ROAD 449 -30 0 (ELLERMAN ROAD) Ø6 *₫*③ 1 90FF N. S. 8/3 LEGENDRESEARCH: VOL. 1058, PG. 284 VOL. 1023, PG. 441 EXISTING IRON PIN VOL. 1004, PG. 424 IRON PIN SET 905 VOL. 1144, PG. (5/8" REBAR W/CAP) VOL. 1023, PG. 441 VOL. 891, PG. 317 VOL. 934, PG. 270 PG441 o ANGLE POINTS MUSKINGUM CO. TAX MAP • EXISTING STONE 3/4" PEE DESCRIPTION APPROVED FOR AUDITORISTRANSFER ROBERT ELLERMAN VOL. 1111, PG. 483 BIEDENBACH ENGINEERING, INC. 10-30-2001 ZANESVILLE, OHIO (740) 453-4850

I HEREBY CERTIFY TO THE BEST OF MY KNOWLEDGE AND BELIEF THE ABOVE PLAT AND SURVEY OF GORRECT AS PREPARED BY ME, THIS 23FT DAY IN STORMS 2001.

COUNTY, OHIO.

SCALE 1"=400"

200

6

NORTHWEST SOUTHEAST SECTION 14

COUNTY LA

QUARTER SECTION LINE

ó

100

MOT RECORD REGISTERED SURVEYOR #8923

DRAWN BY:	DATE:
AJS	10-23-01
SCALE:	CHECKED BY:
1"=400'	WJB
JOB NO:	DRAWING NO:
4535	D:\4535\4535A