LOCATION MAP

LATITUDE: 39°56'56" LONGITUDE: -82°01'51"

0

0

0

0

THE LOCATION OF THE UNDERGROUND UTILITES SHOWN ON THE PLANS ARE OBTAINED FROM THE OWNER OF THE UTILITIES AS REQUIRED BY SECTION 153.64 O.R.C.

## UTILITY OWNERS

LISTED BELOW ARE ALL UTILITIES LOCATED WITHIN THE PROJECT CONSTRUCTION LIMITS TOGETHER WITH THEIR RESPECTIVE OWNERS:

ATRT 160 NORTH SIXTH ST. ZANESVILLE, OHIO 43701 ATTN: BARRETT TAMASOVICH ATTN: PAUL MILLS 740-454-3552 BT2178@ATT.COM

MDCARR@AEP.COM

CITY OF ZANESVILLE 14 BUCKEYE DRIVE ZANESVILLE, OHIO 43701 740-455-0631 EXT. 2 PAUL .MILLS@COZ.ORG

AMERICAN ELECTRIC POWER CO. (TRANSMISSION) 700 MORRISON RD. GAHANNA. OHIO 43230 ATTN: MIKE CARR 614-552-1893

CITY OF ZANESVILLE, DIVISION OF WASTE WATER 1730 MOXAHALA AVENUE ZANESVILLE, OHIO 43701 ATTN: SCOTT BROWN 740-455-0641 SCOTT.BROWN@COZ.ORG

AMERICAN ELECTRIC POWER (DISTRIBUTION) 850 TECH CENTER DRIVE GAHANNA, OHIO 43230 ATTN: PAUL PAXTON 614-883-6831 PTPAXTON@AEP.COM

# CONVENTIONAL SYMBOLS

Township Line ————— Edge of Shoulder (Ex) Edge of Shoulder ( Pr) -Ditch / Creek (Ex)-Center Line -Ownership Hook Symbol Z , Example Z Right of Way (Ex) \_\_\_\_\_ Ex R/W \_\_\_\_\_ Property Line Symbol & , Example -Break Line Symbol V , Example -Tree (Pr) ♥ , Tree (Ex) ♥ , Shrub (Ex) ♥ Tree (Remove) ▼ , Shrub (Remove) ▼ Slope Ease.(Ex) — Ex SL — — — — Evergreen (Ex) , Stump 
Evergreen (Remove) , Stump (Remove) Slope Ease (Pr) - SL -Temporary Right of Way-TMP-Wetland (Pr) لا , Grass (Pr) علا , Aerial Target& Channel Ease. (Pr) \_\_\_\_ СН \_\_\_\_ Post (Ex) O , Mailbox (Ex) 506 , Mailbox (Pr) 100 Utility Ease. (Ex) ------Ex U ------Light (Ex) ☼ , Telephone Marker (Ex)+TEL Fire Hydrant (Ex) 六 , Water Meter (Ex) 麗 Water Valve (Ex.) . Utility Valve Unknown (Ex.) Construction Limits --------Telephone Pole (Ex) \$\overline{\phi}\$, Power Pole (Ex) \$\overline{\phi}\$ Edge of Pavement (Ex) -----Light Pole (Ex) \$\phi\$ Edge of Pavement (Pr) -

RESIDENTIAL

COMMERCIAL

# STRUCTURE KEY

OUT-BUILDING

CH = CHANNEL EASEMENT

LA = LIMITED ACCESS EASEMENT SH = STANDARD HIGHWAY EASEMENT SL = SLOPE EASEMENT T = TEMPORARY EASEMENT

RIGHT OF WAY

LEGEND SHEET

MUS-70-10.49

MUSKINGUM COUNTY

CITY OF ZANESVILLE

FALLS TOWNSHIP

QTR. TWP. 4, T1N, R8W

WASHINGTON TOWNSHIP

QTR. TWP. 3,T1N, R7W

U.S.M.L.

INDEX OF SHEETS:

### PROJECT DESCRIPTION

REMOVAL AND REPLACEMENT OF EXISTING CONCRETE AND ASPHALT CONCRETE MAINLINE AND RAMP PAVEMENT AND DETERIORATED SUBGRADE. REPLACEMENT OF MEDIAN BARRIER, LIGHTING, DRAINAGE SYSTEM, GUARDRAIL, AND SIGNING. FOURTEEN BRIDGES REHABBED OR REPLACED AND ONE BRIDGE REMOVED AND FILLED IN.

### PROJECT CONTROL

ODOT VRS DERRIVED: PROJECT GROUND COORDINATE SYSTEM, RELATIVE TO NAD83(2011) STATE PLANE OHIO SOUTH ZONE 3402 SCALED ABOUT THE ORIGIN BY A PROJECT ADJUSTMENT FACTOR OF 1.00004436. ORTHOMETRIC HEIGHTS ARE RELATIVE TO NAVD88,

### PLAN PREPARED BY:

FIRM NAME: ODOT, DISTRICT 5 PLANS PREPARED BY: CANDY SHOEMAKER FIELD REVIEW BY: LUKE WALKER & CANDY SHOEMAKER OWNERSHIP VERIFIED BY: LUKE WALKER DATE COMPLETED: 3/19/2020

## UNDERGROUND UTILITIES Contact Two Working Days Before You Dig



OHIO811, 8-1-1, or 1-800-362-2764 (Non-members must be called directly)

I, hereby certify that this plat is prepared under the direction and supervision of Luke Walker, P.S. #8701 for the Ohio Department of Transportation, and is based on a survey performed for the Ohio Department of Transportation in 2018 & 2019 by Buckley Group under the supervision of Robert C. Canter, P.S. #7226. The results of that survey are contained herein.

Underground utility locations are shown for informational purposes only. Though they are believed to be accurate, their location is as marked on the ground by the utility company per OHIO8II Confirmation Numbers A814900256-00A, A814900312-00A, A814900333-00A, A814900352-00A, A814900361-00A, A814900379-00A, B811700397-00B, B811700415-00B, B811700432-00B, B811700440-00B, B811700465-00B, and those markings subsequently being surveyed as a part of this project.

The horizontal geometry expressed herein is based on ODOT VRS derived; Project Ground Coordinate System, relative to NAD83(2011) State Plane Ohio South Zone 3402 scaled about the origin by a project adjustment factor of 1.00004436. Orthometric heights are relative to NAVD88, GEOID 12A.

As a part of this project I have reestablished the locations of the existing property lines and centerline of existing Right of Way for property takes contained herein.

As a part of this project [ have established the proposed property lines, calculated the Gross Take, present roadway occupied (PRO), Net Take and Net Residue; as well as prepared the legal descriptions necessary to acquire the parcels as shown herein.

As a part of this work I have set monuments at the proposed property corners, and other The iron pins and caps will be 3/4" x 30" rebar with aluminum cap stamped 'ODOT R/W Distribution work contained herein was conducted in accordance with Ohio Administrative Code 433-370 "A Minimum Standards for Boundary Surveys in the State of Ohio" unless so noted.

The words I and my as used herein are to mean that either myself or someone working under my direct supervision.

ommonly known as WALKER S-8701

93006

E1807

A H Ψ

GHT G E =

Ö

-5