

**Revised DRAFT FOR REVIEW**



# MUS-CR66-0005, PID No. 101730 BRIDGE OVER MUSKINGUM RIVER STRUCTURE TYPE STUDY

Dated: September 2019



*Prepared For:*



155 Rehl Road  
Zanesville, Ohio 43701  
Phone - 740-454-0155  
Fax - 740-455-7180

Mark J. Eicher, P.E., P.S. - Muskingum County Engineer

Engineer@mceo.org

*Prepared By:*



ADR & Associates, Ltd.  
88 West Church Street  
Newark, Ohio 43055  
(740) 345-1921







# TABLE OF CONTENTS

**PREFACE** ..... iii

**EXECUTIVE SUMMARY** ..... iii

**INTRODUCTION** ..... 1

    GENERAL PROJECT DESCRIPTION ..... 1

    PROJECT BACKGROUND ..... 1

    SERVICES NOT INCLUDED..... 1

**LOCATION** ..... 2

    PROJECT VICINITY MAP ..... 2

    PROJECT LOCATION MAP ..... 2

**EXISTING CONDITIONS** ..... 3

    EXISTING ROADWAY DESCRIPTION..... 3

        EXISTING TRAFFIC DATA..... 3

    EXISTING BRIDGE DESCRIPTION..... 3

        EXISTING STRUCTURE DATA ..... 3

    AVAILABLE RECORD PLANS AND RECORD INFORMATION ..... 3

**DESIGN CONSIDERATIONS**..... 4

    ROADWAY ..... 4

        ROADWAY DESIGN CRITERIA ..... 4

        PROPOSED HORIZONTAL ALIGNMENT ..... 4

        PROPOSED VERTICAL ALIGNMENT..... 4

        PEDESTRIAN SIDEWALKS ..... 4

    MAINTENANCE OF TRAFFIC..... 4

        ROADWAY TRAFFIC: ..... 4

        MARINE TRAFFIC:..... 4

BRIDGE DECK AND ROADWAY DRAINAGE ..... 4

PROPOSED STRUCTURE ..... 4

    PROPOSED STRUCTURE DATA ..... 4

    PROPOSED BRIDGE TRANSVERSE SECTION ..... 4

CLEARANCES ..... 5

    MINIMUM VERTICAL NAVIGATIONAL CHANNEL CLEARANCE..... 5

    MINIMUM HORIZONTAL NAVIGATIONAL CHANNEL CLEARANCE ..... 5

STREAM HYDRAULICS ..... 5

    AVAILABLE STREAM DATA ..... 5

    DESIGN FREQUENCY ..... 5

    FLOOD ZONE ..... 5

**STRUCTURE CONSIDERATIONS** ..... 6

    PROPOSED STRUCTURE ..... 6

    NO-BUILD ALTERNATIVE ..... 6

    PRESTRESSED CONCRETE I-BEAMS ALTERNATIVE ..... 6

    APPROACH SPANS (SPANS 1, 2 & 7) ALTERNATIVE..... 6

    20 FEET WIDE TRUSS (SPANS 3 THRU 6) ALTERNATIVE ..... 6

    24 FEET WIDE TRUSS (SPANS 3 THRU 6) ALTERNATIVE ..... 6

    ROLLED BEAM (SPANS 3 THRU 6) ALTERNATIVE..... 6

    20 FEET WIDE STEEL PLATE GIRDERS (SPANS 3 THRU 6) ALTERNATIVE ..... 7

    24 FEET WIDE STEEL PLATE GIRDERS (SPANS 3 THRU 6) ALTERNATIVE ..... 7

    PROPOSED BRIDGE DESIGN FEATURES ..... 7

        PROPOSED RAILING ..... 7

        GALVANIZED STRUCTURAL STEEL ..... 7

        PROPOSED JOINTS ..... 7

        UTILITIES ON BRIDGE ..... 7

    CAUSEWAY VERSES BARGES ..... 8

        CAUSEWAY ..... 8

        BARGES ..... 8

    CORROSION PROTECTION – STEEL GIRDERS..... 8

        PAINTED STEEL ..... 8

        GALVANIZED STEEL ..... 8

        WEATHERING STEEL..... 8



MUS-CR66-0005, PID No. 101730, Bridge over Muskingum River  
STRUCTURE TYPE STUDY



CORROSION PROTECTION LIFESPAN ..... 8  
 CORROSION PROTECTION CONCLUSION ..... 8  
 GIRDER WEB THICKNESS ..... 9

**SUMMARY OF CONSTRUCTION COSTS ..... 9**

CONSTRUCTION COST COMPARISONS ..... 9  
 TRUSS REPLACEMENT COSTS ..... 9  
 APPROACH SPANS ROLLED STEEL beams, 20' Wide, SPANS 1, 2 & 7, COSTS..... 9  
 APPROACH SPANS ROLLED STEEL beams, 24' Wide, SPANS 1, 2 & 7, COSTS..... 9  
 STEEL PLATE GIRDER, 20' WIDE, SPANS 3 THRU 6, COSTS ..... 9  
 STEEL PLATE GIRDER, 24' WIDE, SPANS 3 THRU 6, COSTS ..... 9  
 COST COMPARISON SUMMARY ..... 9  
**LIFE CYCLE COSTS..... 9**  
 BREAKDOWN OF LIFE CYCLE COSTS.....10  
 SUMMARY OF LIFE CYCLE COSTS .....10

**CONCLUSIONS AND RECOMMENDATIONS .....10**

RECOMMENDED PREFERRED ALTERNATIVE..... 10

**APPENDIX .....11**

APPENDIX A: PRELIMINARY PLANS ..... 11  
 APPENDIX B: COST ESTIMATES ..... 11  
 APPENDIX C: HYDRAULIC DATA..... 11  
 APPENDIX D: EXISTING PLANS ..... 11



## PREFACE

This document was prepared in August 2019.

### Prepared For:



155 Rehl Road  
Zanesville, Ohio 43701  
Phone - 740-454-0155  
Fax - 740-455-7180

Mark J. Eicher, P.E., P.S. - Muskingum County Engineer

Engineer@mceo.org

### Prepared By:



ADR & Associates, Ltd.  
88 West Church Street  
Newark, Ohio 43055  
(740) 345-1921

Justin Hartfield, PE

Date

## EXECUTIVE SUMMARY

ADR & Associates, Ltd. (ADR) has prepared this MRS-CR66-0005 (Gaysport Bridge) Structure Type Study for the Muskingum County Engineer's Office. This report is one component of the Preliminary Engineering Process for this project.

The purpose of the MUS-CR66-00.05, PID No. 101730 project is to replace the structurally deficient existing bridge superstructure on the Gaysport bridge (C.R. 66 a.k.a. North Street) over the Muskingum River (SFN 6031307) using the existing bridge substructures. This structure type study evaluates the project site to determine the best bridge superstructure replacement alternative.

The roadway horizontal and vertical alignment are intended to be maintained or slightly improved over the existing conditions. The replacement bridge superstructure low chord was not lowered below the existing bridge low chord elevation so there will be no adverse impacts to the 100-year storm elevation (Base Flood Elevation). The bridge will have a vertical profile set to accommodate 25 MPH two-lane, two-way traffic. There is some room to adjust the profile down thereby improving the profile.

Traffic will need to be detoured for construction because it is not practical or cost effective to reconstruct the bridge part width, to construct a replacement bridge in a new location, or to construct a temporary bridge. Maintaining marine traffic or closing to marine traffic will be dependent on the process for the demolition of the existing superstructure and the construction of the proposed superstructure.

Since the existing substructure was determined to be reused by the Muskingum County Engineer, no alternative evaluation of the substructure was necessary.

The following replacement superstructures were considered.

- Doing nothing (No-Build)
- Four truss spans with rolled steel beam approach spans with a width of 20 feet f/f rail
- Four truss spans with rolled steel beam approach spans with a width of 24 feet f/f rail
- Four steel plate girder spans with rolled steel beam approach spans with a width of 20 feet f/f rail
- Four steel plate girder spans with rolled steel beam approach spans with a width of 24 feet f/f rail
- Prestressed concrete I-beams

The recommended preferred replacement superstructure alternative is to use four lines of galvanized rolled steel beams for spans 1, 2 & 7 and four lines of galvanized constant depth steel plate girders for spans 3 through 6 with 24 feet wide face/face rail reinforced concrete deck with TST railing and over the side drainage. The steel plate girders are proposed to have a depth of between 50" to 52" with an 8.5" composite concrete deck and 2" haunches that will not decrease the low chord elevation of the bridge.

The substructure abutments and piers will have caps replaced with reinforced concrete and new bearings. Abutments will be semi-integral with new approach slabs. Link slab joints are proposed between spans 2 & 3 and between spans 6 & 7. Barges with cranes will be more cost effective and of lower risk than constructing a causeway to demolish the existing bridge superstructure and portions of the substructure and to construct the proposed bridge superstructure.

The preliminary estimated construction cost for the recommended preferred alternative is \$5.98 million.





# INTRODUCTION

## GENERAL PROJECT DESCRIPTION

The purpose of the MUS-CR66-00.05, PID No. 101730 project is to replace the structurally deficient existing bridge superstructure on the Gaysport bridge over the Muskingum River (SFN 6031307) using the existing bridge substructures. This structure type study evaluates the project site to determine the best bridge superstructure replacement alternative.

## PROJECT BACKGROUND

The Muskingum County Engineer employed ADR & Associates, Ltd. (ADR) to provide a structure type study to replace the superstructure for the existing bridge structure on County Road 66 over the Muskingum River.

Based on bridge inspections performed by the Muskingum County Engineer's Office, the Muskingum County Engineer made the determination that the existing bridge superstructure needed to be replaced and that the existing bridge substructure could be salvaged. Therefore, alternatives that require removing and relocating the bridge or permanently closing and removing the bridge are not considered.

The existing bridge has been signalized to allow only one-lane of two-way traffic on the bridge.

## SCOPE OF SERVICES FOR THE STRUCTURE TYPE STUDY

ADR's scope of services includes:

- Performing a structure type study per Section 201 of the Bridge Design Manual (BDM).
- Salvaging and reusing the existing substructure except that the pier and abutment caps are to be specified to be replaced and preliminarily designed as appropriate for each alternative.
- Evaluating and preliminarily developing the following superstructure type alternatives:
  - No build
  - Four truss spans with rolled steel beam approach spans with a width of 20 feet f/f rail
  - Four truss spans with rolled steel beam approach spans with a width of 24 feet f/f rail
  - Four steel plate girder spans with rolled steel beam approach spans with a width of 20 feet f/f rail
  - Four steel plate girder spans with rolled steel beam approach spans with a width of 24 feet f/f rail
  - Prestressed concrete I-beams
- Using TST bridge railing with over the over the side drainage in lieu of using concrete parapets.
- Specifying the bridge spans are to be numbered from west to east.
- Using continuous rolled steel beams for bridge spans 1-2.
- Using simple rolled steel beams for bridge span 7.
- Analyzing and providing preliminary designs for:
  - Continuous rolled beams, spans 1 & 2
  - Continuous plate girders, spans 3 thru 6
  - Simple rolled beam, span 7

- Using the criteria for deflection as specified in AASHTO LRFD Bridge Design Manual Specifications 2.5.2.6.2. The optional span-to-depth ratios specified in AASHTO LRFD Bridge Design Specifications 2.5.2.6.3 will not be used.
- Determining the anticipated cost of the new bearings for the construction cost estimates. The design of the bearings will be deferred to when the preferred alternative is further developed.
- Developing the following for each feasible alternative advanced for consideration:
  - Preliminary site plan
  - Preliminary plan and profile
  - Preliminary engineer's estimate of probable construction costs
- Requesting hydraulic analysis data from FEMA. If the data is available in a format compatible with HEC-RAS, a preliminary analysis will be performed for the feasible alternatives.
- Designing each feasible alternative to maintain the navigable channel height.
- Determining the need and cost of a causeway into the river to construct the replacement bridge superstructure and identifying feasible alternatives to the causeway.
- Proposing only the minimum roadway approach work needed to accommodate the feasible bridge superstructure replacement alternatives and restore the roadway to two-lane, two-way traffic.
- Investigating whether to accommodate replacing utilities on the replacement bridge superstructure or require the utilities currently on the bridge to relocate. In coordination with the Muskingum County Engineer, the affected utilities will be contacted for their input.
- Closing the bridge and detouring traffic during construction. Maintenance of Traffic design and details will be prepared during development of the preferred alternative.
- Comparing considered feasible superstructure replacement alternatives and recommending a preferred superstructure replacement alternative.

## SERVICES NOT INCLUDED

The following services that have not been scoped to be included in this study and are deferred to after the selection of the preferred alternative:

- Environmental investigations, clearance, or permitting
- Asbestos investigations
- Surveying
- Utility relocation
- Determination of existing property ownerships and existing easements
- Existing and proposed right-of-way determinations
- Construction plans and specifications
- Geotechnical investigations
- Public involvement
- Structural inspections
- Analysis of substructure
- Testing
- Another agency coordination




## LOCATION

The Gaysport bridge is in the County of Muskingum and the State of Ohio. It is located along Muskingum County Road No. 66 (C.R. 66 a.k.a. North Street) over the Muskingum River connecting S.R. 60 at the unincorporated Village of Gaysport in the Township of Blue Rock on the east side of the river to Muskingum County Road No. 6 (C.R. 6) on the west side of the river in Harrison Township. The bridge is also located within the jurisdiction of ODOT District 5.


Latitude: 39° 48' 14.18" (39.80394°) Longitude: -81° 53' 36.26" (-81.89306°)

## PROJECT VICINITY MAP



**PROJECT LOCATION**


## PROJECT LOCATION MAP





## EXISTING CONDITIONS

The following are general descriptions of the existing conditions at the bridge site.



### EXISTING ROADWAY DESCRIPTION

Existing County Road 66 (North Street) is a river crossing roadway that connects C.R. 6 (Old River Road) to the west to the intersection of S.R. 60 (S. River Road) with S.R. 376 (Rockville Road) to the east at a distance of approximately 0.17 mile across the Muskingum River.

The pavement surface is asphalt concrete with an unknown thickness and unknown base other than as shown on the record plans.

The existing right-of-way width is shown as being 50 feet in width at the bridge and varies in width at the adjacent intersections according to Muskingum County GIS. The actual R/W widths will need to be determined and verified as the project is further developed.

The existing roadway was intended to have two-lane traffic with two 10 feet wide lanes. It appears that the paved shoulders are a minimum of 2 feet wide. However, due to the condition of the bridge superstructure, the bridge has been signalized to allow only one-lane two-way traffic.

### EXISTING TRAFFIC DATA

- ADT (2015): 2,917
- ADTT (2015): 218
- Directional Distribution: Unknown

### EXISTING BRIDGE DESCRIPTION

The existing bridge is known as the "Gaysport Bridge" further identified as the MUS-CR66-00.05 (SFN 6031307) bridge over the Muskingum River.

### EXISTING STRUCTURE DATA

- Spans: Seven spans (60.93', 140.17', 140.17', 109.67', 102.33', 71.38', 59.83')
- Total Length: 684 ft. (688 ft. per bridge inventory report)
- Ohio % Legal Load: 35%
- Design Speed: Less than 25 mph
- Superstructure Type: Simple steel beam approach spans with four pony truss mid spans
- Abutment Type: Concrete capped sandstone
- Pier Type: Concrete capped sandstone
- Roadway Width: 24'-0" face to face rail
- Skew: None
- Loading: Unknown
- Approach Slabs: None
- Wearing Surface: Asphalt
- Date Constructed: 1955, Modified 1971 & 2001
- Navigation channel is Span 4 with a width of 103.77'+/-

### AVAILABLE RECORD PLANS AND RECORD INFORMATION

The following record plans and information were used to develop this structure type study.

- Reconstruction and Repair of Gaysport Bridge and Approaches over Muskingum River, dated June 1955.
- Proposed New Bridge over Muskingum River at Gaysport, dated Jan. 1970.
- 684' Seven Span Bridge, County Road 66, 24' Roadway Width, Gaysport Bridge, dated July 2001.
- Ohio Department of Transportation Bridge Inventory Report
- Ohio Department of Transportation Bridge Inspection Report



## DESIGN CONSIDERATIONS

The design philosophy for this bridge was to replace the bridge superstructure on the existing substructure except for replacing the substructure pier and abutment caps.

The replacement bridge structure and associated roadway improvements are designed in accordance with the Ohio Department of Transportation (ODOT) Location and Design Manuals (issued July 2019), the ODOT Bridge Design Manual 2019 (issued July 2019), and the AASHTO LRFD Bridge Design Specifications, 8<sup>th</sup> Edition. AASHTO LRFD HL-93 truck (or lane load) are the design live loadings, and a 60 psf future wearing surface, placed out-to-out deck, is used for the future dead load on the structure.

### ROADWAY

The roadway geometrics and typical section were developed referencing L&D Vol. 1 as well as per Muskingum County Engineer criteria.

#### ROADWAY DESIGN CRITERIA

- Highway Classification: Rural Collector
- Legal Speed: Unposted and Signal Controlled
- Design Speed: <25 MPH Existing and 25 MPH Proposed
- ADT (2015): 2,917
- ADTT (2015): 218
- ADT (2035): To be determined upon further project development
- ADT (2035): To be determined upon further project development
- Directional Distribution: To be determined upon further project development

#### PROPOSED HORIZONTAL ALIGNMENT

The proposed horizontal alignment of C.R. 66 (North Street) is on a tangent alignment beginning at the westerly end of C.R. 66 at the intersection with C.R. 6 (North River Road) and extending across 7 bridge spans to a curve to the right having a degree of curve of 19°11'17" and 15.73' west of the easterly bridge limit. The horizontal alignment of C.R. 66 terminates at the intersection with S.R. 60. The proposed horizontal alignment of the proposed bridge follows the horizontal alignment of the existing bridge.

#### PROPOSED VERTICAL ALIGNMENT

The proposed profile grade will provide a crest vertical curve over the Muskingum River like the existing bridge. The proposed design speed is 25 MPH which is a slight improvement over the existing conditions. The intersections located in close proximity of the bridge at both ends of the bridge and required bridge clearances over the Muskingum River limit increasing the design speed of the roadway over the bridge.

#### PEDESTRIAN SIDEWALKS

There are no pedestrian destination or origin points located west of the bridge and the existing bridge has no walks, therefore, no walks are proposed for the replacement bridge superstructure.

### MAINTENANCE OF TRAFFIC

#### ROADWAY TRAFFIC:

Traffic will need to be detoured for construction because it is not practical or cost effective to reconstruct the bridge part width, to construct a replacement bridge in a new location, or construct a temporary bridge. It is 5 miles to the Philo bridge over the Muskingum River to the north (upstream) and 12.6 miles to the McConnellsville bridge to the south (downstream).

#### MARINE TRAFFIC:

The maintenance of marine traffic will be determined as the project further develops. Maintaining marine traffic or closing to marine traffic will be dependent on the process for the demolition of the existing superstructure and the construction of the proposed superstructure.

### BRIDGE DECK AND ROADWAY DRAINAGE

As directed by the Muskingum County Engineer the proposed drainage for the bridge will be over the side drainage.

The approach roadway drainage will be open ditch.

### PROPOSED STRUCTURE

#### PROPOSED STRUCTURE DATA

- Spans: Seven spans
- Superstructure Type: Steel beam and plate girder
- Abutment Type: Reinforced concrete capped stone
- Pier Type: Reinforced concrete capped stone
- Roadway Width: 24' face to face rail
- Skew: None
- Loading: HL-93 with 0.06 KSF future wearing surface
- Approach Slabs: 25' long (AS-1-15)
- Wearing Surface: 1" monolithic concrete

#### PROPOSED BRIDGE TRANSVERSE SECTION

The proposed bridge transverse section for the 24 feet wide face/face rail alternatives will consist of two 10'-0" wide lanes with 2'-0" shoulders on each side. The proposed approach roadways will approximate the existing conditions.

The proposed bridge transverse section for the 20 feet wide face/face rail alternatives will consist of two 9'-0" wide lanes with 1'-0" shoulders on each side. The proposed approach roadways will approximate the existing conditions by transitioning the 9'-0" wide lanes to the 10 feet wide existing approach lanes.



## CLEARANCES

The Muskingum River is designated as a navigable waterway within the specific reach of the river that includes the location of the Gaysport bridge. Preliminary coordination with the United States Coast Guard is ongoing. Past coordination has included telephone discussions.

Based on prior work completed on the MUS-CR32-0.00 (Philo Bridge) project, the following clearances are proposed for the Gaysport bridge.

### MINIMUM VERTICAL NAVIGATIONAL CHANNEL CLEARANCE

The minimum vertical navigational channel clearance is 28 feet above the normal pool elevation defined to be at elevation 660.41 and located within the navigational channel.

### MINIMUM HORIZONTAL NAVIGATIONAL CHANNEL CLEARANCE

The minimum horizontal navigational channel clearance is 76 feet of clearance provided from face to face of the piers in the navigation channel. Since the existing piers are intended to remain, the horizontal clearance will remain as existing.

## STREAM HYDRAULICS

Muskingum River hydraulic data was acquired from the Muskingum County Engineer's Office and additional data was requested from FEMA.

The data received from the Muskingum County Engineer's Office was for portions of the Muskingum River located north of Gaysport and it did not encompass data that could be used to study the Gaysport bridge superstructure replacement.

The initial stream data received from FEMA was not current HEC-RAS data. Based on subsequent requests to FEMA for additional available hydraulic data, additional data was obtained for tributaries to the Muskingum River, but not for the Muskingum River.

ADR & Associates, Ltd. (ADR) attempted to create a duplicative effective model based on the hydraulic outputs obtained from FEMA. The data was keyed into HEC-RAS, but a model that checked within the required tolerances was not generated (within 6 inches of the existing model). Therefore, a stream profile was established based on existing published data.

The replacement bridge superstructure low chord was not lowered below the existing bridge low chord elevation so there will be no adverse impacts to the 100-year storm elevation (Base Flood Elevation).


### AVAILABLE STREAM DATA

- The bridge site is located within the Muskingum River watershed.
- The 1913 Flood Elevation is noted at 683.00 on 1970 plans.
- The river pool elevation is noted as 661.11 USCE (1929 Datum) or 660.41 (1988 Datum).
- The base flood (100-year) elevation is 679.50+/- (1988 Datum).

- The following are based on Ohio StreamStats (<https://streamstats.usgs.gov/ss/>):
  - Drainage Area: 7350 square miles
  - Peak Flood, 10-Year: 89,400 cfs
  - Peak Flood, 100-Year: 145,000 cfs
  - Highest Mean Monthly Flow: Occurs in March at 13,600 cfs
- FEMA stream data varies from Ohio StreamStats

## DESIGN FREQUENCY

As per the ODOT Location and Design Manual Volume 2 Section 1004.2 and as referenced in the 2019 Bridge Design Manual, Section 203.2, the proposed bridge structure will be designed for a 25-year design flood frequency and the 100-year flood frequency will be checked for compliance with federal



regulations.

## FLOOD ZONE

The bridge and approach roadway are in Zone AE per FEMA FIRM Map 39119C0445G dated 7/6/2010. The Base Flood Elevation (BFE) and floodway have been determined and depicted on the FIRM. An existing hydraulic model is available from FEMA. The 100-year discharge found in the FEMA model was used for the analysis.

A No-Rise condition is preferred if construction is performed within the floodway. Construction within the FEMA Zone AE will require coordination with the Local Floodplain Coordinator. For Muskingum County, the Designated Floodplain Administrator (DFPA) is the Chief Building Official, Jason R. Baughman, PE, Floodplain Administrator, 22 North 5<sup>th</sup> Street, Zanesville, OH 43701, (740) 455-7905.



# STRUCTURE CONSIDERATIONS

## PROPOSED STRUCTURE

The project involves replacing the existing deteriorated bridge superstructure on existing substructure with new reinforced concrete caps on the existing piers and abutments. Since the existing substructure was determined to be reused by the Muskingum County Engineer, no alternative evaluation of the substructure was necessary. The following replacement superstructures were considered.

- Doing nothing (No-Build)
- Four truss spans with rolled steel beam approach spans with a width of 20 feet f/f rail
- Four truss spans with rolled steel beam approach spans with a width of 24 feet f/f rail
- Four steel plate girder spans with rolled steel beam approach spans with a width of 20 feet f/f rail
- Four steel plate girder spans with rolled steel beam approach spans with a width of 24 feet f/f rail
- Prestressed concrete I-beams

## NO-BUILD ALTERNATIVE

While the No-Build Alternative is the least expensive of the alternatives considered, it does not meet the purpose and need of the project and is dismissed from further consideration.

The No-Build Alternative will result in the complete closure of the existing bridge to traffic within the next few years. The existing superstructure has experienced significant deterioration with substantial section loss observed on connections and stringers. The bridge load limit has been reduced to 35% of legal load. Traffic has been reduced from two-lane, two-way traffic to one-lane, two-way traffic with signalization on the bridge. Due to the length of the bridge the one-lane two-way traffic with signalization has increased traffic wait times. Closing the bridge to traffic will result in traffic needing to cross the river either 5 miles upstream to the north at Philo/Duncan Falls or 13 miles downstream at McConnellsville/Malta.

## PRESTRESSED CONCRETE I-BEAMS ALTERNATIVE

The use of prestressed concrete I-beams was considered and dismissed from further consideration. The prestressed concrete I-beams were dismissed because constructing a new superstructure with prestressed concrete I-beams would result in a significant increase to the superstructure dead load. The existing substructure is being reused and it was not designed for the substantial additional loading. Additionally, access to the site with the long prestressed concrete I-beams would be problematic and costly. Setting the prestressed concrete I-beams would require a crane larger than required to set the girders and rolled beams for a steel superstructure thereby increasing the erection costs for the prestressed concrete I-beams alternative.

## APPROACH SPANS (SPANS 1, 2 & 7) ALTERNATIVE

While other alternatives were considered, the recommended preferred alternative for the bridge approach spans 1, 2 & 7 are to use rolled steel beams with four beam lines. Rolled steel beams are

recommended because the approach spans are shorter than the middle spans allowing for the more economical steel rolled beams. The rolled steel beams are proposed to be continuous in approach spans 1 & 2 and in a simple span configuration for span 7. Rolled beams can be used in conjunction with either plate girders or trusses for the middle spans.

A joint will be required on piers 2 and 6. A link slab could be used to prevent debris from entering the joint and keep the joint clean. New pier caps will be required to accommodate the proposed rolled steel beams. Existing substructure concrete caps should be removed down to the sandstone and rebuilt to the proposed beam seat. A semi-integral design is recommended on the piers and abutments per a slightly modified version of ODOT standard construction drawing SICD-1-96 Semi-Integral Construction Details for Steel Beam and Girder Bridges on Rigid Abutments. A semi-integral abutment diaphragm is recommended per ODOT SICD-2-14 Semi-Integral Abutment Diaphragm Guide.

## 20 FEET WIDE TRUSS (SPANS 3 THRU 6) ALTERNATIVE

This alternative utilizes four middle truss spans with rolled steel beam approach spans with a width of 20 feet f/f rail. This truss alternative will be less than the cost of the 24 feet wide truss alternative and comparable to the 24 feet wide steel plate girder alternative. However, the superstructure lane widths for this alternative would be significantly less than the 24 feet wide options and the existing bridge lane widths. Additionally, truss superstructures are considered fracture critical. Section 209.12 of the 2019 BDM states ***"The use of fracture critical members is strongly discouraged"***. Fracture critical superstructures require additional maintenance and expensive inspection when compared with the steel plate girder alternative.

Since there are no significant cost savings when compared to the 24 feet wide steel plate girder, and fracture critical superstructures are discouraged by ODOT, this alternative is not recommended for additional consideration and project development.

## 24 FEET WIDE TRUSS (SPANS 3 THRU 6) ALTERNATIVE

This alternative utilizes four middle truss spans with rolled steel beam approach spans with a width of 24 feet f/f rail. This truss alternative will be more costly than the comparable 24' wide steel plate girder alternative. Additionally, truss superstructures are considered fracture critical. Section 209.12 of the 2019 BDM states ***"The use of fracture critical members is strongly discouraged"***. Fracture critical superstructures require additional maintenance and expensive inspection when compared with the steel plate girder alternative. For these reasons, this alternative is not recommended for additional consideration and project development.

## ROLLED BEAM (SPANS 3 THRU 6) ALTERNATIVE

The four middle spans are too long for rolled steel beams, therefore this alternative is dismissed from further consideration.



### 20 FEET WIDE STEEL PLATE GIRDERS (SPANS 3 THRU 6) ALTERNATIVE

This alternative considers four continuous steel plate girder middle spans with rolled steel beam approach spans with a width of 20 feet f/f rail. This results in middle span costs being less than the other middle span options under consideration. However, the superstructure lane widths for this alternative would be significantly less than the 24 feet wide options and the existing bridge lane widths. For these reasons, this alternative is not recommended for additional consideration and project development.

### 24 FEET WIDE STEEL PLATE GIRDERS (SPANS 3 THRU 6) ALTERNATIVE

This alternative considers four continuous constant depth steel plate girder middle spans with rolled steel beam approach spans with a width of 24 feet f/f rail. This alternative is less expensive than the 24 feet wide truss alternative, maintains a 24 feet wide f/f rail width and is not fracture critical.

This alternative is recommended for additional consideration and project development.

## PROPOSED BRIDGE DESIGN FEATURES

### PROPOSED RAILING

The Muskingum County Engineer desires to use Twin Steel Tube (TST) bridge railing.

Per ODOT BDM Section 304.3.3, the TST railing configuration was developed as a replacement to the Deep Beam Bridge Guardrail system on projects requiring a higher NCHRP acceptance level. The TST bridge railing is for use over rural stream crossings on two (2) lane routes with an ADTT in one direction less than 2500 where the finished deck surface is less than 25 feet above the normal water surface elevation or final ground line. The system shall not be used on an overpass structure.

While the bridge is over 25 feet above the normal water surface, the TST is justifiable because the:

- existing bridge does not have concrete parapets,
- TST will be an improvement over the existing conditions,
- ADTT is significantly less than 2500,
- TST will be lighter than concrete parapets,
- TST will better accommodate over the side drainage,
- And the Muskingum County Engineer will be the maintaining agency.

### GALVANIZED STRUCTURAL STEEL

All structural steel should be galvanized. The Muskingum County Engineer desires to use galvanized structural steel over weathering steel even though additional splices may be required for the galvanizing of girders. Painting structural steel requires additional maintenance throughout the lifespan of the structure.


### PROPOSED JOINTS

Expansion joint options were investigated for the two intermediate joint locations where the rolled beam and girder share a pier. A strip seal expansion joint and link slabs were investigated as two alternatives.

The preliminary costs of using link slabs is less than a strip seal expansion joint (approximately \$6000). The link slabs will also eliminate the maintenance issues that a strip seal can have (such as leaking seal, armor damaged by snowplows, etc.).

There will be a joint over piers 2 and 6. Spans 1 & 2 and 3 thru 6 will be continuous. Span 7 is a simple span. A joint will be required between spans 2 & 3 and between spans 6 & 7.

A link slab joint detail that has been recently used in West Virginia and other states is recommended for this project. The link slab joint will keep the beam seat dry and material out of the joint. Following is an example of the link slab joint detail.



### UTILITIES ON BRIDGE

The determination whether to require utilities to relocate or to be allowed on the replacement bridge superstructure will be determined as the project is further developed and utility coordination occurs.

There is an existing utility line on the bridge. The line appears to be telephone. During the construction the line will require relocation. South of the structure there is overhead electric and telephone. These lines may limit cranes to being able to operate only on the north side of the bridge. Coordination with the utilities will be required to determine if relocation of the overhead lines is necessary.



## CAUSEWAY VERSES BARGES

### CAUSEWAY

Due to the length of the four main spans, a causeway or barges will be required to demolish the existing bridge superstructure and portions of the substructure and to construct the proposed bridge superstructure.

A causeway will require environmental permitting since significant fill will be necessary below ordinary high water. It is estimated that the causeway will need to be 50' +/- wide at the top to accommodate cranes and outriggers. Assuming 1:1 embankment slopes, the base of the causeway will need to be 80' to 100' wide. This would result in a large amount of fill to be placed and subsequently removed. Causeways have a risk of overtopping if the design storm is exceeded. This additional cost would be borne by the owner. This is not recommended method due to high cost and risk.

### BARGES

Barges with cranes will be more cost effective and of lower risk than a causeway. Barges may require acquisition of temporary right-of-way for cranes and material to be loaded onto the barge. Permitting may be required to work below the ordinary high-water mark to construct a suitable area for loading and unloading. However, the impacts would be significantly less than a causeway. Based on conversations with contractors, the cost of removing the existing superstructure and constructing the new superstructure with barges is estimated to be approximately \$2,000,000.

## CORROSION PROTECTION – STEEL GIRDERS

There are three primary options that exist for protection against corrosion of steel girders. They are:

- Painted Steel
- Galvanized Steel
- Weathering Steel

The ODOT Bridge Design Manual (BDM) Section 302.4.1.5 serves as a guide in selecting corrosion control systems.

### PAINTED STEEL

Painted steel is a common corrosion protection method used in the State of Ohio. The main drawback of a paint protection system is that it will need to be sand blasted and repainted periodically in order to continually protect the superstructure steel from corrosion. Sand blasting and repainting is complicated because of containment requirements and is expensive because the bridge transverses a relatively large waterway, the Muskingum River.

### GALVANIZED STEEL

Hot dip galvanizing provides an excellent long-lasting corrosion protection system which is anticipated to be relatively maintenance free throughout the life of the galvanized coating which is approximately 100 years. Galvanized steel is often used on smaller bridges where beam/girder units can be easily hot-dipped. Generally structural steel members would need to be relatively short, approximately 55 feet or less, for hot-dipped galvanizing, but longer lengths can be galvanized. Therefore, the longer bridge spans

may need to be fabricated with approximately twice as many members or sections as would typically be designed. This will increase the number of field splices and the cost of construction.

### WEATHERING STEEL

Weathering steel can provide an excellent long-lasting corrosion protection system when used in the appropriate atmospheric circumstances. Typically, weathering steel performs well on bridges which are not exposed to a highly corrosive environment and which are not continuously exposed to long term moisture conditions. Adequate air flow is needed to provide a drying ventilation condition below the bridge. This would allow the girders to remain relatively dry and ensure that the steel will form a stable rust-like appearance when exposed to elements for a long period of time. The net effect is that the steel creates a brown patina coating which guards against future corrosion.

### CORROSION PROTECTION LIFESPAN

A structure with a lower up-front cost which requires significant recurring maintenance may prove to be less economical than a structure with a higher up-front cost and little to no recurring maintenance. Additionally, a structure with high up-front costs and a long service life may prove to be more economical than a structure with lower up-front costs and a shorter service life.

Potential maintenance items include:

- Deck replacement: 40 years
- Sealing of concrete: 5 years
- Structural steel painting (painted steel alternative only): 30 years

A number of factors go into affecting the lifespan of the structure including the effect of corrosive elements in the environment, the type of corrosion protection system used, and the as-built thickness of the corrosion protection systems. A review of available information indicates the following lifespans for each beam/girder type with the associated maintenance work:

- Prestressed concrete I-beams: 75 years, with fascia girder sealing every 5 years
- Weathering steel girders: 75 years, with little to no maintenance
- Galvanized steel girders: 100 years, with little to no maintenance

The value of a structure whose lifespan extends far into the future is hard to accurately quantify. Predicting the operational and loading needs of a structure 50 years into the future is typically not accurate.

### CORROSION PROTECTION CONCLUSION

The girders for the Gaysport bridge are considered to be in a relatively non-corrosive environment except when road salts (deicing salts) find their way to the girders below the deck through a leaky deck and deck joints. While the beams are relatively high above the Muskingum River allowing for adequate air flow, there is fog and moisture associated with the river. Over the side drainage would allow road salts to blow onto the girders.

While having a higher initial cost, galvanized steel is recommended because it will not require maintenance, will better allow for over the side drainage, and avoids rust staining of the new substructure pier and abutment caps.





### GIRDER WEB THICKNESS

Increasing the web thickness of steel plate girders facilitates easier construction when the girders are erected. A thicker web will help prevent the girders from buckling under their own weight prior to attaching cross frames. A thicker web will minimize, and may eliminate, the amount of temporary bracing required during construction.

A thicker web will increase the lifespan of the steel plate girder. Once the galvanizing has deteriorated the underlying steel will have an addition sacrificial thickness that can deteriorate without adversely affecting the superstructure thereby increasing lifespan.

The steel plate girders proposed for the replacement bridge superstructure are 48 inches by 5/8 inch. The steel plate girder web can be increased by 1/4 inch for a total web thickness of 7/8 inch without requiring the redesign of the steel plate girder flanges. The estimated cost of increasing the web thickness is \$120,969 based on the following calculation.

$493.75' \text{ long girders} \times (0.25'' \text{ additional web thickness} \div 12''/\text{ft.}) \times 4' \text{ girder height} \times 4 \text{ girders} \times 490 \text{ lbs./cu. Ft.} \times \$1.50 \text{ per lbs.} = \$120,969$

## SUMMARY OF CONSTRUCTION COSTS

### CONSTRUCTION COST COMPARISONS

A preliminary estimate of probable construction costs based on 2019 costs was developed for each considered alternative and summarized as follows.

#### TRUSS REPLACEMENT COSTS

According to the Muskingum County Engineer's Office (MCEO) on Aug. 26, 2019, the estimated cost to replace the existing truss spans with galvanized truss superstructures having a 24' wide f/f rail concrete deck and TST railing is \$5,320,000. This cost is to replace truss spans 3 thru 6 only, including new pier caps. This does not include costs to replace the steel beam spans 1, 2 & 7, abutments, or approach work.

According to the Muskingum County Engineer's Office (MCEO) on Aug. 27, 2019, the estimated cost to replace the existing truss spans with galvanized truss superstructures having a 20' wide f/f rail concrete deck and TST railing is \$4,400,000. This cost is to replace truss spans 3 thru 6 only, including new pier caps. This does not include costs to replace the steel beam spans 1, 2 & 7, abutments, or approach work.

#### APPROACH SPANS ROLLED STEEL BEAMS, 20' WIDE, SPANS 1, 2 & 7, COSTS

Approximate construction cost is \$1.398 million. See Appendix.

#### APPROACH SPANS ROLLED STEEL BEAMS, 24' WIDE, SPANS 1, 2 & 7, COSTS

Approximate construction cost is \$1.446 million. See Appendix.

#### STEEL PLATE GIRDER, 20' WIDE, SPANS 3 THRU 6, COSTS

Approximate construction cost is \$4.296 million. See Appendix.

#### STEEL PLATE GIRDER, 24' WIDE, SPANS 3 THRU 6, COSTS

Approximate construction cost is \$4.527 million. See Appendix.

#### COST COMPARISON SUMMARY

Truss Alternative, 20' Wide: \$1.398 Million + \$4.400 Million = **\$5.798 Million**

Truss Alternative, 24' Wide: \$1.446 Million + \$5.320 Million = **\$6.766 Million**

Steel Plate Girder Alternative: 20' Wide: \$1.398 Million + \$4.296 Million = **\$5.694 Million**

Steel Plate Girder Alternative: 24' Wide: \$1.446 Million + \$4.527 Million = **\$5.973 Million**

#### LIFE CYCLE COSTS

Life cycle costs are generated by combining the initial construction costs with the future maintenance costs to calculate the anticipated cost of the alternatives over the life of the bridge.

For this study, life cycle costs are calculated on today's dollars and with a negligible discount rate.

For actual performance, it is noted that increasing traffic and damage would result in rehabilitation timing decreases. Meaning that the same standard fix can't last the same time frame as the previous fix.

The time horizon for the life cycle cost analysis:

- Equal for all alternatives under consideration
- Is not the same as the design life
- Is set long enough in include at least one major rehabilitation
- Long enough to distinguish cost differences

For reasons previously stated, painting of structurally steel has been excluded from additional consideration and life cycle cost analysis.



**BREAKDOWN OF LIFE CYCLE COSTS**

The following tables show the life cycle costs for sealing, deck and inspection for a 75-year life cycle.

STRUCTURE TYPE	SEALING Life Cycle Cost		
	Frequency (Years)	Cost	Total
Galvanized Beams	15	\$9,800	\$39,200
Weathering Beams		\$9,800	\$39,200
Truss		\$4,694	\$18,776

STRUCTURE TYPE	DECK Life Cycle Cost *		
	Frequency (Years)	Cost	Total
Galvanized Beams	40	\$943,117	\$943,117
Weathering Beams		\$943,117	\$943,117
Truss	20	\$508,499	1,525,498

\* Deck cost for truss includes superstructure rehabilitation.

STRUCTURE TYPE	INSPECTION Life Cycle Cost		
	Frequency (Years)	Cost	Total
Galvanized Beams	1	\$1,500	\$112,500
Weathering Beams		\$1,500	\$112,500
Truss		\$5,000	\$375,000

**SUMMARY OF LIFE CYCLE COSTS**

The following table shows the life cycle costs for the shown beam types for a 75-year life cycle.

STRUCTURE TYPE	Life Cycle Cost	Superstructure Replacement Initial Construction Cost
Galvanized Beams	\$7,058,106	\$5,972,289
Weathering Beams	\$6,610,672	\$5,524,855
Truss	\$8,684,910	\$6,765,636

**CONCLUSIONS AND RECOMMENDATIONS**

**RECOMMENDED PREFERRED ALTERNATIVE**

The recommended preferred replacement superstructure alternative is to use four beam lines of galvanized rolled steel beams for spans 1, 2 & 7 and galvanized steel plate constant depth girder for spans 3 through 6 with 24 feet wide face/face rail reinforced concrete deck with TST railing and over the side drainage. The steel plate girders are proposed to have a depth of between 50" to 52" with an 8.5" composite concrete deck and 2" haunches. There are also four steel plate girder beam lines.

The total superstructure depth will be 60.5" to 62.5". Span lengths are 102'-3", 110', 140'-3", and 140'-3" for spans 3 through 5.

The bridge will have a vertical profile set to accommodate 25 MPH two-lane, two-way traffic that will not decrease the low chord elevation of the bridge. There is some room to adjust the profile downward to improve the profile.

The substructure abutments and piers will have caps replaced with reinforced concrete and new bearings. Abutments will be semi-integral with new approach slabs. Link slab joints are proposed between spans 2 & 3 and between spans 6 & 7.

Barges with cranes will be more cost effective and of lower risk than constructing a causeway to demolish the existing bridge superstructure and portions of the substructure, and to construct the proposed bridge superstructure.





## **APPENDIX**

**APPENDIX A: PRELIMINARY PLANS**

**APPENDIX B: COST ESTIMATES**

**APPENDIX C: HYDRAULIC DATA**

**APPENDIX D: EXISTING PLANS**

P:\AD\2019\15701 MUS Co Eng-Gaysport Bridge\101730\Design\Structures\MUS066\_0050C\Sheets\066\_0005SP005.dgn Sheet 8/29/2019 11:40:54 AM jhartfield

P.I. Sta. 17+52.70  
 $\Delta = 10^\circ 38' 10''$  (RT)  
 $D_c = 19^\circ 11' 17''$   
 $R = 300.00'$   
 $T = 27.93'$   
 $L = 55.43'$   
 $E = 1.30'$   
 $C = -55.61'$   
 $C.B. = S 66^\circ 52' 32'' E$



DESIGN AGENCY  
**ADR**  
 88 West Ottawa Street  
 (781) 345-1000  
 www.adrinc.com


DATE  
 REVIEWED  
 DRAWN  
 JTH  
 CHECKED  
 DESIGNED

MUSKINGUM COUNTY  
 STA. 10+04.50  
 STA. 17+40.50


**SITE PLAN**  
 BRIDGE NO. MUS-CR66-0005  
 OVER MUSKINGUM RIVER

**MUS-CR66-0005**  
 PID No. 101730

1 / 7




PLAN




PROFILE ALONG  $\text{\textcircled{C}}$  CONSTRUCTION



P:\ADR\2019\315701 MUS Co Eng-Gaysport\_Bridge\101730\Design\Structures\MUS066\_0050C\Sheets\066\_0005SP001.dgn Sheet 8/29/2019 11:41:06 AM jhortfield



PLAN



PROFILE ALONG CONSTRUCTION

**TRAFFIC DATA**

DESIGN TRAFFIC:  
 2015 ADT = 2,917      2015 ADTT = 218  
 2035 ADT = -----      2035 ADTT = ----  
 DIRECTIONAL DISTRIBUTION = UNKNOWN

**HYDRAULIC DATA**

DRAINAGE AREA = 7,341 SQUARE MILES  
 Q (100) = 77,700 CFS BASED ON FEMA FLOOD INSURANCE  
 STUDY 39119CVOOB AUGUST 15, 2017  
 STRUCTURE CLEARS THE 100 YEAR DESIGN HW BY --- FEET

**SPAN CONFIGURATION**

SPANS 1 & 2 - CONTINUOUS ROLLED BEAM WITH COMPOSITE DECK  
 SPANS 3 - 6 - CONTINUOUS PLATE GIRDER WITH COMPOSITE DECK  
 SPAN 7 - SIMPLE ROLLED BEAM WITH COMPOSITE DECK

**EXISTING STRUCTURE**

TYPE: SEVEN SPAN STRUCTURE WITH SIMPLE STEEL BEAM APPROACH SPANS AND TRUSSES WITH ASPHALT WEARING SURFACE ON SANDSTONE ABUTMENTS AND PIERS.

SPANS: 59'±, 71'-3"±, 102'-3"±, 110'±, 140'-3"±, 140'-3"±, 59'±

ROADWAY: 24'-0"± F/F RAIL

LOADING: UNKNOWN

SKEW: NONE

APPROACH SLABS: NONE

ALIGNMENT: TANGENT WITH HORIZONTAL CURVE AT FORWARD ABUTMENT

CROWN: VARIES

STRUCTURAL FILE NUMBER: 6031307

DATE BUILT: UNKNOWN (SUPERSTRUCTURE REPLACEMENT 1971 WITH REHABILITATION IN 2001)

DISPOSITION: SUPERSTRUCTURE TO BE REPLACED

**PROPOSED STRUCTURE**

TYPE: SEVEN SPAN STEEL BEAM AND PLATE GIRDER WITH COMPOSITE REINFORCED DECK ON EXISTING STANDSTONE ABUTMENTS AND PIERS

SPANS: 59'-6", 71'-3", 102'-3", 110'-0", 140'-3", 140'-3", 60'-6"

ROADWAY: 24'-0" F/F RAIL

LOADING: HL-93 WITH 0.06 KSF FUTURE WEARING SURFACE

SKEW: NONE

APPROACH SLABS: 25' LONG (AS-1-15)

WEARING SURFACE: 1" MONOLITHIC CONCRETE

ALIGNMENT: TANGENT WITH HORIZ. CURVE AT FORWARD ABUTMENT

CROWN: 0.016 FT/FT

COORDINATES: LATITUDE 39°48'15"  
 LONGITUDE 81°53'40"

DESIGN AGENCY: **ADR**  
 1000 Old River Road, Suite 100  
 Old River, TN 37050  
 (615) 396-1000  
 www.adrinc.com

MUSKINGUM COUNTY  
 STA. 10+04.50  
 STA. 17+40.50

**SITE PLAN**  
 BRIDGE NO. MUS-CR66-0005  
 OVER MUSKINGUM RIVER

MUS - CR66 - 0005  
 PID No. 101730

2 / 7





P:\ADR\2019\315701 MUS Co Eng-Goyssport\_Bridge\101730\Design\Structures\MUS066\_0050C\Sheets\066\_0005SP003.dgn\_Sheet 8/29/2019 11:46:24 AM jhartfield

MATCH LINE STA. 14+75.00 - SEE SHEET 2

MATCH LINE STA. 14+75.00 - SEE SHEET 2



EX. BUILDING

140'-3" SPAN 5

140'-3" SPAN 6

60'-6" SPAN 7

25'-0" APPROACH SLAB


139'-3" C/C BEARINGS

59'-6" C/C BEARINGS

15

16

17



☉ PIER 5, STA. 15+38.75

☉ CONSTRUCTION  
COUNTY ROAD 66  
NORTH STREET

☉ BEARINGS, STA. 16+79.00  
☉ PIER 6, STA. 16+80.00  
☉ BEARINGS, STA. 16+81.00


BEGIN APPROACH SLAB STA. 17+40.50  
☉ BEARINGS, F.A. STA. 17+39.50

P.I. Sta. 17+52.70  
Δ = 10° 38' 10" (RT)  
Dc = 19° 11' 17"  
R = 300.00'  
T = 27.93'  
L = 55.43'  
E = 1.30'  
C = -55.61'  
C.B. = S 66° 52' 32" E

PC Sta. 17+24.78

MATCH LINE 17+70.00 - SEE SHEET 4

**PLAN**



**PROFILE ALONG ☉ CONSTRUCTION**

DESIGN AGENCY  
ADR  
10000 Oldham Street  
Baltimore, MD 21286  
(410) 341-1011 (ph)  
(410) 341-1012 (fax)  
www.adrinc.com

DATE	
REVIEWED	
DRAWN	JTH
CHECKED	
DESIGNED	
STRUCTURE FILE NUMBER	6031307



MUSKINGUM COUNTY  
STA. 10+04.50  
STA. 17+40.50

**SITE PLAN**  
BRIDGE NO. MUS-CR66-0005  
OVER MUSKINGUM RIVER

**MUS - CR66 - 0005**  
PID No. 101730


4 / 7







P:\ADR\2019\315701 MUS Co Eng-Gaysport Bridge\101730\Design\Structures\MUS066\_0050C\Sheets\066\_0005ST001.dgn Sheet 8/29/2019 11:40:29 AM jhartfield



TRANSVERSE SECTION




PLATE GIRDER SECTIONS




DESIGNED	JTH	CHECKED	BCK
DRAWN	JTH	REVISED	
REVIEWED	RBK	STRUCTURE FILE NUMBER	6130594
DATE	2-14-19		


**TRANSVERSE SECTION - PLATE GIRDER SECTIONS**  
 BRIDGE NO. MUS-CR66-0005  
 OVER EAST FORK DUCK CREEK

**MUS - CR 66 - 0005**  
 PID No. 101730

P:\ADR\2019\315701 MUS Co Eng-Gaysport Bridge\101730\Design\Structures\MUS066\_0050C\Sheets\066\_0005ST002.dgn Sheet 8/29/2019 11:40:44 AM jhortfield



TRANSVERSE SECTION



ROLLED BEAM SECTIONS

**TRANSVERSE SECTION - ROLLED BEAM SECTIONS**

BRIDGE NO. MUS-CR66-0005  
OVER MUSKINGUM RIVER



**MUS - CR 66 - 0005**  
PID No. 101730

DESIGNED	JTH	CHECKED	BCK
DRAWN	JTH	REVISED	
REVIEWED	RBK	STRUCTURE FILE NUMBER	6130594
DATE	2-14-19		

DESIGN AGENCY  
**ADR**  
 100 West Columbia Street  
 (717) 326-1000 (PH)  
 (717) 326-1001 (FX)  
 www.adrinc.com



P:\DDT\MP\0110\_MUS-CR66\_0005\101730\Design\Structures\MUS066\_0005C\Sheets\BEAM ELEVATION.dgn Sheet 8/1/2019 9:14:54 AM CMT006



MUS - CR66 - 0005  
PID No. 101730

GIRDER ELEVATION  
BRIDGE NO. MUS-CR66-0005  
OVER MUSKINGUM RIVER

DESIGNED	MTJ	CHECKED	AMR
DRAWN	MTJ	REVISED	
REVIEWED	XXX	STRUCTURE FILE NUMBER	XXX
DATE	XXX		XXX

DESIGN AGENCY

## Estimate

Estimated Cost:\$1,165,101.65

Contingency: 20.00%

**Estimated Total: \$1,398,121.98**

Spans 1,2,7 & Approach Work (20' F/F)

**Base Date: 08/20/19**

Spec Year: 19

Unit System: E

Work Type: BRIDGE REHABILITATION

Highway Type:

Urban/Rural Type: RURAL CLASS

Season: SUMMER

County: MUSKINGUM

Latitude of Midpoint: 394814

Longitude of Midpoint: 815336

District: 05

Federal/State Project Number:

*Prepared by Damon Fulk*

Estimate:

<u>Line #</u>	<u>Item Number</u>	<u>Quantity</u>	<u>Units</u>	<u>Unit Price</u>	<u>Extension</u>
<u>Description</u>					
<u>Supplemental Description</u>					
<b>Group 0100:</b>					
0006	202E23500 WEARING COURSE REMOVED	1,829.000	SY	\$5.01587	\$9,174.03
0007	202E23000 PAVEMENT REMOVED	510.000	SY	\$14.89737	\$7,597.66
0008	203E10000 EXCAVATION	25.000	CY	\$33.05942	\$826.49
0009	203E20000 EMBANKMENT	25.000	CY	\$31.00139	\$775.03
0010	304E20000 AGGREGATE BASE	184.000	CY	\$95.55089	\$17,581.36
0011	301E46000 ASPHALT CONCRETE BASE, PG64-22	157.000	CY	\$181.21869	\$28,451.33
0012	441E10000 ASPHALT CONCRETE SURFACE COURSE, TYPE 1, (446), PG64-22	33.000	CY	\$181.05222	\$5,974.72
0013	441E10200 ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE 2, (446)	46.000	CY	\$180.00000	\$8,280.00
0037	644E00104 EDGE LINE, 6"	0.340	MILE	\$2,629.74596	\$894.11
0038	644E00300 CENTER LINE	0.170	MILE	\$6,462.30090	\$1,098.59
0039	644E00500 STOP LINE	20.000	FT	\$8.83998	\$176.80
<b>Total for Group 0100:</b>					<b>\$80,830.12</b>
<b>Group 1900:</b>					
0014	202E11000 STRUCTURE REMOVED	1.000	LS	\$100,000.00000	\$100,000.00
0015	503E21300 UNCLASSIFIED EXCAVATION	1.000	LS	\$5,000.00000	\$5,000.00
0016	509E10000 EPOXY COATED REINFORCING STEEL	32,900.000	LB	\$1.00000	\$32,900.00



Estimate:

<u>Line #</u>	<u>Item Number</u>	<u>Quantity</u>	<u>Units</u>	<u>Unit Price</u>	<u>Extension</u>
<u>Description</u>					
<u>Supplemental Description</u>					
0017	511E21522	162.000	CY	\$796.83118	\$129,086.65
CLASS QC2 CONCRETE WITH QC/QA, SUPERSTRUCTURE					
0018	511E50210	11.000	CY	\$1,431.71836	\$15,748.90
CLASS QC1 CONCRETE, SUBSTRUCTURE					
0019	512E10000	130.000	SY	\$18.68300	\$2,428.79
SEALING OF CONCRETE SURFACES					
0020	513E10220	31,153.000	LB	\$1.50000	\$46,729.50
STRUCTURAL STEEL MEMBERS, LEVEL 1					
0021	513E10240	103,697.000	LB	\$1.50000	\$155,545.50
STRUCTURAL STEEL MEMBERS, LEVEL 2					
0022	513E20000	3,084.000	EACH	\$3.11676	\$9,612.09
WELDED STUD SHEAR CONNECTORS					
0023	516E14600	40.000	FT	\$300.00000	\$12,000.00
STRUCTURAL JOINT OR JOINT SEALER, MISC.:					
0024	516E44200	20.000	EACH	\$200.00000	\$4,000.00
ELASTOMERIC BEARING WITH INTERNAL LAMINATES AND LOAD PLATE ( NEOPRENE)					
0026	517E70000	382.500	FT	\$124.69023	\$47,694.01
RAILING (TWIN STEEL TUBE)					
0027	518E21200	22.000	CY	\$104.34588	\$2,295.61
POROUS BACKFILL WITH GEOTEXTILE FABRIC					
0028	518E40000	40.000	FT	\$9.19862	\$367.94
6" PERFORATED CORRUGATED PLASTIC PIPE					
0029	518E40012	120.000	FT	\$10.70539	\$1,284.65
6" NON-PERFORATED CORRUGATED PLASTIC PIPE					
0030	526E25000	136.000	SY	\$218.00268	\$29,648.36
REINFORCED CONCRETE APPROACH SLABS (T=15")					
0031	601E32104	78.000	CY	\$114.26724	\$8,912.84
ROCK CHANNEL PROTECTION, TYPE B WITH GEOTEXTILE FABRIC					
0032	846E00110	28.000	CF	\$357.73906	\$10,016.69
POLYMER MODIFIED ASPHALT EXPANSION JOINT SYSTEM					
0033	513E95020	1.000	LS	\$100,000.00000	\$100,000.00
STRUCTURAL STEEL, MISC.:					

Estimate:

<u>Line #</u>	<u>Item Number</u>	<u>Quantity</u>	<u>Units</u>	<u>Unit Price</u>	<u>Extension</u>
<u>Description</u>					
<u>Supplemental Description</u>					
<i>Bridge Erection - Spans 1, 2, 7</i>					
					<b>Total for Group 1900:\$713,271.53</b>

**Group 1901:**

0034	614E11000	1.000	LS	\$10,000.00000	\$10,000.00
MAINTAINING TRAFFIC					
0035	624E10000	1.000	LS	\$350,000.00000	\$350,000.00
MOBILIZATION					
0036	623E10000	1.000	LS	\$11,000.00000	\$11,000.00
CONSTRUCTION LAYOUT STAKES AND SURVEYING					
					<b>Total for Group 1901:\$371,000.00</b>

## Estimate

Estimated Cost:\$1,204,696.26

Contingency: 20.00%

**Estimated Total: \$1,445,635.51**

Spans 1,2,7 & Approach Work (24' F/F)

**Base Date: 08/20/19**

Spec Year: 19

Unit System: E

Work Type: BRIDGE REHABILITATION

Highway Type:

Urban/Rural Type: RURAL CLASS

Season: SUMMER

County: MUSKINGUM

Latitude of Midpoint: 394814

Longitude of Midpoint: 815336

District: 05

Federal/State Project Number:

*Prepared by Damon Fulk*

Estimate:

<u>Line #</u>	<u>Item Number</u>	<u>Quantity</u>	<u>Units</u>	<u>Unit Price</u>	<u>Extension</u>
<u>Description</u>					
<u>Supplemental Description</u>					
<b>Group 0100:</b>					
0006	202E23500 WEARING COURSE REMOVED	1,829.000	SY	\$5.01587	\$9,174.03
0007	202E23000 PAVEMENT REMOVED	510.000	SY	\$14.89737	\$7,597.66
0008	203E10000 EXCAVATION	25.000	CY	\$33.05942	\$826.49
0009	203E20000 EMBANKMENT	25.000	CY	\$31.00139	\$775.03
0010	304E20000 AGGREGATE BASE	184.000	CY	\$95.55089	\$17,581.36
0011	301E46000 ASPHALT CONCRETE BASE, PG64-22	157.000	CY	\$181.21869	\$28,451.33
0012	441E10000 ASPHALT CONCRETE SURFACE COURSE, TYPE 1, (446), PG64-22	33.000	CY	\$181.05222	\$5,974.72
0013	441E10200 ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE 2, (446)	46.000	CY	\$180.00000	\$8,280.00
0037	644E00104 EDGE LINE, 6"	0.340	MILE	\$2,629.74596	\$894.11
0038	644E00300 CENTER LINE	0.170	MILE	\$6,462.30090	\$1,098.59
0039	644E00500 STOP LINE	20.000	FT	\$8.83998	\$176.80
<b>Total for Group 0100:</b>					<b>\$80,830.12</b>
<b>Group 1900:</b>					
0014	202E11000 STRUCTURE REMOVED	1.000	LS	\$100,000.00000	\$100,000.00
0015	503E21300 UNCLASSIFIED EXCAVATION	1.000	LS	\$5,000.00000	\$5,000.00
0016	509E10000 EPOXY COATED REINFORCING STEEL	39,805.000	LB	\$1.00000	\$39,805.00



Estimate:

<u>Line #</u>	<u>Item Number</u>	<u>Quantity</u>	<u>Units</u>	<u>Unit Price</u>	<u>Extension</u>
0017	511E21522 CLASS QC2 CONCRETE WITH QC/QA, SUPERSTRUCTURE	170.000	CY	\$789.71448	\$134,251.46
0018	511E50210 CLASS QC1 CONCRETE, SUBSTRUCTURE	13.000	CY	\$1,325.02451	\$17,225.32
0019	512E10000 SEALING OF CONCRETE SURFACES	145.000	SY	\$18.41114	\$2,669.62
0020	513E10220 STRUCTURAL STEEL MEMBERS, LEVEL 1	33,863.000	LB	\$1.50000	\$50,794.50
0021	513E10240 STRUCTURAL STEEL MEMBERS, LEVEL 2	112,714.000	LB	\$1.50000	\$169,071.00
0022	513E20000 WELDED STUD SHEAR CONNECTORS	3,084.000	EACH	\$3.11676	\$9,612.09
0023	516E14600 STRUCTURAL JOINT OR JOINT SEALER, MISC.:	48.000	FT	\$300.00000	\$14,400.00
0024	516E44200 ELASTOMERIC BEARING WITH INTERNAL LAMINATES AND LOAD PLATE ( NEOPRENE)	20.000	EACH	\$200.00000	\$4,000.00
0026	517E70000 RAILING (TWIN STEEL TUBE)	382.500	FT	\$124.69023	\$47,694.01
0027	518E21200 POROUS BACKFILL WITH GEOTEXTILE FABRIC	25.000	CY	\$101.93788	\$2,548.45
0028	518E40000 6" PERFORATED CORRUGATED PLASTIC PIPE	48.000	FT	\$8.43135	\$404.70
0029	518E40012 6" NON-PERFORATED CORRUGATED PLASTIC PIPE	120.000	FT	\$10.70539	\$1,284.65
0030	526E25000 REINFORCED CONCRETE APPROACH SLABS (T=15")	161.000	SY	\$213.88850	\$34,436.05
0031	601E32104 ROCK CHANNEL PROTECTION, TYPE B WITH GEOTEXTILE FABRIC	78.000	CY	\$114.26724	\$8,912.84
0032	846E00110 POLYMER MODIFIED ASPHALT EXPANSION JOINT SYSTEM	31.000	CF	\$346.98213	\$10,756.45
0033	513E95020 STRUCTURAL STEEL, MISC.:	1.000	LS	\$100,000.00000	\$100,000.00

Estimate:

<u>Line #</u>	<u>Item Number</u>	<u>Quantity</u>	<u>Units</u>	<u>Unit Price</u>	<u>Extension</u>
	<i>Bridge Erection - Spans 1, 2, 7</i>				
<b>Total for Group 1900:\$752,866.14</b>					
<b>Group 1901:</b>					
0034	614E11000 MAINTAINING TRAFFIC	1.000	LS	\$10,000.00000	\$10,000.00
0035	623E10000 CONSTRUCTION LAYOUT STAKES AND SURVEYING	1.000	LS	\$11,000.00000	\$11,000.00
0036	624E10000 MOBILIZATION	1.000	LS	\$350,000.00000	\$350,000.00

**Total for Group 1901:\$371,000.00**

## Estimate

Estimated Cost:\$3,579,799.17

Contingency: 20.00%

**Estimated Total: \$4,295,759.00**

Girder - Spans 3,4,5,6 - 20' F/F

**Base Date: 08/20/19**

Spec Year: 19

Unit System: E

Work Type: BRIDGE REHABILITATION

Highway Type:

Urban/Rural Type: RURAL CLASS

Season: SUMMER

County: MUSKINGUM

Latitude of Midpoint: 394814

Longitude of Midpoint: 815336

District: 05

Federal/State Project Number:

*Prepared by Damon Fulk*

Estimate:

<u>Line #</u>	<u>Item Number</u>	<u>Quantity</u>	<u>Units</u>	<u>Unit Price</u>	<u>Extension</u>
<u>Description</u>					
<u>Supplemental Description</u>					
<b>Group 1900:</b>					
0014	202E11000	1.000	LS	\$1,000,000.00000	\$1,000,000.00
STRUCTURE REMOVED					
0015	509E10000	82,743.000	LB	\$1.00000	\$82,743.00
EPOXY COATED REINFORCING STEEL					
0016	511E21522	320.000	CY	\$702.00910	\$224,642.91
CLASS QC2 CONCRETE WITH QC/QA, SUPERSTRUCTURE					
0017	511E50210	24.000	CY	\$997.20645	\$23,932.95
CLASS QC1 CONCRETE, SUBSTRUCTURE					
0018	512E10000	432.000	SY	\$15.90154	\$6,869.47
SEALING OF CONCRETE SURFACES					
0021	513E10280	544,888.000	LB	\$2.00000	\$1,089,776.00
STRUCTURAL STEEL MEMBERS, LEVEL 4					
0022	513E20000	7,908.000	EACH	\$3.11676	\$24,647.34
WELDED STUD SHEAR CONNECTORS					
0024	516E44200	20.000	EACH	\$200.00000	\$4,000.00
ELASTOMERIC BEARING WITH INTERNAL LAMINATES AND LOAD PLATE ( NEOPRENE)					
0025	517E70000	985.500	FT	\$125.00000	\$123,187.50
RAILING (TWIN STEEL TUBE)					
0032	513E95020	1.000	LS	\$1,000,000.00000	\$1,000,000.00
STRUCTURAL STEEL, MISC.: Bridge Erection Using Barges and Cranes					

**Total for Group 1900:\$3,579,799.17**

## Estimate

Estimated Cost:\$3,772,210.90

Contingency: 20.00%

**Estimated Total: \$4,526,653.08**

Girder Spans 3,4,5,6 - 24' F/F

**Base Date: 08/20/19**

Spec Year: 19

Unit System: E

Work Type: BRIDGE REHABILITATION

Highway Type:

Urban/Rural Type: RURAL CLASS

Season: SUMMER

County: MUSKINGUM

Latitude of Midpoint: 394814

Longitude of Midpoint: 815336

District: 05

Federal/State Project Number:

*Prepared by Damon Fulk*

Estimate:

<u>Line #</u>	<u>Item Number</u>	<u>Quantity</u>	<u>Units</u>	<u>Unit Price</u>	<u>Extension</u>
<u>Description</u>					
<u>Supplemental Description</u>					
<b>Group 1900:</b>					
0014	202E11000	1.000	LS	\$1,000,000.00000	\$1,000,000.00
STRUCTURE REMOVED					
0015	509E10000	95,493.000	LB	\$1.00000	\$95,493.00
EPOXY COATED REINFORCING STEEL					
0016	511E21522	371.000	CY	\$682.95075	\$253,374.73
CLASS QC2 CONCRETE WITH QC/QA, SUPERSTRUCTURE					
0017	511E50210	28.000	CY	\$928.43027	\$25,996.05
CLASS QC1 CONCRETE, SUBSTRUCTURE					
0018	512E10000	451.000	SY	\$15.80994	\$7,130.28
SEALING OF CONCRETE SURFACES					
0021	513E10280	619,191.000	LB	\$2.00000	\$1,238,382.00
STRUCTURAL STEEL MEMBERS, LEVEL 4					
0022	513E20000	7,908.000	EACH	\$3.11676	\$24,647.34
WELDED STUD SHEAR CONNECTORS					
0024	516E44200	20.000	EACH	\$200.00000	\$4,000.00
ELASTOMERIC BEARING WITH INTERNAL LAMINATES AND LOAD PLATE ( NEOPRENE)					
0025	517E70000	985.500	FT	\$125.00000	\$123,187.50
RAILING (TWIN STEEL TUBE)					
0032	513E95020	1.000	LS	\$1,000,000.00000	\$1,000,000.00
STRUCTURAL STEEL, MISC.: Bridge Erection Using Barges and Cranes					
<b>Total for Group 1900:</b>					<b>\$3,772,210.90</b>



FLOODING SOURCE		FLOODWAY					1-PERCENT-ANNUAL-CHANCE FLOOD WATER SURFACE ELEVATION (FEET NAVD)		
CROSS SECTION	DISTANCE <sup>1</sup>	WIDTH (FEET)	SECTION AREA (SQUARE FEET)	MEAN VELOCITY (FEET PER SECOND)	WIDTH REDUCED FROM PRIOR STUDY (FEET)	REGULATORY	WITHOUT FLOODWAY	WITH FLOODWAY	INCREASE
MUSKINGUM RIVER									
A	60.6	354	12276	6.3	61	676.3	676.3	677.3	1.0
B	62.2	1065	21121	3.7		678.1	678.1	679.1	1.0
C	64.7	420	13152	5.9		680.7	680.7	681.7	1.0
D	66.7	500	15919	4.9	70	682.5	682.5	683.5	1.0
E	68.6	810	22901	3.2		684.5	684.5	685.5	1.0
F	70.7	540	14760	5.0		686.3	686.3	687.3	1.0
G	72.7	487	14369	5.1	73	688.3	688.3	689.3	1.0
H	74.6	485	13862	5.3		690.3	690.3	691.3	1.0
I	75.1	481	13377	5.1		690.3	690.3	691.3	1.0
J	80.1	561	14595	4.4		699.3	699.3	700.3	1.0
K	82.9	445	10786	6.0		703.3	703.3	704.3	1.0
L	86.0	370	9130	7.1		708.3	708.3	709.3	1.0
M	89.1	1155	16338	3.9		713.8	713.8	714.8	1.0
N	91.8	450	10618	6.1		717.4	717.4	718.4	1.0
O	93.1	653	14071	4.6		718.5	718.5	719.5	1.0
P	94.5	3778	32601	1.9		720.9	720.9	721.9	1.0
Q	97.9	2883	22032	2.9		725.8	725.8	726.8	1.0
R	100.5	1800	25895	2.5		729.4	729.4	730.4	1.0


BRIDGE LOCATION

<sup>1</sup>Miles above confluence with Ohio River

TABLE 9

FEDERAL EMERGENCY MANAGEMENT AGENCY  
**MUSKINGUM COUNTY, OH  
AND INCORPORATED AREAS**

**FLOODWAY DATA**  
**MUSKINGUM RIVER**



**NOTES TO USERS**

This map is for use in administering the National Flood Insurance Program. It does not necessarily identify all areas subject to flooding, particularly from local drainage sources of small size. The community map repository should be consulted for possible updated or additional flood hazard information.

To obtain more detailed information in areas where **Base Flood Elevations (BFEs)** and/or **floodways** have been determined, users are encouraged to consult the Flood Profiles and Floodway Data and/or Summary of Stillwater Elevations tables contained within the Flood Insurance Study (FIS) report that accompanies this FIRM. Users should be aware that BFEs shown on the FIRM represent rounded whole-foot elevations. These BFEs are intended for flood insurance rating purposes only and should not be used as the sole source of flood elevation information. Accordingly, flood elevation data presented in the FIS report should be utilized in conjunction with the FIRM for purposes of construction and/or floodplain management.

**Coastal Base Flood Elevations** shown on this map apply only landward of 0.0' North American Vertical Datum of 1988 (NAVD 88). Users of this FIRM should be aware that coastal flood elevations are also provided in the Summary of Stillwater Elevations table in the Flood Insurance Study report for this jurisdiction. Elevations shown in the Summary of Stillwater Elevations table should be used for construction and/or floodplain management purposes when they are higher than the elevations shown on this FIRM.

Boundaries of the **floodways** were computed at cross sections and interpolated between cross sections. The floodways were based on hydraulic considerations with regard to requirements of the National Flood Insurance Program. Floodway widths and other pertinent floodway data are provided in the Flood Insurance Study report for this jurisdiction.

Certain areas not in Special Flood Hazard Areas may be protected by **flood control structures**. Refer to Section 2.4 "Flood Protection Measures" of the Flood Insurance Study report for information on flood control structures for this jurisdiction.

The **projection** used in the preparation of this map was Ohio State Plane South zone 501 (FIPSZONE 3402). The **horizontal datum** was NAD83. Differences in datum, spheroid, projection or state plane zones used in the production of FIRMs for adjacent jurisdictions may result in slight positional differences in map features across jurisdiction boundaries. These differences do not affect the accuracy of this FIRM.

Flood elevations on this map are referenced to the North American Vertical Datum of 1988. These flood elevations must be compared to structure and ground elevations referenced to the same vertical datum. For information regarding conversion between the National Geodetic Vertical Datum of 1929 and the North American Vertical Datum of 1988, visit the National Geodetic Survey website at <http://www.ngs.noaa.gov/> or contact the National Geodetic Survey at the following address:

NGS Information Services  
NOAA NINGS12  
National Geodetic Survey  
SSMC-3, #9202  
1315 East-West Highway  
Silver Spring, Maryland 20910-3282  
(301) 713-3242

To obtain current elevation, description, and/or location information for **bench marks** shown on this map, please contact the Information Services Branch of the National Geodetic Survey at (301) 713-3242, or visit its website at <http://www.ngs.noaa.gov/>.

**Base Map** information shown on this FIRM was derived from the Muskingum County GIS Office from photography dated 2002 or later.

This map reflects more detailed and up-to-date **stream channel configurations** than those shown on the previous FIRM for this jurisdiction. The floodplains and floodways that were transferred from the previous FIRM may have been adjusted to conform to these new stream channel configurations. As a result, the Flood Profiles and Floodway Data tables in the Flood Insurance Study report (which contains authoritative hydraulic data) may reflect stream channel distances that differ from what is shown on this map.

**Corporate limits** shown on this map are based on the best data available at the time of publication. Because changes due to annexations or de-annexations may have occurred after this map was published, map users should contact appropriate community officials to verify current corporate limit locations.


Please refer to the separately printed **Map Index** for an overview map of the county showing the layout of map panels; community map repository addresses; and a Listing of Communities table containing National Flood Insurance Program dates for each community as well as a listing of the panels on which each community is located.

Contact the **FEMA Map Service Center** at 1-800-358-9616 for information on available products associated with this FIRM. Available products may include previously issued Letters of Map Change, a Flood Insurance Study report, and/or digital versions of this map. The FEMA Map Service Center may also be reached by Fax at 1-800-358-9620 and its website at <http://msc.fema.gov/>.


If you have **questions about this map** or questions concerning the National Flood Insurance Program in general, please call 1-877-FEMA-MAP (1-877-336-2627) or visit the FEMA website at <http://www.fema.gov/business/nfip/>.

The **profile base lines** depicted on this map represent the hydraulic modeling baselines that match the flood profiles in the FIS report. As a result of improved topographic data, the **profile base line**, in some cases, may deviate significantly from the channel centerline or appear outside the SFHA.

**PANEL INDEX**



Panel Not Printed



**LEGEND**

**SPECIAL FLOOD HAZARD AREAS SUBJECT TO INUNDATION BY THE 1% ANNUAL CHANCE FLOOD**

The 1% annual chance flood (100 year flood), also known as the base flood, is the flood that has a 1% chance of being equaled or exceeded in any given year. The Special Flood Hazard Area is the area subject to flooding by the 1% annual chance flood. Areas of Special Flood Hazard may include Zones A, AE, AH, AO, AR, A99, V, and VE. The Base Flood Elevation is the water-surface elevation of the 1% annual chance flood.

**ZONE A** No Base Flood Elevations determined.  
**ZONE AE** Base Flood Elevations determined.  
**ZONE AH** Flood depths of 1 to 3 feet (usually areas of ponding); Base Flood Elevations determined.  
**ZONE AO** Flood depths of 1 to 3 feet (usually sheet flow on sloping terrain); average depths determined. For areas of alluvial fan flooding, velocities also determined.  
**ZONE AR** Area of special flood hazard formerly protected from the 1% annual chance flood event by a flood control system that was subsequently determined. Zone AR indicates that the former flood control system is being restored to provide protection from the 1% annual chance or greater flood.  
**ZONE A99** Area to be protected from 1% annual chance flood event by a Federal flood protection system under construction; no Base Flood Elevations determined.  
**ZONE V** Coastal flood zone with velocity hazard (wave action); no Base Flood Elevations determined.  
**ZONE VE** Coastal flood zone with velocity hazard (wave action); Base Flood Elevations determined.

**FLOODWAY AREAS IN ZONE AE**

The floodway is the channel of a stream plus any adjacent floodplain areas that must be kept free of encroachment so that the 1% annual chance flood can be carried without substantial increases in flood heights.

**OTHER FLOOD AREAS**

**ZONE X** Areas of 0.2% annual chance flood; areas of 1% annual chance flood with average depths of less than 1 foot or with drainage areas less than 1 square mile; and areas protected by levees from 1% annual chance flood.

**OTHER AREAS**

**ZONE X** Areas determined to be outside of the 0.2% annual chance floodplain.  
**ZONE D** Areas in which flood hazards are undetermined, but possible.

**COASTAL BARRIER RESOURCES SYSTEM (CBRS) AREAS**

**OTHERWISE PROTECTED AREAS (OPAs)**

CBRS areas and OPAs are normally located within or adjacent to Special Flood Hazard Areas.

1% annual chance floodplain boundary  
 0.2% annual chance floodplain boundary  
 Floodway boundary  
 Zone D boundary  
 CBRS and OPA boundary

Boundary dividing Special Flood Hazard Areas of different Base Flood Elevations, flood depths or flood velocities.  
 Base Flood Elevation line and value; elevation in feet\*  
 Base Flood Elevation value where uniform within zone; elevation in feet\*

\*Referenced to the North American Vertical Datum of 1988

— A — A — Cross section line  
 — T — T — Transect line  
 — B — Bridge  
 — C — Culvert


85° 02' 45.0"; 41° 24' 22.5"  
 487,000 M  
 2250000 FT  
 KA0015 X  
 M1.5  
 River Mile

**MAP REPOSITORY**  
 Refer to listing of Map Repositories on Map Index

**EFFECTIVE DATE OF COUNTYWIDE FLOOD INSURANCE RATE MAP**  
 July 6, 2010

**EFFECTIVE DATE(S) OF REVISION(S) TO THIS PANEL**

For community map revision history prior to countywide mapping refer to the Community Map History table located in the Flood Insurance Study report for this jurisdiction.  
 To determine if flood insurance is available in this community, contact your insurance agent or call the National Flood Insurance Program at 1-800-638-6629.



**NATIONAL FLOOD INSURANCE PROGRAM**

**PANEL 0445G**

**FIRM**  
**FLOOD INSURANCE RATE MAP**  
**MUSKINGUM COUNTY, OHIO**  
**AND INCORPORATED AREAS**

**PANEL 445 OF 500**  
 (SEE MAP INDEX FOR FIRM PANEL LAYOUT)

**CONTAINS:**  
 COMMUNITY: MUSKINGUM COUNTY  
 NUMBER: 390425  
 PANEL: 0445  
 SUFFIX: G

Notice to User: The Map Number shown below should be used when placing map orders; the Community Number shown above should be used on insurance applications for the subject community.

**MAP NUMBER**  
 39119C0445G  
**EFFECTIVE DATE**  
 JULY 6, 2010

**Federal Emergency Management Agency**