NOTES GENERAL

PROTECTION FOR TRAFFIC.

THE CONTRACTOR FALL PROVIDE A SUITABLE FIELD OFFICE HAVING A MINIMUM OF 800 SQ. FT. OF FLOOR SPACE WHICH SHALL BE IN ACCORDANCE WITH 619.02. PAYMENT SHALL BE INCLUDED IN THE LUMP SUM PRICE BID FOR ITEM 624, MOBILIZATION, AS PER PLAN.

ROUNDING OF CORNERS SHOWN ON CROSS SECTIONS THE ROUNDED CORNERS SHOWN ON THE TYPICAL SECTIONS, APPLY TO ALL CROSS SECTIONS ELN THOUGH OTHERWISE SHOWN ON THESE PLANS.

UNDERGROUND JTILITIES THE LOCATIONS OF THE UNDERGROUND UTILITIES SHOWN ON THE PLANS ARE AS OBTAINED FOM THE OWNERS OF THE UTILITY AS REQUIRED BY

UTILITY OWNERS IP THE FOLLOWING I TIES AND OWNERS ARE LOCATED WITHIN THE WORK LIMITS OF THIS PERIOD:

OHIO BELL 160 NORTH 6th I EET ZANESVILLE, OH! :37Ø1 PHONE: 614-454-514

COLUMBIA GAS OF OHIO INC. CAMBRIDGE, OHIO 43725 PHONE: 614-452-5467

AND SEWER DEPT. 7 SHAWNEE AVE. S ZANESVILLE OHIO 43701 PHONE: 614-453-3113

OHIO POWER COMPANY 301 CLEVELAND AVENUE SW. P.O. BOX 24400 CANTON, OHIO 44731-4400 PHONE: 216-656-3173

ZANESVILLE CITY WATER & SEWER CO. ROOM 2 MUNICIPAL BUILDING ZANESVILLE, DHIO 43701 PHONE: 614-455-0650

CONTINGENCY QUANTITIES THE CONTRACT OR SHALL NOT ORDER MATERIALS OR PERFORM WORK LISTED IN THE GENERAL SUMMARY FOR ITEMS DESIGNATED BY PLAN NOTE TO BE SED "AS DIRECTED BY THE ENGINEER" UNLESS AUTHOR-IZED BY THE NGINEER. THE ACTUAL WORK LOCATIONS AND QUANTITIES USED AT THE ENGINEER'S DISCRETION SHALL BE MADE A MATTER OF RECORD BY INCORPORATION INTO THE FINAL CHANGE ORDER GOVERNING

COMPLETION OF THIS PROJECT.

REMOVAL () TREES OR STUMPS ALL TREES AND STUMPS SPECIFICALLY MARKED FOR REMOVAL WITHIN THE CONSTRUCTION LIMITS OF THIS PROJECT SHALL BE REMOVED UNDER THE LUMP SUM PRICE BID FOR ITEM 201, CLEARING AND GRUBBING, EXCEPT THAT THOSE TREES FOR WHICH PROTECTION AND PRESERVATION WORK IS INDICATED ELSEWHERE IN THESE PLANS SHALL NOT BE REMOVED.

THE FOLLOWING S AN APPROXIMATE ESTIMATE OF THE NUMBER OF TREES AND STUMPS TO 35 REMOVED:

SIZES	NO. TREES	NO. STUMPS	TOTA
18''	195	_	75
30"	K S	- ·	5
48''	1		1
6Ø''	-		_

THE ABOVE ESTIMATE IS APPROXIMATE AND THE STATE OF OHIO RESERVES THE RIGHT TO CROER THE REMOVAL OF ADDITIONAL TREES OR STUMPS OUT-SIDE OF THE LIMITS OF CONSTRUCTION BUT WITHIN THE RIGHT-OF-WAY AND/OR EASEMENT LINES. PAYMENT FOR THE REMOVAL OF THESE ADDI-TIONAL TREES OR STUMPS SHALL BE INCLUDED IN THE LUMP SUM PRICE BID FOR ITEM 201, CLEARING AND GRUBBING.

.MONUMENTS

4 🔍

MONUMENTS SHALL BE CONSTRUCTED IN ACCORDANCE WITH DETAILS SHOWN ON STANDARD CONSTRUCTION DRAWING MC 1. FOR LOCATIONS, SEE SHEET NO. 45.

LOCATION OF GUARDRAIL THE LOCATIONS OF GUARDRAIL RUNS, AS SHOWN IN THESE PLANS, ARE SUBJECT TO ADJUSTMENT PRIOR TO FINAL ACCEPTANCE. THE ENGINEER SHALL BE SATISFIED THAT ALL INSTALLATIONS WILL AFFORD MAXIMUM

QUANTITIES FOR SEEDING ARE CALCULATED FOR THE SOIL AREAS BETWEEN TEN (10) FEET OUTSIDE THE WORK LIMITS, AS SHOWN ON THE CROSS SECTIONS, OR TO THE RIGHT-OF-WAY LINE, IF SUCH LINE IS LESS THAN TEN (10) FEET FROM THE WORK LIMITS.

ITEM 203, PROOF ROLLING AN ESTIMATÉD QUANTITY FOR THIS ITEM HAS BEEN PROVIDED IN THE GENERAL SUMMARY FOR USE AS DIRECTED BY THE ENGINEER.

WATERING AND MOWING PERMANENT SEEDED AREAS THE FOLLOWING ESTIMATED QUANTITIES ARE TO BE USED AS DIRECTED BY THE ENGINEER TO PROMOTE GROWTH AND TO CARE FOR THE PERMANENT SEEDED AREAS, AS PER 659.09:

ω59 WATER 659 MOWING

3Ø M.GAL. 60 M SQ. FT.

TEMPORARY SOIL EROSION AND SEDIMENT CONTROL THE FOLLOWING ESTIMATED QUANTITIES ARE TO BE USED AS DIRECTED BY THE ENGINEER, FOR TEMPORARY EROSION AND SEDIMENT CONTROL MEASURES:

TEMPORARY SEEDING AND MULCHING STRAW OR HAY BALES	7DGD 184	SQ. YD. EACH
TEMPORARY SLOPE DRAINS	50	LIN. FT.
TEMPORARY BENCHES, DIKES,		
DAMS AND SEDIMENT BASINS	250	CU. YD.
FILTER FABRIC FENCE	150	LIN. FT.
TYPE C ROCK CHANNEL		
PROTECTION (WITHOUT FILTER)	2	CU. YD.
MOWING	08	M SQ. FT
COMMERCIAL FERTILIZER	1.50	TON
REPAIR SEEDING AND MULCHING	1750	SQ. YD.
WATER	15	M GAL.
	STRAW OR HAY BALES TEMPORARY SLOPE DRAINS TEMPORARY BENCHES, DIKES, DAMS AND SEDIMENT BASINS FILTER FABRIC FENCE TYPE C ROCK CHANNEL PROTECTION (WITHOUT FILTER) MOWING COMMERCIAL FERTILIZER REPAIR SEEDING AND MULCHING	STRAW OR HAY BALES TEMPORARY SLOPE DRAINS TEMPORARY BENCHES, DIKES, DAMS AND SEDIMENT BASINS FILTER FABRIC FENCE TYPE C ROCK CHANNEL PROTECTION (WITHOUT FILTER) ROWING COMMERCIAL FERTILIZER REPAIR SEEDING AND MULCHING 184 184 184 184 184 184 184 18

CONNECTION TO EXISTING PIPE WHERE THE PLANS PROVIDE FOR PROPOSED CONDUIT TO BE CONNECTED TO, OR TO CROSS EITHER OVER OR UNDER AN EXISTING SEWER, IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO LOCATE THE EXISTING PIPE BOTH AS TO LINE AND GRADE BEFORE HE STARTS TO LAY THE PROPOSED

THE UNIT PRICE BID FOR THE PERTINENT 603 CONDUIT ITEMS.

ITEM 605 AGGREGATE DRAINS AGGREGATE DRAINS SHALL BE PLACED AT FIFTY (50) FOOT INTERVALS ON EACH SIDE OF NORMAL CROWNED SECTIONS AND AT TWENTY-FIVE (25) FOOT INTERVALS ON THE LOW SIDE ONLY OF SUPERELEVATED SECTIONS, EXCEPT WHERE ITEM 605 PIPE UNDERDRAINS HAVE BEEN PROVIDED.

AN AGGREGATE DRAIN SHALL BE PLACED AT THE LOW POINT OF EACH SAG VERTICAL CURVE.

ITEMS 601, 660, 667 AND 670 ARE PROVIDED IN THE PLANS FOR EROSION CONTROL. ROCK OF A STABLE NATURE WILL NOT BE REMOVED IN ORDER TO PLACE ANY OF THESE ITEMS, AND TURF OF A STABLE NATURE WILL NOT BE REMOVED IN ORDER TO PLACE 660, 667 OR 670. THE ENGINEER SHALL CHECK AND NON-PERFORM QUANTITIES OR ADJUST LOCATIONS AND QUANTITIES FOR THESE ITEMS WHERE INDICATED BY FIELD CONDITIONS DURING CONSTRUCTION.

TREATED SANITARY FLOW INTO HIGHWAY DRAINAGE SYSTEMS TREATED SANITARY FLOW MAY BE DISCHARGED INTO THE HIGHWAY DRAINAGE

SYSTEM PROVIDED THE OWNER HAS SECURED THE APPROVAL AND PERMIT FROM THE LOCAL HEALTH AUTHORITIES TO HAVE THE CONNECTION MADE.

IN EACH CASE WHERE A PERMIT HAS BEEN ISSUED FOR A SANITARY CONNECTION TO BE MADE INTO A HIGHWAY DRAINAGE CONDUIT, IT SHALL BE PROVIDED WITH AN INSPECTION WELL, IN ACCORDANCE WITH THE DETAIL SHOWN ON STANDARD DRAWING MC-8.

THE FOLLOWING ESTIMATED QUANTITIES HAVE BEEN INCLUDED IN THE GENERAL SUMMARY, FOR USE AS DIRECTED BY THE ENGINEER, IN MAKING THE ABOVE DESCRIBED CONNECTIONS:

ITEM 603, 6" CONDUIT, TYPE C 50 LIN. FT. *ITEM 604, INSPECTION WELLS 1 EACH

NECESSARY BENDS OR BRANCHES SHALL BE INCLUDED FOR PAYMENT IN THE PERTINENT CONDUIT ITEM.

NONE OF THE ABOVE MATERIALS SHALL BE ORDERED BY THE CONTRACTOR UNTIL AUTHORIZED BY THE ENGINEER.

*NO INSPECTION WELL IS REQUIRED IF EFFLUENT IS DISCHARGED INTO AN OPEN DITCH, CHANNEL, CATCH BASIN OR MANHOLE.

HOUSE CONNECTIONS EXISTING ROOF DRAINS, FOOTER DRAINS OR YARD DRAINS, DISTURBED BY THE PROPOSED WORK, SHALL BE PROVIDED WITH UNOBSTRUCTED OUTLETS BY CONNECTING TO A STORM SEWER, MANHOLE, CATCH BASIN OR THROUGH THE

THE LOCATION, TYPE, SIZE AND GRADE OF REQUIRED REPLACEMENTS WILL BE DETERMINED BY THE ENGINEER DURING CONSTRUCTION.

THE FOLLOWING ESTIMATED QUANTITIES HAVE BEEN INCLUDED IN THE GENERAL SUMMARY FOR THE WORK NOTED ABOVE:

ITEM 603 4" CONDUIT, TYPE E, 711.29 50 L.F. ITEM 603 6" CONDUIT, TYPE E 50 L.F. ITEM 603 6" CONDUIT, TYPE F 5Ø L.F.

NONE OF THE ABOVE MATERIALS SHALL BE ORDERED BY THE CONTRACTOR UNTIL REQUESTED BY THE ENGINEER.

CONDUIT END TREATMENT IMMEDIATELY AFTER PLACEMENT OF ANY CONDUITS, THE CONTRACTOR SHALL CONSTRUCT THE END TREATMENTS REQUIRED BY THE PLANS AT BOTH THE OUT-LET AND INLET ENDS. THIS SHALL INCLUDE HEADWALLS, CONCRETE RIPRAP, ROCK CHANNEL PROTECTION, SODDING, ETC.

DUST CONTROL THE FOLLOWING QUANTITIES FOR DUST CONTROL HAVE BEEN ADDED TO BE USED AS DIRECTED BY THE ENGINEER.

ITEM 616 CALCIUM CHLORIDE ITEM 616 WATER

10 TONS 100 M.GAL

EARTHWORK ALONG CURVED ALIGNMENT THE CENTROIDS OF AREAS ON THE CROSS SECTION SHEETS ARE INDICATED BY A VERTICAL LINE. THE LENGTH OF VOLUME ALONG THE CURVE IS COMPUTED BASED UPON THE AVERAGE OF THE ADJACENT CENTROIDS. INDIVDUAL VOLUMES ALONG THE CURVED ALIGNMENT ARE COMPUTED BY AN ELECTRONIC COMPUTER, AND THEN TOTALED. THE TOTAL VOLUME OF EACH SECTION IS SHOWN ON THE CROSS SECTION SHEETS.

NO.3 AND 3A CATCH BASINS THE OFFSET SHOWN ON THE PLANS IS TO THE FACE OF THE CURB. THE ELEVATION SHOWN ON THE PLAN IS A HALF INCH BELOW THE GUTTER LINE.

MAINTENANCE OF TRAFFIC THE MAINTENANCE OF TRAFFIC SHALL BE GOVERNED BY THE "OHIO MANUAL OF UNIFORN TRAFFIC CONTROL DEVICES" FOR STREETS AND HIGHWAYS, HEREINAFTER CALLED THE MANUAL, AND AS SUPPLEMENTED BY PERTINENT ITEMS OF THE STATE OF OHIO DEPARTMENT OF

GENERAL NOTES

TTL 11-87

FHWA REGION

STATE

ОНЮ

MUS-CR 719

MUSKINGUM COUNTY

55

SECTION 153.64 ORC

216 HIGHLAND AVENUE

S. ZANESVILLE WATER

NATIONAL GAS AND OIL CORP. 1500 GRANVILLE ROAD NEWARK, OHIO 43055 PHONE: 614-344-2102

PAYMENT FOR ALL OPERATIONS DESCRIBED ABOVE SHALL BE INCLUDED IN