

29-01-05-05-000 B

- (1) S 86° 29' 03" W – 109.65 feet, to a point;
- (2) S 69° 25' 47" W – 259.65 feet, to a point;
- (3) N 83° 23' 49" W – 82.30 feet, to a point;
- (4) S 69° 18' 17" W – 208.88 feet, to a point, which bears S 39° 11' 36" E – 36.30 feet from a found reference iron pin of 5/8 – inch rebar;
- (5) S 50° 38' 00" W – 774.60 feet, to a point, which bears S 1° 11' 17" E – 72.00 feet from a found reference iron pin of 5/8 – inch rebar;
- (6) N 84° 19' 32" W – 132.00 feet, to a point;
- (7) S 78° 01' 54" W – 1365.19 feet, to a point;

thence leaving said Wakatomica Creek centerline, N 0° 56' 48" E – 99.85 feet, to a found iron pin of 5/8 – inch rebar, marking the Northeast corner of a 21.826 acre tract conveyed to Thomas W. & Michael T. Graham (2826/515);

thence along the North line of said Graham lands, N 87° 57' 46" W – 707.05 feet, to a point in the centerline of Wakatomica Creek, said point bears S 87° 57' 46" E 75.00 feet from a found reference iron pin of 5/8 – inch rebar;

thence along the centerline of Wakatomica Creek, the following (6) courses:

- (1) N 65° 18' 55" W – 203.47 feet, to a point, which bears N 41° 05' 54" E – 39.33 feet, from a found reference iron pin of 5/8 – inch rebar;
- (2) N 43° 15' 22" W – 657.12 feet, to a point, which bears N 56° 58' 12" E – 39.90 feet, from a found reference iron pin of 5/8 – inch rebar;
- (3) N 23° 26' 00" W – 600.02 feet, to a point, which bears N 57° 14' 54" E – 40.27 feet, from a found reference iron pin of 5/8 – inch rebar;
- (4) N 37° 17' 13" W – 337.46 feet, to a point, which bears N 79° 07' 23" E – 37.42 feet, from a found reference iron pin of 5/8 – inch rebar;
- (5) N 16° 48' 23" W – 452.25 feet, to a point, which bears N 56° 28' 14" E – 49.27 feet, from a found reference iron pin of 5/8 – inch rebar;
- (6) N 30° 15' 46" W – 198.45 feet, to a point on the centerline of a bridge;