## ALAN DONAKER SURVEYING

## Alan Donaker, P.S. 19849 TR 383 Walhonding, OH 43843

Fax: (740) 327-1083 Phone: (740) 327-7001

T-2

Being 2.147 acres, more or less, in Lot 2, in the First Quarter, Township 3 North, Range 9 West, United States Military Lands, in the Township of Jackson, in the County of Muskingum, in the State of Ohio, conveyed to Vicki S. Smith, DR 2466-102 (part), Parcel #29-20-41-05-005 (part), and more particularly described as follows:

Commencing at a %" rebar found at the Northeast corner of Lot 2:

thence, with the South line of Coshocton County, the following 4 courses:

- 1. thence, S. 89° 26' 03" W. a distance of 191.59' to a \%" rebar found;
- 2. thence, S. 89° 26' 03" W. a distance of 70.54' to a %" rebar found;
- 3. thence, S. 89° 26' 03" W. a distance of 300.00' to a %" rebar found;
- 4. thence, S. 89° 26' 03" W. a distance of 139.63' to a %" rebar found, said rebar being the TRUE POINT OF BEGINNING:

thence, with the property line of John C. and Dorothy K. Hindel, DR 604-212, S. 24° 17' 56" W. a distance of 30.33' to a point in the centerline of Scout Road, County Road 314;

thence, with the centerline of Scout Road, County Road 314, the following 2 courses:

- 1. thence, with a curve to the left, the curve data for which is: D = 71° 44' 27", R = 184.15', L = 230.58', Ch. B. S. 34° 16' 55" W., Ch. L. 215.81' to a point;
- 2. thence, S. 01° 35' 18" E. a distance of 120.38' to a point;

thence, through the property of Vicki S. Smith, DR 2466-102, the following 2 courses:

- 1. thence, S. 89° 26' 03" W. a distance of 20.00' to a \%" rebar set;
- 2. thence, S. 89° 26' 03" W. a distance of 350.75' to a %" rebar set;

thence, with the property line of Robert D. Hindel, DR 2466-97, the following 2 courses:

- 1. thence, N. 03° 12' 01" E. a distance of 83.72' to a 1/8" rebar found;
- 2. thence, N. 03° 12' 01" E. a distance of 20.00' to a 5%" rebar found;

thence, with the property line of Richard K. and Venetia L. Morin, DR 2386-371, the following 2 courses:

- 1. thence, N. 61° 11' 09" E. a distance of 129.91' to a railroad spike found;
- 2. thence, N. 42° 46' 09" E. a distance of 219.98' to a 1/8" rebar found;

thence, with the South line of Coshocton County, N. 89° 26' 03" E. a distance of 232.45' to the TRUE POINT OF BEGINNING, containing 2.147 acres, more or less, including public road right-of-way and is subject to all easements, rights-of-way, or restrictions, whether recorded or implied.

Bearings are based on DR 1023-185 and are for angular calculations only.

All %" rebars set are 30" long with plastic cap marked "AMD 8050". Page 1 of 2