

W.J. BIEDENBACH AND ASSOCIATES
SURVEYING AND MAPPING
3120 LISA LANE, ZANESVILLE, OHIO 43701
(614) 453-4850

44-56-02-05-011
5063 ARSLEN CT

DESCRIPTION FOR CONVEYANCE
R. WILSON
PARCEL NUMBER 44-44-56-02-05 (PART)

BEING A PART OF THE SOUTHEAST QUARTER OF SECTION 21, TOWNSHIP 2, RANGE 8, OF THE UNITED STATES MILITARY LANDS, MUSKINGUM TOWNSHIP, MUSKINGUM COUNTY, OHIO AND BEING FURTHER DESCRIBED AS FOLLOWS:

COMMENCING AT AN EXISTING 1/2 INCH PIPE MARKING THE SOUTHWEST CORNER OF LOT NUMBER 16 OF PRICE ESTATES AS RECORDED IN PLAT BOOK 14, PAGE 134 OF THE MUSKINGUM COUNTY PLAT RECORDS; THENCE SOUTH 00 DEGREES 07 MINUTES 00 SECONDS WEST 1075.49 FEET TO THE PLACE OF BEGINNING OF THE TRACT HEREIN INTENDED TO BE DESCRIBED, PASSING AN IRON PIN SET AT 769.70 FEET; THENCE SOUTH 89 DEGREES 43 MINUTES 42 SECONDS EAST 820.82 FEET TO AN IRON PIN SET, PASSING AN IRON PIN SET AT 15.00 FEET; THENCE WITH A CURVE TO THE LEFT HAVING A RADIUS OF 50.00 FEET (CHORD BEARING NORTH 42 DEGREES 30 MINUTES 50 SECONDS EAST 70.71 FEET) AN ARC DISTANCE OF 78.53 FEET TO AN IRON PIN SET; THENCE SOUTH 02 DEGREES 29 MINUTES 07 SECONDS EAST 301.18 FEET TO AN EXISTING 5/8 INCH REBAR; THENCE NORTH 89 DEGREES 43 MINUTES 42 SECONDS WEST 882.17 FEET ALONG THE LINE SEPARATING MUSKINGUM TOWNSHIP AND FALLS TOWNSHIP TO AN EXISTING 5/8 INCH REBAR; THENCE NORTH 00 DEGREES 07 MINUTES 00 SECONDS EAST 248.48 FEET TO THE PLACE OF BEGINNING.

CONTAINING 5.014 MORE OR LESS ACRES, SUBJECT TO ALL APPLICABLE EASEMENTS.

DESCRIPTION APPROVED
FOR AUDITOR'S TRANSFER

BY _____

OFFICE COPY
NOT RECORDABLE

ALSO THE FOLLOWING EASEMENT FOR INGRESS AND EGRESS

BEING A PART OF THE SOUTHEAST QUARTER OF SECTION 21, TOWNSHIP 2, RANGE 8, OF THE UNITED STATES MILITARY LANDS, MUSKINGUM TOWNSHIP, MUSKINGUM COUNTY, OHIO AND BEING FURTHER DESCRIBED AS FOLLOWS:

COMMENCING AT AN EXISTING 1/2 INCH PIPE MARKING THE SOUTHWEST CORNER OF LOT NUMBER 16 OF PRICE ESTATES AS RECORDED IN PLAT BOOK 14, PAGE 134 OF THE MUSKINGUM COUNTY PLAT RECORDS; THENCE SOUTH 00 DEGREES 07 MINUTES 00 SECONDS WEST 1075.49 FEET TO A POINT, PASSING AN IRON PIN SET AT 768.70 FEET; THENCE SOUTH 89 DEGREES 43 MINUTES 42 SECONDS EAST 820.82 FEET TO AN IRON PIN SET, SAID IRON PIN BEING THE PLACE OF BEGINNING OF THE EASEMENT HEREBY INTENDED TO BE DESCRIBED, PASSING AN IRON PIN SET AT 15.00 FEET; THENCE WITH A CURVE TO THE RIGHT HAVING A RADIUS OF 50.00 FEET (CHORD BEARING NORTH 47 DEGREES 29 MINUTES 07 SECONDS WEST 70.71 FEET) AN ARC DISTANCE OF 78.53 FEET TO AN IRON PIN SET; THENCE WITH A CURVE TO THE RIGHT HAVING A RADIUS OF 50.00 FEET (CHORD BEARING NORTH 27 DEGREES 32 MINUTES 03 SECONDS EAST 50.03 FEET) AN ARC DISTANCE OF 52.39 FEET TO AN IRON PIN SET; THENCE NORTH 58 DEGREES 54 MINUTES 15 SECONDS EAST 47.24 FEET TO AN IRON PIN SET; THENCE WITH A CURVE TO THE LEFT HAVING A RADIUS OF 50.00 FEET (CHORD BEARING NORTH 21 DEGREES 28 MINUTES 39 SECONDS EAST 40.61 FEET) AN ARC DISTANCE OF 41.81 FEET TO AN IRON PIN SET; THENCE NORTH 02 DEGREES 29 MINUTES 07 SECONDS WEST 184.09 FEET TO AN IRON PIN SET, PASSING AN IRON PIN SET AT 72.46 FEET; THENCE WITH A CURVE TO THE RIGHT HAVING A RADIUS OF 125.00 FEET (CHORD BEARING OF NORTH 06 DEGREES 43 MINUTES 15 SECONDS EAST 40.00 FEET) AN ARC DISTANCE OF 40.17 FEET TO AN IRON PIN SET; THENCE WITH A CURVE TO THE RIGHT HAVING A RADIUS OF 125.00 FEET (CHORD BEARING NORTH 52 DEGREES 47 MINUTES 48 SECONDS EAST 150.00 FEET) AN ARC DISTANCE OF 160.88 FEET TO AN IRON PIN SET; THENCE NORTH 89 DEGREES 40 MINUTES 00 SECONDS EAST 660.60 FEET TO AN EXISTING IRON PIN 5/8 INCH REBAR; THENCE NORTH 51 DEGREES 09 MINUTES 59 SECONDS EAST 274.13 FEET ALONG THE SOUTH LINE OF OCCASIONALLY MORE OR LESS ACRE TRACT TO THE CENTER OF COUNTY (ROAD NUMBER 2) (DRESDEN ROAD), PASSING AN EXISTING IRON PIN (1/2 INCH ID PIPE) AT 245.18 FEET; THENCE SOUTH 47 DEGREES 18 MINUTES 41 SECONDS EAST 50.31 FEET TO A POINT IN THE SAID CENTER; THENCE LEAVING THE SAID CENTER SOUTH 49 DEGREES 05 MINUTES 00 SECONDS WEST 300.19 FEET ALONG THE NORTHERLY LINE OF A 0.846 MORE OR LESS ACRE TRACT TO AN EXISTING IRON PIN (5/8 INCH REBAR), PASSING AN EXISTING IRON PIN (5/8 INCH REBAR) AT 30.19 FEET; THENCE NORTH 50 DEGREES 47 MINUTES 20 SECONDS WEST 13.98 FEET TO A POINT; THENCE SOUTH 89 DEGREES 40 MINUTES 00 SECONDS WEST 673.10 FEET TO AN IRON PIN SET; THENCE WITH A CURVE TO THE LEFT HAVING A RADIUS OF 75.00 FEET (CHORD BEARING OF SOUTH 43 DEGREES 35 MINUTES 27 SECONDS WEST 108.04 FEET) AN ARC DISTANCE OF 120.63 FEET TO AN IRON PIN SET; THENCE SOUTH 02 DEGREES 29 MINUTES 07 SECONDS EAST 259.90 FEET TO AN IRON PIN SET; THENCE NORTH 89 DEGREES 43 MINUTES 42 SECONDS WEST 33.03 FEET TO AN IRON PIN SET; THENCE SOUTH 02 DEGREES 29 MINUTES 07 SECONDS EAST 28.82 FEET TO AN IRON PIN SET; THENCE WITH A CURVE TO THE RIGHT HAVING A RADIUS OF 50.00 FEET (CHORD BEARING SOUTH 42 DEGREES 30 MINUTES 50 SECONDS WEST 70.71) AN ARC DISTANCE OF 78.53 FEET TO THE PLACE OF BEGINNING.

ALL IRON PINS SET ARE 5/8 INCH X 30 INCH REBAR WITH PLASTIC IDENTIFICATION CAPS. BEARINGS ARE BASED ON THE PLAT BEARING OF THE SOUTH LINE OF PRICE ESTATES (PLAT BOOK 14 PAGE 134).

I HEREBY CERTIFY TO THE BEST OF MY KNOWLEDGE AND BELIEF THIS SURVEY AND DESCRIPTION TO BE CORRECT AS SURVEYED BY ME, THIS 17TH DAY OF JUNE 1987.

NOT A COPY
REGISTERED SURVEYOR

D2648F R. WILSON



