

SITUATED IN

The State of Ohio, County of Muskingum, Township of Springfield,
being part of the Northwest Quarter of Section 6, T15, R14.

ReSurvey

BASIS OF BEARING

Bearings are based on State Plane Grid Coordinates
& Distances, NAD83, Ohio South, per GPS Observation.

LEGEND

- Iron Pin Set, 5/8" rebar
- Iron Pin Found
- Z— Property Hook
- Drill Hole Set
- ⊠ Stone Found
- ⊗ Axle Found
- Point Not Marked

DESCRIPTION

APPROVED

By: *[Signature]* 11/13/2022

REFERENCES

* As Noted on Plat
www.muskingumcountyauditor.org
www.mceo.org
<http://recorder.muskingumcounty.org>


LINE TABLE

LINE	BEARING	DISTANCE
L1	N 27°53'41" W	77.19'
L2	N 50°14'26" W	316.85'
L3	N 48°16'32" W	174.45'
L4	N 45°51'24" W	165.84'
L5	N 50°15'45" W	70.97'
L6	N 64°39'14" W	46.08'
L7	N 70°17'44" W	50.05'
L8	N 85°10'38" W	15.62'

CURVE TABLE

CURVE	RADIUS	ARC LENGTH	CHORD LENGTH	CHORD BEARING	DELTA ANGLE
C1	506.89'	236.58'	234.43'	N 36°52'12" W	26°44'28"
C2	271.64'	65.46'	65.30'	N 57°45'00" W	13°48'27"
C3	731.68'	95.21'	95.15'	N 80°50'16" W	7°27'21"

Graphic Scale



(IN FEET)

1 inch = 250 ft.



OFFICE COPY
NOT RECORDABLE

Brian Kelly McPeck
Reg. Surveyor No. 8517

Date

This plat was prepared by McPeck Land Surveying, LLC
in accordance with Chapter 4733-37 of the Administrative Code,
and is intended to be used for the legal transfer of the property
described and does not intend to describe all or any easements of
record, nor encroachments unless otherwise intended.



www.mcpeeklandsurveying.com
email: brian@mcpeeklandsurveying.com
340 Robin Hood Ln., * Zanesville, Oh 43701 * 740.704.6073