

Jacob & Loretta Shetler DR 1128-387 +/-10.361 Ac.

Being a part of the Northeast Quarter of the Southwest Quarter of Sec. 11, Township 3, Range 6, Adams Township, Muskingum County, also being part of the lands now owned by Jacob & Loretta Shetler as recorded in DR 1128-387 of the Muskingum County Recorder more fully described as follows.

Beginning at an iron pin found at the Southeast Corner of the Northeast Quarter of the Southwest Quarter of Sec. 11, T3, R6, Adams Township, said iron pin also being the Northeast corner of the lands now owned by Tobe W. & Martha Hostetler (DR 1097-350) and on the west line of the lands now owned by Duane E. Bell & Beth Quinn (DR 1129-636);

Thence with the north line of said Hostetler's lands, North 87 degrees 42 minutes 07 seconds West, 458.17 feet to a railroad spike set in the center of Bell Road (T-169), said railroad spike set is referenced by an iron pin found (Finley) which bears, North 87 degrees 42 minutes 07 seconds West, 20.06 feet;

Thence with the centerline of said Bell Road and with the east line of the lands now owned by Tobe W. & Martha Hostetler (DR 1144-648) the following 4 courses:

- 1. North 41 degrees 45 minutes 16 seconds West, 226.14 feet to a point;
- 2. North 36 degrees 20 minutes 20 seconds West, 63.54 feet to a point;
- 3. North 29 degrees 06 minutes 21 seconds West, 86.85 feet to point;
- 4. North 25 degrees 03 minutes 09 seconds West, 295.12 feet to a railroad spike set in said centerline;

Thence leaving said centerline and said Hostetler's east line and going through said Shetler's lands the following 2 courses:

- 1. North 42 degrees 29 minutes 59 seconds East, 89.07 feet to an iron pin set;
- 2. North 86 degrees 47 minutes 45 seconds East, 772.94 feet to an iron pin set on the west line of said Bell & Quinn's lands, said iron pin also being on the mid-section line and referenced by a corner post which bears, North 01 degrees 32 minutes 51 seconds East, 382.10 feet;

Thenc with the mid-section line and the west line of said Bell & Quinn's lands, South 01 degrees 32 minutes 51 seconds West, 690.62 feet to the

point of beginning, containing 10.361 acres more or less, subject to all legal highways and easements of record.

All bearings described herein are based on the Ohio State Plane Grid Coordinates, NAD83, Ohio South per GPS Observation.

All iron pins set are 5/8 inch by 30 inch steel rebar with plastic identification caps marked MCPEEK PS8517.

The above described 10.361 acreptancel is based on a field survey made by McPeek Land Surveying on October 5th, 2012

Parcel No.

Part of: 02-60-11-09-000 (+/- 10.361 ac.)

SITUATED IN

The State of Ohio, County of Muskingum Township of Adams, and being a part of the NE Qrtr., of the SW Qrtr., of Sec. 11, T3, R6.

BASIS OF BEARING

Bearings are based on State Plane Grid Coordinates, NAD83, Ohio South, per GPS Observation.

Jacob & Loretta Shetler 382.10 DR 1128-387 N 86'47'45" E 772.94 N 42°29'59" E 89.07' Wid-Section C/L Bell Rd. (T-169) Jacob & Loretta Shetler DR 1128-387 29°06'21" W Tobe W. & Martha ±10.361 Ac. 86.85 Hostetler DR 1144-648 N 36°20'20" W 63.54' Approved for Transfer POB- Iron Pin Found at the No On-Lot Sewage SE Crnr. of the NE Qtr. of the SW Qrtr., Sec. 11. Zanesville-Muskingum Co. Health Department N 87°42'07" W 458.17' 20.06 Tobe W. & Martha **APPROVED** Hostetler MUSKINGUM COUNTY PLANNING COMMISSION DIRECTOR DR 1097-350

REFERENCES

Date

* As Noted on Plat www.muskingumcountyauditor.org www.mceo.org http://recorder.muskingumcounty.org

Previous Survey by Terry J. Finley, Sept. 27, 1996. Land Surveyors of America, Inc., February 2000.

Fee Paid

PARCEL NO.

Part of: 02-60-11-09-000(±10.361ac.)

DESCRIPTION
APPROVED
By:

GRAPHIC SCALE


100 200 400

(IN FEET)

1 inch = 200 ft.

<u>LEGEND</u> n Pin Set

- O Iron Pin Set, 5/8" rebar (MCPEEK 8517)
- Iron Pin Found
- ▲ Railroad Spike Set
- **♦** Corner Post Found





mcpeeklandsurveying.com 423 Smithfield Ave., Zanesville, Ohio 43701 740.704.6073



Jacob & Loretta Shetler DR 1128-387 +/-16.000 Ac.

Being a part of the Northeast Quarter of the Southwest Quarter of Sec. 11, Township 3, Range 6, Adams Township, Muskingum County, also being part of the lands now owned by Jacob & Loretta Shetler as recorded in DR 1128-387 of the Muskingum County Recorder more fully described as follows.

Beginning at an iron pin found at the Southeast Corner of the Northeast Quarter of the Southwest Quarter of Sec. 11, T3, R6, Adams Township, said iron pin also being the Northeast corner of the lands now owned by Tobe W. & Martha Hostetler (DR 1097-350) and on the west line of the lands now owned by Duane E. Bell & Beth Quinn (DR 1129-636);

Thence with the north line of said Hostetler's lands, North 87 degrees 42 minutes 07 seconds West, 458.17 feet to a railroad spike set in the center of Bell Road (T-169), said railroad spike set is referenced by an iron pin found (Finley) which bears, North 87 degrees 42 minutes 07 seconds West, 20.06 feet;

Thence with the centerline of said Bell Road and with the east line of the lands now owned by Tobe W. & Martha Hostetler (DR 1144-648) the following 4 courses:

- 1. North 41 degrees 45 minutes 16 seconds West, 226.14 feet to a point;
- 2. North 36 degrees 20 minutes 20 seconds West, 63.54 feet to a point;
- 3. North 29 degrees 06 minutes 21 seconds West, 86.85 feet to point;
- 4. North 25 degrees 03 minutes 09 seconds West, 295.12 feet to a railroad spike set in said centerline;

Thence leaving said centerline and said Hostetler's east line and going through said Shetler's lands the following 2 courses:

- 1. North 42 degrees 29 minutes 59 seconds East, 89.07 feet to an iron pin set;
- 2. North 49 degrees 09 minutes 34 seconds East, 1042.91 feet to a corner post found at the northeast corner of the southwest quarter of Sec. 11, also being the northwest corner of said Bell & Quinn's lands;

Thence with the mid-section line and the west line of said Bell & Quinn's lands, South 01 degrees 32 minutes 51 seconds West, 1329.67 feet, passing an iron pin set at 639.05 feet to the point of beginning, containing 16.000 acres more or less, subject to all legal highways

and easements of record.

All bearings described herein are based on the Ohio State Plane Grid Coordinates, NAD83, Ohio South per GPS Observation.

All iron pins set are 5/8 inch by 30 inch steel rebar with plastic identification caps marked MCPEEK PS8517.

The above described 16.000 acre parcel is based on a field survey made by McPeek Land ring on October 5^{th} , 2012 $\mathbb{C} F \cap \mathbb{C}$

Surveying on October 5th, 2012

Brian

Parcel No.

Part of: 02-60-11-09-000 (+/- 16.000 ac.)

Fee Paid