

Robert Barr

Situated in the State of Ohio, County of Muskingum, Township of Brush Creek, Township 11, Range 13, part of the Southwest quarter of Section 27, bounded and described as follows:

Being all of Robert Barr Deed Volume 623, page 205, Parcel No. 08-36-01-18-000.

Commencing at the Northwest corner of Lot 63 of Webster's Second Addition to Cannelville recorded in Plat Book 2, page 41; Thence North $11^{\circ}51'34''$ West across Main Street 42.08 feet to a stone found; Thence South $67^{\circ}45'00''$ West along Main Street 103.00 feet to an iron pin found, the place of beginning; Thence along said street South $66^{\circ}55'10''$ West 61.68 feet to a railroad spike found in the center of access road (East Street); Thence along center of access road and Robert Barr Volume 1141, page 342 North $22^{\circ}26'08''$ West 125.00 feet to a railroad spike set passing a railroad spike found at 100.00 feet; Thence North $69^{\circ}30'26''$ East along Sammie Seconds Volume 1007, page 330, 52.60 feet to an iron pin found; Thence South $26^{\circ}41'05''$ East along Kevin Sparks Volume 2018, page 668, 122.86 feet to the place of beginning containing 0.16 Acre(s) more or less.

Bearings are based on the West line of the Southwest quarter of Section 27 bearing North $04^{\circ}20'53''$ East.

Above description is based on a survey by R.L. Daniels, Registered Surveyor No. 5410, May 7, 2008, and is intended for the legal transfer of property described and does not intend to describe all or any easements of record nor encroachments unless otherwise indicated.

Iron pins set are No. 5 reinforcing bars, 30 inches long, with plastic ID caps.

Reference: Volume 623, page 205

OFFICE COPY
NOT RECORDABLE
R L


DESCRIPTION

APPROVED
BY *alhb* 5/29/2008




*Muskingum County, Ohio
Brush Creek Township,
Part of The Southwest Quarter of Section 27,
Township 11, Range 13.*

Bearings are based on the
West Line of the Southwest
Quarter;
Bearing North 42°53' East.
Bearings shown hereon are to
an assumed meridian and are
used to denote angles only.



Line	Bearing	Distance
1	N19°44'02"W	23.33'
2	N14°31'09"W	21.81'
3	N6°27'44"W	21.31'
4	N1°27'26"E	22.15'
5	N29°47'31"E	11.46'
6	N45°34'41"E	11.52'
7	N61°33'57"E	13.02'
8	S26°41'05"E	49.67'

1. Dead references as shown
2. Tax Maps
3. Various surveys found
4. Webster's 2nd addition to Canneshville
P.B. 2, Page 41



By: ALB 5/29/08

R.L. Daniels
R.L. Daniels Reg. Surveyor # 5410

Survey of Part of Sammie Secords Volume 1005, page 330
Parcel No. 08-36-01-14-000.
Survey of All of Robert Barr Volume 623, page 205.
Parcel No. 08-36-01-18-000.

R.L. Daniels & Ass.
61 Old Rainer Rd.
Roseville, Oh. 43777

Date : May 7, 2008

Scale : 1" = 50'

LEGEND

- IRON PIN SET
- IRON PIN FOUND
- STONE
- ▲ RAILROAD SPIKE

reveyor # 5410
 Gamme Second Volume 1007
 01-14-000.
 Robert Barr Volume 623, page 205
 01-18-060.
 01-69-000
 77
 Scale : 1" = 50'