ALAN DONAKER SURVEYING

Alan Donaker, P.S. 19849 TR 383 Walhonding, OH 43843

Fax: (740) 327-1083 Phone: (740) 327-7001



Being 35.073 acres, more or less, 9.778 acres in Section 3 and 25.295 acres in Section 4, in the Second Quarter of Township 3 North, Range 8 West, United States Military Lands, in Township of Cass, in the County of Muskingum, in the State of Ohio, conveyed to Kenneth Moore, Jr., DR 1032-567 (part), Parcel No. 10-04-03-04-000 (part, 9.778 acres) and Parcel No. 10-04-04-23-000 (part, 25.295 acres) and more particularly described as follows:

Commencing at a 1/2" rebar found at the Northwest corner of the South 1/2 of Section 3, said rebar being the TRUE POINT OF BEGINNING:

thence, with the property line of Kenneth W. Moore, Jr., DR 719-37, N. 86° 16' 50" E. a distance of 625.00' to a 5/8" rebar found:

thence, with the property line of Jack J. and Kendra J. Hindel, DR 1137-423, the following 3 courses:

- 1. thence, S. 04° 34′ 56" E. a distance of 30.00' to a \(\frac{5}{8} \)" rebar found;
- 2. thence, S. 04° 34' 56" E. a distance of 67.93' to a %" rebar set;
- 3. thence, S. 04° 34' 56" E. a distance of 597.71' to a point;

thence, with the North line of the Limited Access line of State Road 16 (Musk-16-7.16), the following 7 courses:

- 1. thence, S. 73° 21' 47" W. a distance of 0.38' to a 3/4" pipe found;
- 2. thence, N. 81° 10' 25" W. a distance of 267.22' to a 1/8" rebar set;
- 3. thence, S. 70° 10' 19" W. a distance of 384.71' to a ³/₄" pipe found; 4. thence, S. 77° 55' 32" W. a distance of 235.05' to a ³/₄" pipe found; 5. thence, S. 70° 36' 50" W. a distance of 404.47' to a ³/₄" pipe found;

- 6. thence, S. 69° 16' 43" W. a distance of 350.18' to a 3/4" pipe found;
- 7. thence, N. 86° 25' 25" W. a distance of 285.60' to a 5/8" rebar set;

thence, with the property line of Kenneth W. III and Annette Moore, DR 1136-642, the following 2 courses:

- 1. thence, N. 04° 34' 56" W. a distance of 442.11' to a 1/8" rebar set;
- 2. thence, N. 04° 34' 56" W. a distance of 517.88' to a %" rebar set;

thence, with the property line of Charles H. and Jill Baumgardner Fry, DR 858-340, N. 86° 33' 26" E. a distance of 1249.98' to the TRUE POINT OF BEGINNING, containing 35.073 acres, more or less, and is subject to all easements, rights-of-way, or restrictions, whether recorded or implied.

Bearings are based on DR 1137-423 and are for angular calculations only. All 5/8" rebars set are 30" long with plastic cap marked "AMD 8050". Pertinent Documents: Tax Map and all Deeds and Plats shown, Mus-16-7.16 Surveys by: Earl R. Donaker, W.J. Biedenbach, Malcolm A. Grove, Alan Donaker

Description and plat by Alan Donaker, Professional Surveyor, #8050, from a survey of the premises of May 2 m the year of our Lord Two Thousand Thirteen.

TIPECORDABLE CRITICAL APPEARAGE APPE

ALAN DONAKER SURVEYING

Alan Donaker, P.S. 19849 TR 383 Walhonding, OH 43843

Fax: (740) 327-1083 Phone: (740) 327-7001

60' Non-Exclusive Easement

Granting and Reserving a 60' Non-Exclusive Easement for ingress and egress and regress, 30.00' both sides of the following described centerline said easement is to be maintained in equal shares North of the ½ Section line of Section 3 with the owners of Parcel No. 10-04-03-04-001 and Parcel No. 10-04-03-04-002, their heirs and assigns and by the Grantee, their heirs and assigns, South of the ½ Section line of Section 3;

Being in Sections 3 and 4, in the Second Quarter of Township 3 North, Range 8 West, United States Military Lands, in Township of Cass, in the County of Muskingum, in the State of Ohio, conveyed to Kenneth W. Moore Jr., DR 719-37 and Kenneth Moore, Jr., DR 1032-567 and more particularly described as follows:

Commencing at a 1/2" rebar found at the Northwest corner of the South 1/2 of Section 3;

thence, with the property line of Charles H. and Jill Baumgardner Fry, DR 858-340, the following 2 courses:

- 1. thence, N. 04° 06' 52" W. a distance of 700.04' to a %" rebar set;
- 2. thence, N. 04° 06' 52" W. a distance of 30.00' to a point in the centerline of Cass Irish Ridge Road;

thence, with the centerline of Cass Irish Ridge Road, the following 3 courses:

- 1. thence, S. 53° 58' 49" E. a distance of 201.01' to a point;
- 2. thence, S. 56° 26' 15" E. a distance of 76.42' to a point;
- 3. thence, S. 58° 33' 39" E. a distance of 33.60' to a point, said point being the TRUE POINT OF BEGINNING:

thence, with the centerline of an existing 60' easement, DR 1137-423, and through the property of Kenneth W. Moore Jr., DR 719-37, the following 3 courses:

- 1. thence, S. 04° 39' 50" W. a distance of 43.65' to a point;
- 2. thence, S. 31° 13' 19" E. a distance of 136.23' to a point;
- 3. thence, S. 42° 59' 25" E. a distance of 177.61' to a point;

thence, with the centerline of an existing 60' easement, DR 1137-423, and through the property of Kenneth W. Moore Jr., DR 719-37 and Kenneth Moore, Jr., DR 1032-567, S. 32° 29' 18" E. a distance of 292.52' to a %" rebar set;

thence, through the property of Kenneth Moore, Jr., DR 1032-567, the following 14 courses:

- 1. thence, S. 04° 46' 03" E. a distance of 157.00' to a \(\frac{5}{8} \)" rebar set;
- 2. thence, S. 22° 14' 22" W. a distance of 243.43' to a 5/8" rebar set;
- 3. thence, S. 59° 04' 00" W. a distance of 71.48' to a \(\frac{5}{8} \)" rebar set;
- 4. thence, N. 75° 45' 50" W. a distance of 212.91' to a %" rebar set;
- 5. thence, S. 62° 06' 44" W. a distance of 119.57' to a \(\frac{5}{8} \)" rebar set;
- 6. thence, S. 77° 43' 27" W. a distance of 193.23' to a 5/8" rebar set;
- 7. thence, N. 79° 14' 44" W. a distance of 201.66' to a 5/8" rebar set;

Page 1 of 2

- 8. thence, S. 40° 34' 46" W. a distance of 142.94' to a 5/8" rebar set;
- 9. thence, S. 54° 11' 15" W. a distance of 122.37' to a 5/8" rebar set;
- 10. thence, S. 57° 48' 04" W. a distance of 544.19' to a %" rebar set;
- 11. thence, N. 77° 49' 33" W. a distance of 91.15' to a 1/8" rebar set;
- 12. thence, N. 27° 01' 46" W. a distance of 95.29' to a %" rebar set;
- 13. thence, N. 42° 07' 18" W. a distance of 154.93' to a 5/8" rebar set;
- 14. thence, N. 19° 43' 54" W. a distance of 76.35' to a 5%" rebar set on the property line of Kenneth W. III and Annette Moore, DR 1136-642 and the TRUE POINT OF ENDING.

Bearings are based on DR 1137-423 and are for angular calculations only.

All 5/8" rebars set are 30" long with plastic cap marked "AMD 8050".

Pertinent Documents: Tax Map and all Deeds and Plats shown, Mus-16-7.16

Surveys by: Earl R. Donaker, W.J. Biedenbach, Malcolm A. Grove, Alan Donaker

Description and plat by Alan Donaker, Professional Surveyor, #8050, from a survey of the premises on May 21 in the year of our Lord Two Thousand Thirteen.

NOT RECORDABLE



