13-40-10-24 9747 E. ATHENS PLD 13-40-10-24-001 9750 E ATHENS 20

Conrad Miller

Situated in the State of Ohio, County of Muskingum, Township of Clay, Township 1 Office 14, Section RD 10, bounded and described as follows: Being the dividing of 43.86 acres Parcel No. 12 40 in the State of Ohio, County of Muskingum, Township of Clay, Township 1 Olinge 14, Series ORD ABLE 10, bounded and described as follows: Being the dividing of 43.86 acres Parcel No. 13-40-400 ECO Deed Vol. 1116, Page 187.

Parcel One on East side of County B. 2. 2.

Commencing at the Northeast Corner of the Southeast Quarter of Section 10; Thence South 00°38'12" East 793.21 feet to a stone found the place of beginning; Thence South 00°38'12" East along L. Zgirbar Vol. 1072, Page 170, 858.66 feet to an iron pin found passing iron pins found at 320.63 feet and 775.71 feet: Thence North 89°55'40" West along M&L Toth Vol. 737, Page 52, 473.08 feet to a point in center of County Road 87 passing an iron pin set at 448.08 feet; Thence along the split line of 43.86 acres and center of County Road 87 the next eight courses and distances: North 23°18'29" East 41.34 feet to a point, North 18°47'48" East 34.68 feet to a point, North 10°10'58" East 68.31 feet to a point, North 2°17'09" West 285.93 feet to a point, North 00°29'04" East 201.82 feet to a point, North 10°52'07" West 105.56 feet to a point. North 10°05'37" West 68.81 feet to a point, and North 9°04'37" West 62.80 feet to a point; Thence South 89°53'09" East 475.49 feet along F. Thompson Vol. 1062, Page 235, the place of beginning passing an iron pin set at 20.00 feet containing 8.76 acres more or less:

Parcel Two on the West side of County Road 87

Commencing at the Northeast Corner of the Southeast Quarter of Section 10: Thence South 00°38'12" East 793.21 feet to a stone found; Thence leaving Quarter Section line North 89°53'09" West 475.49 feet to a point in center of County Road 87 the place of beginning; Thence along the center of County Road 87 and split line of 43.86 acres the next eight courses and distances: South 9°04'37" East 62.80 feet to a point, South 10°05'37" East 68.81 feet to a point, South 10°52'07" East 105.56 feet to a point, South 00°29'04" West 201.82 feet to a point, South 02°17'09" East 285.93 feet to a point, South 10°10'58" West 68.31 feet to a point, South 18°47'48" West 34.68 feet to a point and South 23°18'29" West 41.34 feet to a point; Thence leaving County Road 87 North 89°55'40" West along M&L Toth Vol. 737, Page 52, 1645.46 feet to an iron pin passing iron pins at 25.00 feet and 775.00 feet; Thence North 18°19'27" West along M&L Toth Vol. 737, Page 52, 466.72 feet to an iron pin; Thence North 00°00'00" East along Harry McCaughey Vol. 377, Page 389, 417.48 feet to an iron pin; Thence South 89°53'09" East along F. Thompson Vol. 1062, Page 235, 1780.22 feet to the place of beginning passing an iron pin at 1760.22 feet containing 35.10 acres more or less:

Also excepting the following description. This description being part of Old Holmes Limestone Corp. Rail Road Spur Track recorded in Vol. 1100 Page 613.

(See Deed Vol. 280, Page 58, this indicates rail road reverts back to property owners when operation

Commencing at a stone found at the Northwest Corner of the Southeast Quarter of Section 10; Thence South 89°23'39" East 1934.15 feet to a point; Thence South 28°23'53" East 104.18 feet to a point; Thence South 11°48'49" East 746.31 feet to a point the place of beginning; Thence South 88°56'35" East 44.45 feet to a point; Thence South 2°45'19" East 84.72 feet to a point; Thence South 11°48'49" East 227.55 feet to a point; Thence South 8°39'52" East 49.36 feet to a point; Thence North 84°29'05" East 50.00 feet to a point; Thence on a 499.28 foot radius curve to the right chord of which bears South 13°10'08" West 319.89 feet to a point; Thence South 31°51'11" West 237.77 feet to a point; Thence

South 89°47'11" West 70.80 feet to a point; Thence North 31°51'11" East 200.73 feet to a point; Thence North 58°08'49" West 20.00 feet to a point; Thence North 31°51'11" East 74.99 feet to a point; Thence on a 419.28 foot radius curve to the left the chord of which bears North 10°01'11" East 311.87 feet to a point; Thence North 11°48'49" West 321.11 feet to the place of beginning containing 1.20 acres more or less:

Being part of Auditor's Parcel Number 13-40-10-28-000.

Bearings are based on the North line of the Southeast Quarter of Section 10 bearing North 89°23'39" East.

Ref. Deed Vol. 1100, Page 613.

Bearings are based on the West Line of the Southeast Quarter of Section 10 bearing South 40°38'12" East.

Above description is based on the survey by R.L. Daniels, Registered Surveyor No. 5410, June 18, 1998 and is intended for legal transfer of property described and does not intend to describe all or any easements of record nor engapachments collected.

Iron pins set are No. 5 senf. bers stanches long with plastic ID caps.

Reference Co. 1116 Hay 087.

DESCRIPTION APPROVED FOR AUDITOR'S TRANSFER

BY 47513

9-1-95 (1.26 Accepted)



