

25-16-07-15-006

9467 MACEDONIA RD

Description of Parcel 5

Situated in the State of Ohio, County of Muskingum, Township of Hopewell, being in the southeast quarter of Section 7, Range 9 West, Township 1 North, of "The United States Military District", and being bounded and described as follows:

Commencing for reference at the calculated center of Section 7 (Note: Reference bearing on the north line of the southeast quarter of Section 7 used as South 89°24'23" East);

thence, with the west line of said quarter section, South 00°49'28" West a distance of 73.73 feet to a point in the south line of a 10.85 acres tract as conveyed to Shirl E. Cohen by Deed Volume 867, Page 110 of the Muskingum County Recorder's Office;

thence, with the south line of said Cohen property, South 43°12'20" East a distance of 772.28 feet to an iron pin set, being THE TRUE POINT OF BEGINNING for this description;

thence, from said Point of Beginning continuing with the south line of said Cohen property, South 43°12'20" East a distance of 860.00 feet to a point in the centerline of Township Road No. 291, passing through an iron pin found at a distance of plus 838.26 feet.

thence, with the centerline of Township Road No. 291, the following two courses:

- (1) South 22°42'58" West a distance of 51.75 feet to a point;
- (2) thence South 16°03'31" West a distance of 200.00 feet to a point;

thence, leaving the road, North 45°07'37" West a distance of 985.42 feet to an iron pin set, passing through two iron pins set at distances of plus 30.00 feet and plus 130.00 feet, respectively;

thence North 47°08'35" East a distance of 252.20 feet to the Point of Beginning;

containing 5.000 acres, more or less, being a new split out of Parcel No. 25-25-16-07-15-000 in the southeast quarter of Section 7.

Subject to all legal right-of-ways, easements, restrictions, reservations, and zoning regulations of record.

All iron pins set are rebar with yellow caps labeled "Claus 6456".

Page 2 of 2
Description of Parcel 5

The bearings in this description are for angle calculations only and are based on the east line of Section 7 assumed as North 01^{16'59"} East.

The above description prepared by Roger W. Claus, Registered Surveyor No. 6456, based on a new survey of March 12, 1990.

Prior Deed: Deed Volume _____, Page _____

DESCRIPTION APPROVED
FOR AUDITOR'S TRANSFER

BY J L Nambu
3-21-90

OFFICE COPY
NOT RECORDABLE

N

**SURVEY PLAT
FOR
BRUNER LAND CO.**

THOMAS L. RIDENOUR
33 AC ±
DV. 574 PG. 735

QUARTER SEC. LINE

ROBERT E. DAVIS
30.04 AC ±
DV. 786 PG. 37

SITUATED IN THE
STATE OF OHIO, COUNTY
OF MUSKINGUM, TOWNSHIP
OF HOPEWELL, BEING IN THE
SOUTH HALF OF SECTION 7,
R-9 W, T-1 N, OF "THE U.S.
MILITARY DISTRICT".

- = IRON PIN SET CAPPED "CLAUS 6456".
- = IRON PIN FOUND
- ◎ = AXLE FOUND
- △ = IRON PIN FOUND CAPPED "BIEDENBACH
PS-5718 PS 6923".
- R = EXISTING PROPERTY LINES.
- * * * = FENCE EVIDENCE FOUND.
- L = CENTERLINE OF ROADS.
- = LINES OF THIS SURVEY.

SCALE 1"=200'

| LINE | BEARING | DIST. |
|------|-----------------|---------|
| A | S 22° 42' 58" W | 51.75' |
| B | S 16° 03' 31" W | 200.00' |
| C | S 16° 03' 31" W | 100.94' |
| D | S 20° 54' 13" W | 39.56' |
| E | S 26° 50' 12" W | 41.97' |
| F | S 35° 58' 09" W | 35.23' |
| G | S 41° 43' 05" W | 60.17' |
| H | S 45° 25' 58" W | 285.74' |
| I | S 45° 25' 58" W | 73.90' |
| J | S 44° 11' 10" W | 76.37' |
| K | S 36° 17' 19" W | 67.25' |
| L | S 37° 11' 34" W | 130.48' |
| M | S 43° 01' 05" W | 31.28' |
| N | N 39° 13' 08" W | 135.83' |

N.E. CORNER OF
S.E. 1/4 OF
SEC. 7

(2044.77 TOTAL)

QUARTER SEC. LINE

256.00

S89°24'23"E

TR-291

SECTION 7

SECTION 8

SOI-16-59" ~ 1/23.99"

47.34 AC.
DV. 574 PG. 735

339.00'

S89°24'23"E

10.735 AC. OUT OF
25-25-16-07-14-000

⑥
19.001 AC.

CENTER OF
SEC. 7

JOHN R. SMITH
26.53 AC.
DV. 563 PG. 551

SHIRL
E.
COHEN

10.85 AC. ±
DV. 867
PG. 110

8.266
AC.
OUT OF
25-25-16-07-15-000

N 47°08'35"E
252.20'

543°12'20"E

160.5'
TO TR-PL

5.000 AC.

OUT OF
25-25-16-07-15-000

547°03'09"E
304.94'

7.874 AC.
OUT OF
25-25-16-07-15-000

545°07'37"E
107.70'

5.000 AC.

OUT OF
25-25-16-07-15-000

545°07'37"E
107.70'

1.950 AC.
OUT OF
25-25-16-07-15-000

545°07'37"E
107.70'

1.950 AC.
OUT OF
25-25-16-07-15-000

545°07'37"E
107.70'

6.129 AC.
OUT OF
25-25-16-07-15-000

545°07'37"E
107.70'

12.039 AC.

OUT OF
25-25-16-07-15-000

545°07'37"E
107.70'

8.079 AC.

OUT OF
25-25-16-07-15-000

545°07'37"E
107.70'

5.011 AC.

OUT OF
25-25-16-07-15-000

545°07'37"E
107.7