Linn Engineering, Inc.

Civil Engineering Consultants 740-452-7434 • 1-800-991-7434 • FAX 740-452-5198 534 Market Street • P.O. Box 2086 • Zanesville, Ohio 43702-2086

TRACT FIVE

Situated in the State of Ohio, County of Muskingum, Township of Jackson and bounded and described as follows:

Being a part of the east half of Lot 12, Quarter Township One, Jackson Township, Township 3 North, Range 9 West, United States Military Lands, also being a part of the lands now owned by The Longaberger Company as recorded in Muskingum County Deed Record 1508-773, and more particularly described as follows:

Beginning for reference at an existing stone on the northwest corner of Lot 11, Quarter Township One, Jackson Township, Township 3 North, Range 9 West, United States Military Lands; thence along the west line of Lot 11, Quarter Township One and the east line of lands now owned by Elaine Slaughter (DR 1160-421) South 02 degrees 43 minutes 00 seconds West 825.00 feet to an iron pin found on said Slaughter's southeast corner and the principal place of beginning; thence through lands currently owned by the Longaberger Company (DR 1508-773) South 02 degrees 43 minutes 00 seconds West 957.93 feet to an iron pin found on the east line of lands now owned by Paul and Geraldine Moran (DR 571-846), passing an iron pin set at 572.49 feet; thence along said Morans' east line the following three courses:

- 1) North 88 degrees 09 minutes 34 seconds West 511.50 feet to an iron pin found;
- 2) North 03 degrees 28 minutes 17 seconds West 385.44 feet to an iron pin found;
- 3) North 01 degrees 20 minutes 10 seconds West 580.08 feet to an iron pin found on said Slaughter's south line;

thence along said Slaughter's south line South 87 degrees 39 minutes 45 seconds East 594.00 feet to the east line of Lot 12, Quarter Township One and the principal place of beginning;

containing 12.28 acres more or less, subject to all legal road right of ways and all applicable easements.

Iron pins set are 5/8 inch diameter by 30 inch long rebar with plastic identification caps.

Bearings are based on the North American Datum 1983 (NAD83) State Plane Grid Coordinate System, Ohio South Zone, as per GPS observations.

This description is written based on a survey completed December 2, 2004 by Timothy H. Linn, Reg. No. 7113.



PARCEL NO .: Part of .: 29-29-20-71-30-000 (12.28 ac.)

