BOWMAN SURVEYING Zanesville, Ohio 43701 PH. (740) 819-1087

SURVEY DESCRIPTION FOR Raymond Frew, Jr.

PART OF AUDITORS PARCEL 29-62-04-01-000 (0.64 Acres)

Situated in the Southeast Quarter of Section 19, T-3-N, R-9-W, U.S.M.L., Village of Frazeysburg, Muskingum County, Ohio. Being part of the lands of the Raymond H. Frew, Jr. and Brenda K. Frew Revocable Living Trust recorded in Deed Book 1902 page 93 of the Muskingum County Deed records and being described as follows:

Beginning at a point located at the intersection of the South line of the Village of Frazeysburg with the west line of the Southeast quarter of section 19, said point referenced by a found concrete post located S.89°40'08"W. a distance of 1.44 feet; Thence, N.00°09'46"W. a distance of 1,250.99 feet along the West line of said Quarter section line to a found iron pin on the South line of a rail road owned by Caprail; Thence, N.65°02'48"E. a distance of 121.15 feet along the South line of said rail road to a set rebar; Thence, S.89°58'03"E. a distance of 667.23 feet along the South line of the lands, now or formerly, owned by R. & R. Priest (818/302) to a found iron pin; Thence, S.00°24 00"W. a distance of 127.00 feet along the West line of the lands, now or formerly, owned by A. Grove, Et Al, (1945/045) to a found iron pin, BEING THE POINT OF BEGINNING;

- Thence, S.86°37'50"E. a distance of 223.30 feet along the South line of said Grove lands to a found iron pin on the West line of Clay Street;
- Thence, S.00°24'00"W. a distance of 120.84 feet along the west line of clay street to a set rebar;
- Thence, N.88°55'49"W. a distance of 223.01 feet through the lands of Raymond H. Frew, Jr and Brenda K. Frew Revocable living Trust (1902/093) to a set rebar on the East line of lands, now or formerly, owned by Jackson Township (1976/518);
- Thence, N.00°24'00"E. a distance of 129.80 feet along said Township lands to the point of beginning.

The above described parcel contains 0.64 acres, more or less, and is subject to all legal easements and right of ways. All set rebars are 5/8" x 30" rebars with plastic I.D. caps. North is based upon an assumed meridian.

Description was prepared from an accuracy Surveying, Stephen M. Bowman, P.S. #7135. June 25, 200 OFFICE COPY Description was prepared from an actual field survey by Bowman

APPROXED FOR CLOSURE

PLANNING COMMISSION NOT RECORDABLE

