

29-70-25-34

* the chord bearing North $44^{\circ} 41' 44''$ West,
147.50 feet, ADAMSS N/A

Situated in The State of Ohio, County of
Muskingum, Township of Jackson, Township
3-N, Range 9-W, Quarter Township 3, Section
25 and being further described as follows;
beginning at a point at an existing iron pin at
the southeast corner of the northeast quarter
of Section 25;

thence, South $59^{\circ} 29' 15''$ West, 324.65 feet along
a northwesterly line of The Longaberger Co
(Deed Book 1147, Page 825) to a point on the
centerline of State Route 586, passing an
existing iron pin at 293.65 feet,

thence, along the centerline of State Route 586
along a curve to the right 147.50 feet - radius
5729.58 feet to a point at the southwest

* $\rightarrow$ corner of K. Ramsey (Deed Book 1135, Page 882,
the chord bearing North $44^{\circ} 41' 44''$ West, 147.50 feet,
thence, North $51^{\circ} 56' 56''$ E, 274.89 feet along a
southeasterly line of the said K. Ramsey to
a point at an iron, passing an iron pin at
29.49 feet,

thence, North $38^{\circ} 08' 17''$ West, 50.08 feet along
a northeasterly line of the said K. Ramsey
to a point at an iron pin,

thence, North $38^{\circ} 02' 41''$ West, 99.93 feet along
a northeasterly line of the said K. Ramsc
to a point at an iron pin,

thence, South $51^{\circ} 59' 06''$ West, 288.46 feet along a
northwesterly line of the said K. Ramsey to
point on the centerline of State Route 586,
passing an iron pin at 258.39 feet,

thence, along the centerline of State Route 586
 with a curve to the right 177.99 feet -
 radius 5729.58 feet - to a point of tangency
 the chord bearing North $41^{\circ}42'06''$ West,
 177.99 feet,
 thence, North $40^{\circ}43'18''$ West, 287.11 feet along the
 centerline of State Route 586 to a point
 at a railroad spike on the centerline of
 an open ditch,
 thence, North $52^{\circ}16'37''$ East, 983.97 feet along
 the open ditch to a point on the east
 line of the said Section 25, the open
 ditch is also the south line of the
 State of Ohio (Deed Book 1144, Page 739)
 thence, South $00^{\circ}48'35''$ East, 1002.51 feet along
 the east line of the said Section 25
 to the point of beginning, passing an
 iron pin at 10.00 feet.


DESCRIPTION APPROVED
 FOR AUDITOR'S TRANSFER

BY

Containing 10.966 Acres


7-8-98

All of parcels 29-29-70-25-34
 29-29-70-25-36
 29-29-70-25-37



SURVEY AND DESCRIPTION BY
 William H. Derwacter
 William H. Derwacter
 Registered Professional Surveyor #5437
 July 8, 1998

OFFICE COPY
 NOT RECORDABLE



Iron Pins

SITUATED IN
State of Ohio
County of Muskingum
Township of Jackson
Twp 3-N, Range 9-W
Section 25

Prior Deed
756-228

State of Ohio
114A-739

N 52° 16' 37" E
983.97'

10.966 Ac.

ALL 29-29-70-25-36
ALL 29-29-70-25-37
ALL 29-29-70-25-37

DESCRIPTION APPROVED
FOR AUDITOR'S TRANSFER
BY W.S.V.
7-8-98

Railroad Spike
Sta 177+83.81

East Line Section 25
1002.51'
S 00° 48' 35" E

N 40° 49' 18" W
287.11'

PT Sta.
174+96.7

Chord 177.99'
N 41° 42' 06" W
177.99'
Radius 5729.58'

258.39'
S 51° 59' 06" W
288.46'

K. Ramsey
1135-882

N 38° 02' 41" W
99.93'

N 38° 01' 17" W
50.08'

S.E. Cor.
N.E. Qtr.
Sec. 25

Qtr. Section Line

PT Sta.
171+74.7

274.89'
N 51° 56' 56" E
274.89'

324.65'
N 27° 09' 21" W

Longaberger Co.
1147-825

Pass 293.65'

PC Sta.
168+52.7



OFFICE COPY
NOT RECORDABLE
Survey and Plat by
William H. Derwacter
Registered Surveyor No. 5437
July 8, 1998