



450 S. Fourth St. Coshocton, Ohio,43812 Phone 740-622-2783 Fax 740-622-2786 e-mail aps@sota-oh.com

February 19, 2004

Description for William Klein in Monroe Township, Muskingum County, Ohio.

Being a tract of land in the Northwest Quarter of Section 15, Range 5W, Township 3N, Monroe Township, Muskingum County, State of Ohio, and being further described as follows;

Note: North based on a survey by G.W. Johnson, R.S. 5252, August, 1985. All pins indicated as set are 5/8" x 30" rebars with plastic caps.

Research Data: Deeds, surveys and plats as shown on plat.

Beginning at a 5/8" rebar with plastic cap recovered at the Southwest corner of the said Northwest Quarter and on the East line of Section 11, Adams Township;

thence, with the West line of the said Northwest Quarter the following two (2) courses;

- 1. North 1 degree 13' 36" East, a distance of nine hundred three and ninety-eight hundreths (903.98) feet to a set steel pin;
- 2. continuing North 1 degree 13' 36" East, a distance of twenty-nine and eighty hundredths (29.80) feet to a point on the centerline of Township Road 100 (Brush Run Road);

thence, with the said centerline of Township Road 100 the following twelve (12) courses;

- 1. South 73 degrees 48' 12" East, a distance of forty-six and sixty-four hundredths (46.64) feet to a point;
- 2. South 82 degrees 54' 10" East, a distance of ninety-five and eighty-eight hundredths (95.88) feet to a point;
- 3. South 83 degrees 23' 13" East, a distance of one hundred eighty-two and forty-four hundredths (182.44) feet to a point;
  - 4. South 89 degrees 36' 50" East, a distance of eighty-four and seventysix hundredths (84.76) feet to a point;
  - 5. North 84 degrees 45' 44" East, a distance of eighty-one and sixty-two hundredths (81.62) feet to a point;
  - 6. North 81 degrees 20' 35" East, a distance of eighty-eight and forty-one hundredths (88.41) sect to a point;
  - 7. North 71 degrees 42' 35" East, a distance of eighty-two and ten hundredths (82.10) feet to a point;
- 8. North 63 degrees 21' 09" East, a distance of one hundred lifty-five and thirty-one hundredths (155.31) feet to a point;
- 9. North 60 degrees 22' 19" East, a distance of one hundred thirty-eight and five hundredths (138.05) feet to a point;
- 10. North 58 degrees 52' 10" East, a distance of one hundred twenty-nine and sixteen hundredths (129.16) feet to a point;
  - 11. North 71 degrees 06' 40" East, a distance of fifty-seven and twenty-one hundredths (57.21) feet to a point;
- 12. North 80 degrees 24' 19" East, a distance of one hundred seventy-nine and sixteen hundredths (179.16) feet to a point at the Northwest corner of the lands of C. Lucas (D.R. 991, Pg. 63);

thence, with the West line of the said lands of C. Lucas the following two (2) courses;

- 1. South 1 degree 32'01" West, a distance of thirty-two and ninety-eight hundredths (32.98) feet to a set steel pin;
- 2. continuing South 1 degree 32' 01" West, a distance of one thousand one hundred ninety-five and eight hundredths (1195.08) feet to a 5/8" rebar with plastic cap recovered on the South line of the said Northwest Quarter and on the North line of the lands of R.M. Bontrager et al (D.R. 605, Pg. 149);

thence, with the said South line of the Northwest Quarter, North 88 degrees 06' 37" West, a distance of one thousand two hundred forty and fifty hundredths (1240.50) feet to the point of beginning;

The above described tract contains twenty-eight and eight hundred twenty-three thousandths (28.823) acres, more or less, as surveyed by Bruce D. Eckelberry, Registered Professional Surveyor No. 7103, February 19, 2004.

This description is intended to convey part of Parcel One of the lands previously transferred from Gail W. Klein to William B. & Mary Ruth Klein (D.R. 617, Pg. 133) and from Mary Ruth Klein to William B. Klein (D.R. 1095, Pg. 540) (Parcel No. 42-42-40-15-05).

OFFICE COPY NOT RECORDABLE DESCRIPTION APPROVED FOR AUDITOR'S TRANSFER

2-24-104

42.40-15-05-001 9000 BEWSHIZUN ED Boundary Survey far O = Recovered 3/4" pipes William Klein = Set 5/8" x 30" rebars with plastic caps Northwest Quarter = Recovered 5/8° rebars with plastic caps Section 15 Range 5W, Township 3N Monroe Township North based on a survey by G.W. Johnson, R.S. 5252, Muskingum County August 1985. Ohio Scale: 1" = 200' February 19, 2004 Research Data 400 Deeds, surveys and plats as shown. Sec. Line te of BRUCE OFFICE COPY ECKETHERMA Registered Professional Surveyor No. STONAL S N 71°06'40" E 57,21 William B. Klein N 80°24'19° E D.R. 617, Pg. 133 & D.R. 1095, Pg. 540 N 58°52'10" E Parcel One 129.16 S 191336" W S 1°32'01\* W C/L T.R. 100 S 73°48'12" E 32.98 Brush Run Rd. 46.64 N 60°22'19" E S 82°54'10" E N 81°20'35" E 138.05 95.88 88.41 N 63°21'09" E Sec. 11, Adams Twp. \$ 83°23'(3° E 182,44 155.31 N 1°13'36" E N 71°42'35" E \$ 89°36'50" E 82,10 84,76 N 84°45'44" E Part of 81.62 William B. Klein D.R. 617, Pg. 133 & D.R. 1095, Pg. 540 Parcel Onc 28.823 acres DESCRIPTION APPROVED M. McCon D.R. 754, Pg. 83 FOR AUDITOR'S TRANSFER Part of Parcet No. 42-42-40-15-05 2-24-2004 SW Cor. NW Qtr. Sec. 15 N 88°06'37" W Qtr. Twp. Line 1240.50 Lot 40 Prepared by R.M. Bontrayer et al AMERICAN PRECISION SURVEYING D.R. 605, Pg. 149 3rd Qtr. 450 South 4th St. (740) 622-2783 COSHOCTON, OHIO 43812