



www.mcpeeklandsurveying.com  
email: brian@mcpeeklandsurveying.com  
340 Robin Hood Ln., \* Zanesville, Oh 43701 \* 740.704.6073

**Donald F. Hampp & Garnet L. Hampp as Trustees of the Donald F. Hampp and Garnet L. Hampp Revocable Trust Dated August 18, 2001**

**OR 1604-419**

**+/-39.211 Ac.**

**All of: 47-04-01-22-000**

Situated in the State of Ohio, County of Muskingum, Township of Newton, Southeast Quarter of Section 1, T17, R15. Being all of the land now owned by Donald F. Hampp & Garnet L. Hampp as Trustees of the Donald F. Hampp and Garnet L. Hampp Revocable Trust Dated August 18, 2001 as recorded in OR 1604-419 of the Muskingum County Recorders office and more particularly described as follows.

Beginning at the northeast corner of the said southeast quarter, thence with the east line of said southeast quarter, S 03°08'54" W a distance of 258.88 feet to a point in the center of Slack Road (T-90), passing an iron pin found (roof bolt) at 232.88 feet;

thence with the center of said Slack Road the following eleven (11) courses:

1. S 67°11'17" W a distance of 73.47 feet to a point;
2. S 70°03'23" W a distance of 138.82 feet to a point;
3. with a curve turning to the right an arc length of 235.43 feet, a radius of 847.91 feet, with a chord bearing of S 82°30'16" W and a chord length of 234.67 feet, to a point, referenced by an iron pin set that bears N 66°37'26" E a distance of 52.56 feet;
4. with a reverse curve turning to the left an arc length of 164.37 feet, a radius of 972.50 feet, with a chord bearing of S 82°39'12" W and a chord length of 164.18 feet, to a point;
5. with a reverse curve turning to the right an arc length of 337.87 feet, a radius of 1770.45 feet, with a chord bearing of S 80°25'46" W and a chord length of 337.36 feet, to a point;
6. N 88°46'39" W a distance of 242.47 feet to a point;
7. N 86°31'51" W a distance of 101.04 feet to a point;
8. with a curve turning to the left an arc length of 232.38 feet, a radius of 403.55 feet, with a chord bearing of S 74°06'19" W and a chord length of 229.18 feet, to a point;
9. S 57°36'31" W a distance of 121.99 feet to a point;
10. with a curve turning to the left an arc length of 124.85 feet, a radius of 321.46 feet, with a chord bearing of S 49°06'10" W and a chord length of 124.07 feet, to a point;
11. with a reverse curve turning to the right an arc length of 128.72 feet, a radius of 182.83 feet, with a chord bearing of S 50°04'30" W and a chord length of 126.08 feet to a point at the northwest corner of the lands now owned by James V. White (OR 3094-97);

thence with the west line of said White's lands, S 20°49'15" E a distance of 107.77 feet to a point in the center of Kent Run;

thence with the center of said Kent Run the following seven (7) courses:

1. N 82°42'01" W a distance of 283.09 feet to a point;
2. S 80°50'48" W a distance of 149.27 feet to a point;
3. S 67°46'31" W a distance of 145.03 feet to a point;
4. S 44°18'15" W a distance of 130.14 feet to a point;
5. S 76°50'03" W a distance of 65.42 feet to a point;
6. N 64°11'44" W a distance of 37.65 feet to a point;
7. N 41°17'59" W a distance of 219.02 feet to a point on the west line of said southeast quarter, referenced by an iron pin set that bears, N 89°05'20" E a distance of 117.20 feet;

thence with the west line of said southeast quarter, N 02°02'39" E a distance of 959.49 feet to an iron pin found (newcome) at the northwest corner of said southeast quarter;

thence with the north line of said southeast quarter, S 86°20'41" E a distance of 2626.06 feet to the principal place of beginning, passing an iron pin found (newcome) at 55.66 feet and an iron pin found (newcome) at 370.39 feet, containing 39.211 acres more or less, subject to all legal highways and easements of record.

All bearings described herein are based on the Ohio State Plane Grid Coordinates, NAD83, Ohio South per GPS Observation.

All iron pins set are 5/8 inch by 30 inch steel rebar with plastic identification caps marked MCPEEK PS8517.