



www.mcpeeklandsurveying.com LLC  
email: brian@mcpeeklandsurveying.com  
340 Robin Hood Ln., \* Zanesville, Oh 43701 \* 740.704.6073

**Donald F. Hampp & Garnet L. Hampp as Trustees of the Donald F. Hampp and Garnet L. Hampp Revocable Trust Dated August 18, 2001**

**OR 1604-413**

**+/-38.614 Ac.**

**Part of: 47-06-02-02-000**

Situated in the State of Ohio, County of Muskingum, Township of Newton, Southwest Quarter of Section 6, T15, R14. Being part of the land now owned by Donald F. Hampp & Garnet L. Hampp as Trustees of the Donald F. Hampp and Garnet L. Hampp Revocable Trust Dated August 18, 2001 as recorded in OR 1604-413 of the Muskingum County Recorder's office and more particularly described as follows.

Beginning for reference at an iron pin found (roof bolt) at the northeast corner of said southwest quarter, thence with the east line of said southwest quarter, S 03°41'28" W a distance of 481.39 feet to an iron pin set, the principal place of beginning;

thence continuing with said east line, S 03°41'28" W a distance of 2199.61 feet to an iron pin set at the southeast corner of said southwest quarter, passing an iron pin found (5/8") at 212.78 feet, an iron pin found (5/8") at 395.00 feet, an iron pin found (5/8") at 519.07 feet, a stone found at 879.62 feet, an iron pin found (biedenbach) at 1199.90 feet and an iron pin found (5/8") at 1827.13 feet;

thence with the south line of said southwest quarter, N 87°08'37" W a distance of 1086.37 feet to a point in the center of Wesley Chapel Road (CR-126), passing an iron pin found (harkness) at 1052.89 feet;

thence with the center of said Wesley Chapel Road the following three (3) courses:

1. N 03°51'49" E a distance of 2.73 feet to a point;
2. with a curve turning to the right an arc length of 231.63 feet, a radius of 1445.31 feet, with a chord bearing of N 10°01'46" E and a chord length of 231.38 feet to a point;
3. with a compound curve turning to the right an arc length of 181.45 feet, a radius of 719.24 feet, with a chord bearing of N 18°55'31" E and a chord length of 180.97 feet to a point at the southwest corner of the lands now owned by Annette B. Cornish (OR 2523-1);

thence with the perimeter of said Cornish's lands the following three (3) courses:

1. S 87°00'10" E a distance of 470.66 feet to an iron pin found (5/8"), passing an iron pin found (roof bolt) at 34.75 feet;
2. N 02°59'23" E a distance of 300.00 feet to an iron pin set, passing an iron pin set (5/8") at 199.38 feet;
3. N 87°00'10" W a distance of 329.29 feet to a point in the center of said Wesley Chapel Road, passing an iron pin found (5/8") at 304.79 feet;

thence with the center of said Wesley Chapel Road the following five (5) courses:

1. N 27°57'49" E a distance of 21.87 feet to a point;
2. with a curve turning to the right an arc length of 348.34 feet, a radius of 1326.15 feet, with a chord bearing of N 31°46'02" E and a chord length of 347.34 feet to a point;
3. with a reverse curve turning to the left an arc length of 293.88 feet, a radius of 245.86 feet, with a chord bearing of N 05°58'47" E and a chord length of 276.69 feet to a point;
4. N 21°06'34" W a distance of 307.34 feet to a point;
5. with a curve turning to the right an arc length of 253.83 feet, a radius of 1318.41 feet, with a chord bearing of N 15°35'39" W and a chord length of 253.43 feet to a point;

thence leaving said road and going through said Hampp Revocable Trust's lands the following three (3) courses:

1. N 83°08'11" E a distance of 238.77 feet to an iron pin set, passing an iron pin set at 24.31 feet;
2. N 01°00'05" E a distance of 223.91 feet to an iron pin found (roof bolt) at the southeast corner of the lands now owned by Ronald E. Spring & Teresa L. Hampp (DR 997-188);
3. N 83°51'22" E a distance of 690.50 to the principal place of beginning, containing 38.614 acres more or less, subject to all legal highways and easements of record.

All bearings described herein are based on the Ohio State Plane Grid Coordinates, NAD83, Ohio South per GPS Observation.

All iron pins set are 5/8 inch by 30 inch steel rebar with plastic identification caps marked MCPEEK PS8517.