

47-56-62-00

p/A

Edna Wilkens
10/10/86

Situated in the State of Ohio, County of Muskingum,
Township of Newton, T 15, R 14, Southwest Quarter
of Section 19, bounded and described as follows:

Commencing at the Northeast corner of the Southwest
Quarter of Section 19; thence on section line North
84° 40' West 1976.78 feet; thence leaving section
line South 5° 20' West 127.83 feet to an axel on the
Southwest corner of Donald Fisher property; thence
South 24° 34' 52" East 453.70 feet to an axel on the
Northwest corner of Donald Jones property; thence
North 23° 35' 10" West 155.03 feet to an iron pin
found on the Northwest corner of Arthur Hayes property,
the place of beginning; thence North 23° 35' 10"
West 100.00 feet to an iron pin found at the Southwest
corner of Lot No. One (1) of Krofft's Addition to
East Fultonham recorded in Plat Book 4, Page 27;
thence North 75° 14' 50" West 132.00 feet to West
side of Hoover Avenue Extended passing an iron pin
at 131.50 feet; thence along said road South 23°
36' 23" West 99.81 feet to an iron pin found; thence
leaving said road South 75° 09' 50" West 132.00 feet
to the place of beginning, containing 0.30 acres
more or less.

East

East

Bearings are based on the North line of the Southwest
Quarter of Section 19 bearing North 84° 40' West.

Being all of Auditor's Parcel No. 47-47-56-02-20-000.

Survey & Description By:

**OFFICE COPY
NOT RECORDABLE**

R. L. Daniels
Registered Surveyor No. 5410

DESCRIPTION APPROVED
for Auditor's transfer
By *R. L. Daniels*
10-20-86

47-56-02-00
19-15-14
Columbia Portland Cement
5/13/85

Tract Seven

Situated in the State of Ohio, County of Muskingum,
Township of T 15, R 14, Southeast and South-
west Quarters of Section 19, bounded and described
as follows:

Commencing at the Northeast corner of the Southwest
Quarter of Section 19; thence South $50^{\circ} 50' 52''$ West
935.75 feet; thence South $62^{\circ} 14' 35''$ East 230.58
feet to the place of beginning; thence South $21^{\circ} 58'$
 $46''$ West 176.87 feet; thence North $79^{\circ} 12' 25''$ West
544.37 feet to an iron pin on O. R. T. A. Railroad
right-of-way; thence on a 831.47 foot radius curve
to the right 630.30 feet the cord of which bears
North $57^{\circ} 29' 25''$ West 615.32 feet to an iron pin;
thence North $25^{\circ} 23'$ West 140.49 feet to the center
of Jonathan Creek passing an iron pin at 52.49 feet;
thence along Jonathan Creek the following two courses
and distances, South $80^{\circ} 18' 34''$ East 643.44 feet and
South $62^{\circ} 14' 35''$ East 616.76 feet to the place of
beginning, containing 7.01 acres more or less. 5.44
acres in the Southwest Quarter of Section 19 and 1.57
acres in the Southeast Quarter of Section 19.

Bearings are based on the East line of the Southwest
Quarter of Section 19 bearing South $50^{\circ} 50'$ West.

Being Auditors Parcel No. 47-04897.

Survey & Description By:

**OFFICE COPY
NOT RECORDABLE**
R. L. Daniels
Registered Surveyor 5410

47-47-56-02-00-802