SNR

Lawrence and Debera S. Spring

Situated in the State of Ohio, County of Muskingum, Township of Newton, Township 15, Range 14, Section 26, bounded and described as follows:

Being part of Lawrence E. Spring and Debera S. Spring Volume 1128, page 634, Parcel No. 48-47-94-26-14-000.

Commencing at an axle found at the Southwest Corner of the Southwest Quarter of Section 26; Thence North 51°37'13" East 506.00 feet to a point (in Ransbottom Road); Thence South 89°41'03" East 428.85 feet to an iron pin set the place of beginning passing iron pins found at 30.00 feet and 203.39 feet; Thence along the split lines of Lawrence and Debera Spring the next 8 courses and distances: North 24°26'54" East 355.07 feet to a point in center of access road passing an iron pin set at 323.86 feet, along center of access road the next 5 courses and distances: South 74°41'03" East 108.55 feet to a point, South 84°18'10" East 201.43 feet to a point, South 88°42'18" East 54.83 feet to a point, North 85°07'20" East 118.33 feet to a point, and North 69°51'29" East 176.08 feet to a point; Thence South 12°17'33" East 356.99 feet to an iron pin set passing an iron pin set at 28.43 feet; Thence North 89°41'02" West along George Spring Volume 1128, page 333, 866.12 feet to the place of beginning containing 5.23 Acres more or less:

Also the right to use the existing 50-foot wide access road for Aggress and Egress to Ransbottom Road the centerline described as follows:

Beginning at the Northeast Corner of the 5.23 Acre Description; Thence along the North line of said parcel in the center line of access road the next 5 courses and distances: South 69°51'29 West 176.08 feet to a point, South 85°07'20" West 118.33 feet to a point, North 88°42'18" West 54.83 feet to a point, North 84°18'10" West 201.43 feet to a point, North 74°41'03" West 108.55 feet to a point; Thence continuing along the center of said access road the next 9 courses and distances: North 74°41'03" West 43.98 feet to a point, North 66°27'45" West 98.27 feet to a point, North 58°01'07" West 40.23 feet to a point, North 49°23'49" West 80.55 feet to a point, North 46°28'44" West 52.63 feet to a point, North 55°42'37" West 33.68 feet to a point, North 65°26'53" West 43.61 feet to a point, North 78°10'11" West 39.95 feet to a point, and North 87°53'07" West 76.41 feet to a point in center of Ransbottom Road:


Bearings are based on the West line of the Northwest Quarter of Section 26 bearing 00°21'15" East:

Above description is based on a survey by R.L. Daniels, Registered Surveyor No. 5410, March 18, 2008, and is intended for the legal transfer of property described and does not intend to describe all or any easements of record nor encroachments unless otherwise indicated.

Iron pins set are No. 5 reinforcing bars 30 inches long with plastic ID caps.

OFFICE COPY28, page 834
NOT RECORDABLE

5ALL 4)29/08



oKAU 9/14/08