Lawrence and Debera S. Spring

Situated in the State of Ohio, County of Muskingum, Township of Newton, Township 15, Range 14, Section 26, bounded and described as follows:

Being part of Lawrence E. Spring and Debera S. Spring Volume 1128, page 834, Parcel No. 46-47-94-26-14-000.

Commencing at an iron pin found at the Southwest corner of the Southwest quarter of Section 26; Thence North 00°21'15" East 324.62 feet to an iron pin found; Thence North 59°40'16" East 496.90 feet to a point in the center of Ransbottom Road, the place of beginning; Thence along the center of Ransbottom Road and the split lines of Volume 1128, page 834, the next six courses and distances – North 20°59'53" East 53.31 feet to a point; North 26°52'23" East 73.66 feet to a point, North 21°05'05" East 57.18 feet to a point, North 14°18'49" East 56.58 feet to a point, North 07°14'29"East 45.15 feet to a point, North 05°54'36" East 26.48 feet to a point, and North 05°42'02" East 167.78 feet to a point; Thence leaving Ransbottom Road and along Ronald Spring Volume 1129, page 235, the next two courses and distances – South 50°09'10" East 195.00 feet to an iron pin found passing an iron pin set at 25.00 feet and South 43°40'17" East 133.16 feet to an iron pin found; Thence leaving Ronald Spring and along the split line of Lawrence Spring, the next two courses and distances – South 02°38'36" West 209.72 feet to an iron pin found and South 84°51'26" West 345.42 feet to the place of beginning containing 2.23 Acres more or less.

Excepting from above, a 50.00 foot wide right of way described as follows:

Commencing at the Northwest corner of above 2.23 Acres; Thence South 05°42'02" West 167.7 feet to a point; Thence South 05°54'36" West 26.48 feet to a point in the center of Ransbottom Road, the beginning of said 50 foot right of way; Thence on the next six courses and distances – South 87°53'07" East 76.41 feet to a point, South 78°10'11" East 39.95 feet to a point, South 65°26'53" East 43.61 feet to a point, South 55°42'37" East 33.68 feet to a point, South 46°28'44" East 52.63 feet to a point, and South 49°23'49" East 47.35 feet to the East line of above description.

Bearings are based on the West line of the Northwest Quarter of Section 26 bearing 00°21'15" East:

Above description is based on a survey by R.L. Daniels, Registered Surveyor No. 5410, May 22, 2008, and is intended for the legal transfer of property described and does not intend to describe all or any easements of record nor encroachments unless otherwise indicated.

PECONDA DELECTOR

Description

Iron pins set are No. 5 reinforcing bars 30 inches long with plastic ID caps.

APPROVED

MINOR LOT SPLIT ONLY

MUSKINGUM COUNTY

Dete

Pee Paid

Fee Paid

