

4. **N 48 degrees 09'04" W a distance of 334.45 feet** along the centerline of said easement to a point;
5. **N 44 degrees 53'49" W a distance of 167.74 feet** along the centerline of said easement to a point;
6. **N 32 degrees 49'28" W a distance of 139.53 feet** along the centerline of said easement to a point;
7. **N 27 degrees 22'49" W a distance of 395.38 feet** along the centerline of said easement to a point;
8. **N 53 degrees 29'07" W a distance of 199.24 feet** along the centerline of said easement to a point;
9. **N 62 degrees 37'57" W a distance of 144.11 feet** along the centerline of said easement to a point;
10. **N 73 degrees 04'26" W a distance of 137.66 feet** along the centerline of said easement to a point;
11. **N 62 degrees 44'55" W a distance of 46.28 feet** along the centerline of said easement to a point THERE ENDS.

Bearings from – Grid North, Ohio State Plane Coordinate System, South Zone, NAD 83.

All iron pins set are 5/8 inch rebars with plastic identification cap marked "Galbraith 8703".

This survey was made and description prepared by Caleb Jerome Galbraith P.S. 8703. on Jan. 2, 2024.

**OFFICE COPY
NOT RECORDABLE**

DESCRIPTION

APPROVED

By: *CJG 1/18/24*

