

DESCRIPTION FOR CONVEYANCE  
GILMORE C. AND AUNDAH F. MOOREHEAD  
PARCEL NUMBER 66-66-50-14-36-000 (PART)  
PARCEL NUMBER 66-66-80-17-05-000 (PART)

PS

BEING A PART OF THE SOUTHEAST QUARTER OF SECTION 14 AND A PART OF THE NORTHEAST QUARTER OF SECTION 17, TOWNSHIP 1, RANGE 5, OF THE UNITED STATES MILITARY LANDS, UNION TOWNSHIP, MUSKINGUM COUNTY, OHIO AND BEING FURTHER DESCRIBED AS FOLLOWS:

BEGINNING AT AN EXISTING IRON PIN (5/8 INCH REBAR) AT THE SOUTHWEST CORNER OF THE SOUTHEAST QUARTER OF SECTION 14; THENCE NORTH 04 DEGREES 06 MINUTES 35 SECONDS EAST 430.00 FEET TO AN IRON PIN SET, SAID POINT BEING SOUTH 04 DEGREES 06 MINUTES 35 SECONDS WEST 1800.58 FEET FROM AN EXISTING IRON PIN (1/2 INCH ID PIPE) AT THE SOUTHWEST CORNER OF A 3.009 MORE OR LESS ACRE TRACT CONVEYED TO GARY A. AND VONDA K. MOOREHEAD BY DEED RECORDED IN VOLUME 947, PAGE 247 OF THE MUSKINGUM COUNTY DEED RECORDS; THENCE NORTH 78 DEGREES 13 MINUTES 46 SECONDS EAST 519.26 FEET TO AN IRON PIN SET; THENCE SOUTH 04 DEGREES 06 MINUTES 35 SECONDS WEST 573.23 FEET TO A POINT IN THE CENTER OF TOWNSHIP ROAD 186 (ZANE TRACE ROAD); PASSING AN IRON PIN SET AT 558.23 FEET; THENCE WITH THE SAID CENTER OF THE TOWNSHIP ROAD THE NEXT THREE COURSES AND DISTANCES:  
1) NORTH 81 DEGREES 22 MINUTES 20 SECONDS WEST 140.09 FEET TO A POINT,  
2) WITH A CURVE TO THE LEFT HAVING A RADIUS OF 1060.00 FEET (CHORD BEARING NORTH 87 DEGREES 38 MINUTES 45 SECONDS WEST 231.66 FEET) AN ARC DISTANCE OF 232.13 FEET TO A POINT,  
3) SOUTH 86 DEGREES 04 MINUTES 50 SECONDS WEST 129.53 FEET TO A POINT AT THE SOUTHEAST CORNER OF A 3.017 MORE OR LESS ACRE TRACT CONVEYED TO DARRELL R. AND MARY L. GARBER BY DEED RECORDED IN VOLUME 830, PAGE 15 OF THE SAID COUNTY RECORDS; THENCE LEAVING THE SAID TOWNSHIP ROAD AND WITH THE EAST LINE OF THE SAID GARBER TRACT, NORTH 04 DEGREES 14 MINUTES 00 SECONDS EAST 15.30 FEET TO THE PLACE OF BEGINNING.

CONTAINING 5.693 MORE OR LESS ACRES TOTAL, 5.673 MORE OR LESS ACRES IN SECTION 14 (66-66-50-14-36-000 PART) AND 0.020 MORE OR LESS ACRES IN SECTION 17 (66-66-80-17-05-000 PART). SUBJECT TO ALL LEGAL ROAD RIGHT-OF-WAY AND ALL OTHER APPLICABLE EASEMENTS.

ALL IRON PINS SET ARE 5/8 INCH X 30 INCH REBAR WITH PLASTIC IDENTIFICATION CAPS.

BEARINGS ARE BASED ON THE PREVIOUS SURVEY OF THE ABOVE MENTIONED 3.017 MORE OR LESS ACRE TRACT AS PREPARED BY JOSEPH T. SPILKER, REGISTERED SURVEYOR #5862 AND DATED MARCH 25, 1980.

I HEREBY CERTIFY TO THE BEST OF MY KNOWLEDGE THE SURVEY AND DESCRIPTION TO BE CORRECT AS PREPARED BY ME, THIS 23RD DAY OF JANUARY 1991

OFFICE COPY  
NOT RECORDED  
W. J. BIEDENBACH  
REGISTERED SURVEYOR

D3290-3 D. RALPH

DESCRIPTION APPROVED  
FOR AUDITOR'S TRANSFER

BY J. L. Hambl  
2-01-91

✓