

**TRACT 6**  
**PAGE 3**

THENCE North 76 degrees 41 minutes 52 seconds East for a distance of 13.57 feet along the south line of lands now or formerly owned by A.E. Stotts (DR 1059-492) to an iron pin set;

THENCE along said A.E. Stotts' lands the following two courses:

- 1) South 82 degrees 27 minutes 51 seconds East for a distance of 396.00 feet to an iron pin set;
- 2) South 69 degrees 55 minutes 06 seconds East for a distance of 481.80 feet to an iron pin set on the east line of said Lot 13;

THENCE South 02 degrees 20 minutes 29 seconds West for a distance of 130.02 feet along the east line of said Lot 13 to an iron pin set on the southeast corner of said Lot 13;

THENCE South 85 degrees 42 minutes 16 seconds East for a distance of 1582.04 feet along the north line of said Lot 6 and the south line of lands now or formerly owned by K. and A. Stotts (DR 1059-492) to an iron pin set;

THENCE South 86 degrees 10 minutes 07 seconds East for a distance of 1137.00 feet along the north line of said Lot 6 and the south line of lands now or formerly owned by Robert J. and Doris L. Moore (DR 1084-304) to the place of beginning;

containing 235.43 acres, more or less, subject to all applicable right of ways and easements, written or implied.

Iron pins set are 5/8 inch diameter by 30 inch long rebar with plastic identification caps.

Bearings on based on NAD 83 State Plane Grid Coordinate System as per GPS observations made in February 1998.

This description is written based on a survey completed February 16, 1998 by Timothy H. Linn, Reg. No. 7113.

**OFFICE COPY**  
**NOT RECORDABLE**  
Timothy H. Linn  
Reg. No. 7113  
Date 2/24/98  
7113  
REGISTERED  
PROFESSIONAL SURVEYOR  
STATE OF OHIO

DESCRIPTION APPROVED  
FOR AUDITORS TRANSFER

EV. 2-24-98

2-24-98

**PARCEL NO:**

70-70-13-02-06-000	( 4.81 ac.)
70-70-13-02-13-000	( 83.99 ac.)
70-70-13-02-14-000	( 6.39 ac.)
70-70-13-02-15-000	( 9.99 ac.)
70-70-13-02-32-000	( 3.24 ac.)
70-70-13-02-33-000	(127.01 ac.)
<b>Total</b>	<b>(235.43 ac.)</b>