

10. North 02 degrees 53 minutes 33 seconds East 59.60 feet to an iron pin found;
11. North 87 degrees 07 minutes 20 seconds West 90.07 feet to an iron pin found;
12. On a curve to the right having a radius of 100.00 feet, a delta angle of 90 degrees 26 minutes 44 seconds, a chord bearing and distance of South 48 degrees 10 minutes 30 seconds West 141.97 feet to an iron pin found;
13. On a curve to the left having a radius of 1954.86 feet, a delta angle of 14 degrees 07 minutes 03 seconds, a chord bearing and distance of South 86 degrees 19 minutes 17 seconds West 480.45 feet to an iron pin found;
14. South 79 degrees 15 minutes 44 seconds West 787.50 feet to an iron pin found;
15. South 82 degrees 46 minutes 07 seconds West 340.20 feet to the place of beginning containing 295.516 acres, more or less.

Part of Parcel No.:	70-70-15-02-24-000 (\pm 6.220 acres)
Part of Parcel No.:	70-70-15-08-02-000 (\pm 50.590 acres)
Part of Parcel No.:	70-70-15-09-04-000 (\pm 191.089 acres)
All of Parcel No.:	70-70-15-09-19-000 (\pm 36.254 acres)
Part of Parcel No.:	70-70-15-09-06-000 (+ 11.363 acres)
TOTAL 295.516 ACRES	

This legal description was written by Denis P. Swierz based on a field survey completed July 2006, July 2008 AND September 2010 by Muskingum County Engineers' Office. The bearings in this description are based on NAD 83, Ohio South Zone, State Plane coordinates as per GPS Observations from Muskingum County Engineer GPS monument - GPS 41.

Subject to all easements, right of ways, restrictions, reservations, etc.. of record and those that may be implied.

**OFFICE COPY
NOT RECORDABLE**

Denis P. Swierz
Reg. Surv. No. 8062

1 Oct. 2010
Date

OHIO
DENIS
P.
SWIERZ
8062
REGISTERED
PROFESSIONAL SURVEYOR