TERRY J. FINLEY SURVEYING & MAPPING

155 Mockingbird Hill, Zanesville, OH 43701

Phone ir Fax: (614) 454-8721

Obio Re ristered Surveyor #5-7222

73-2101.27 PS

LEGAL DESCRIPTION FOR ROBERT MELL PROPERTY

TRACT 2

SITUATED IN THE STATE OF OHIO, COUNTY OF MUSKINGUM, TOWNSHIP OF WAYNE, AND BEING PAR! OF THE NORTHWEST QUARTER OF SECTION 8, TOWNSHIP 12, RANGE 13, AND BEING PART OF THOSE LANDS INTENDED TO BE DESCRIBED IN DEED VOLUME 489, PAGE 636; BEING FURTHER BOUNDED AND DESCRIBED AS FOLLOWS:

COMMENCING AT AN IRON PIN FOUND AT THE SOUTHWEST CORNER OF THE NORTHWEST QUARTER OF SAID SECTION 8, THENCE, NORTH 00 DEGREES - 06 MINUTES - 46 SECONDS EAST, 1010.00 FEET ALONG THE QUARTER SECTION LINE TO AN AXLE POUND; THENCE, SOUTH 87 DEGREES - 26 MINUTES - 04 SECOND. EAST, 538.27 FEET TO A POINT IN THE CENTER OF WAYNE RIDGE ROAD, PASSIN; AN IRON PIN SET AT 508.27 FEET; THENCE, SOUTH 62 DEGREES - 46 MINUTES - 28 SECONDS EAST, 30.01 FEET TO A POINT IN SAID CENTERLINE; THENCE, SOUTH 38 DEGREES - 16 MINUTE; - 40 SECONDS WEST, 173 28 PEET TO AN IRON PIN SET, PASSING AN IRON PIN SIT AT 30.00 PEET; THENCE, SOUTH 43 DEGREES - 26 MINUTES - 00 SECONDS EAST, 203.40 FEET TO AN IRON PIN SET, AND THE TRUE POINT OF BEGINNING FOR THE PARCEL HEREIN INTENDED TO BE DESCRIBED; THENCE, NORTH 38 DEGREES - 6 MINUTES - 40 SECONDS EAST, 259.29 FEET TO A POINT IN THE CENTERLINE OF WAYNE RIDGE ROAD, PASSING AN IRON PIN SET AT 239.29 FEET; THENCE, ALONG THE CENTERLINE OF SAID ROAD, THE FOLLOWING FOUR (4) COURSES AND DISTANCES:

- 1) SOUTH 63 DEGREES 52 MINUTES -35 SECONDS BAST, 34.62 FEET TO A POINT;
- 2) SOUTH 57 DEGREES MINUTES -SECONDS EAST, 38.26 FEET 10 POINT;
- 3) SOUTH 50 DEGREES 14 MINUTES -04 SECONDS EAST, 51.83 FEET TO POINT;
- 4) SOUTH 45 DEGREES - 18 MINUTES - 50 SECONDS BAST, 25.17 FEET TO A POINT:

THENCE, LEAVING SAID ROAD, SOUTH 35 DEGREES - 11 MINUTES - 00 SECONDS WEST, 290.81 FEET TO AN IRON PIN SET, PASSING AN IRON PIN SET AT 20.00 FEET; THENCE, NORTH 43 DEGREES - 26 HINUTES - 00 SECONDS WEST, 166.15 PEET TO THE POINT OF BEGINNING, AND CONTAINING 1.0026 ACRES MORE OR LESS.

SUBJECT TO ALL LEGAL HIGHWAYS AND EASEMENTS OF RECORD.

BEARINGS DESCRIBED HEREIN ARE BASED UPON ASSUMED AZIMUTH AND TO BE USED FOR ANGLE FURPOSES ONLY.

IRON PINS SET ARE 5/8* REBAR WITH YELLOW IDENTIFICATION CAP S-7222). (PINCEY

BEING PART OF AUDITOR'S PARCEL #73-21-01-27-000.

THIS DESCRIPTION, WRITTEN ON NOVEMBER 13, 1997, IS BASED ON AN ACTUAL SURVEY OF THE PREMISES BY TERRY OHIO REGISTERED BURYEYOR **₹**S-7222,

> TERRY J. TERRY J. TIRE D. REGISTERED SURVEYOR

> > DESCRIPTION APPROVED **TRANSFER**

: