

Carl Gibson  
5/19/93

Situated in the State of Ohio, County of Muskingum, Township of Wayne, Township 13, Range 12, part of the Northwest Quarter of Section 7, Southwest Quarter of Section 6 and Northeast Quarter of Section 10 and bounded and described as follows:

Commencing at the Northeast corner of Section 10; thence South  $3^{\circ} 10' 19''$  West on the East line of said section 1779.54 feet to an iron pin found, the place of beginning; thence South  $64^{\circ} 55' 46''$  West 93.48 feet to an iron pin found; thence South  $72^{\circ} 43' 48''$  West 217.56 feet to an iron pin found; thence South  $39^{\circ} 59' 56''$  West 162.43 feet to an iron pin found; thence South  $56^{\circ} 41' 20''$  West 122.09 feet to an iron pin found; thence North  $77^{\circ} 33' 38''$  West 125.21 feet to an iron pin found; thence North  $77^{\circ} 35' 41''$  West 139.64 feet to an iron pin found; thence North  $12^{\circ} 13' 30''$  East 94.41 feet to an iron pin found; thence North  $76^{\circ} 35' 16''$  West 48.60 feet to a corner post at Jim Kannal; thence North  $12^{\circ} 20' 55''$  East along Jim Kannal, Vol. 766, Page 91, 1941.97 feet to an iron pin found; thence South  $53^{\circ} 51' 39''$  East along the South line of old Ohio River & Western Railroad 669.33 feet to the center of Millers Lane passing a large post found at 651.43 feet; thence along the center of said road the following four (4) courses and distances, South  $2^{\circ} 07' 03''$  East 115.90 feet to a point, South  $3^{\circ} 08' 45''$  West 177.82 feet to a point, South  $6^{\circ} 40' 52''$  East 198.92 feet to a point and South  $8^{\circ} 23' 05''$  East 157.84 feet to a point; thence leaving Millers Lane and along the North line of Vincent Sirgist, Vol. 549, Page 155, South  $80^{\circ} 38' 41''$  West 217.50 feet to an iron pin found, passing an iron pin set at 25.00 feet; thence South  $9^{\circ} 35' 37''$  East 202.20 feet along the West line of Vincent Sirgist to an iron pin found; thence along the South line of Vincent Sirgist North  $80^{\circ} 38' 41''$  East 217.80 feet to the center of Millers Lane, passing an iron pin found at 164.70 feet; thence along center of Millers Lane the following two (2) courses and distances, South  $8^{\circ} 42' 40''$  West 222.70 feet to a point and South  $15^{\circ} 40' 43''$  West 319.44 feet to a point; thence leaving Millers Lane North  $86^{\circ} 49' 41''$  West 125.86 feet to the place of beginning, passing an iron pin set at 43.36 feet, containing 29.90 acres more or less.

Bearings are based on the East line of Section 10 bearing South  $3^{\circ} 10' 19''$  West.

Being all of Auditor's Parcel Number 73-27-01-01-000.

Iron pins set are No. 5 reinforcing bars 30 inches long with plastic I. D. caps.

Description By:

**OFFICE COPY  
NOT RECORDABLE**  
*R. L. Daniels*  
R. L. Daniels  
Registered Surveyor No. 5410

DESCRIPTION APPROVED  
FOR AUDITOR'S TRANSFER

BY *A. L. Smith*  
5-20-93