Carl Gibson 2/20/95

73-27-01-01 1721 MILLERS LN

Situated in the State of Ohio, County of Muskingum, Township of Wayne, Township 13, Range 12, part of the Northwest Quarter of Section 7, Southwest Quarter of Section 6 and Section 10, bounded and described as follows:

Commencing at the Northeast corner of Section 10; thence South 3° 10' 19" West 1779.54 feet to an iron pin found, the place of beginning; thence South 64° 55' 46" West along G. W. Arnold, Vol. 324, Page 162, 93.48 feet to an iron pin found; thence continuing along G. W. Arnold South 72° 43' 48" West 217.56 feet to an iron pin found; thence South 39[°] 59' 56" West along J. D. Baker, Vol. 855, Page 205, 162.43 feet to an iron pin found; thence South 56[°] 41' 20" West along R. A. Blaney, Vol. 860, Page 132, 122.09 feet to an iron pin found; thence North 77[°] 33' 38" West along R. J. Herron, Vol. 837, Page 226, 125.21 feet to an iron pin found; thence North 77[°] 35' 41" West along V. P. Tucker, Vol. 669, Page 113, 139.64 feet to an iron pin found; thence North 12° 13' 30" East along H. & E. Baughman, Vol. 368, Page 411, 94.41 feet to an iron pin found; thence North 76° 35' 16" West along H. & E. Baughman 48.60 feet to a corner post found; thence North 12° 20' 55" East along J. R. Kannal, Vol. 766, Page 91, 1941.97 feet to an iron pin found; thence South 53° 51' 39" East along abandoned Ohio River and Western Railroad 669.33 feet to a point in Millers Lane, passing a large post at 651.43 feet; thence in Millers Lane and along the West line of W. A. Wise, Vol. 731, Page 26, the following two (2) courses and distances, South 2° 07' 03" East 115.90 feet to a point and South 3° 08' 45" West 134.90 feet to a point; thence along C. S. Hendershot, Vol. 496, Page 406, the next three (3) courses and distances, South 88° 07' 23" West 242.59 feet to an axle found, passing an iron pin set at 28.81 feet, South 9° 35' 37" East 400.00 feet to an axle found and North 80° 38' 41" East 218.13 feet to a point in Millers Lang, passing an axle found at 189.89 feet; thence in Millers Lane South 8° 23' 05" East 30.01 feet to a point; thence leaving Millers Lane and along Vincent Sirgist, Vol. 549, Page 155, the next three 13) courses and distances, South 80° 38' 41" West 217.50 feet to an iron pin found, passing an iron pin set at 25.00 feet, South 9° 35' 37" East 202.20 feet to an iron pin found and North 80° 38' 41" East 217.80 feet to a point in Millers Lane, passing an iron pin found at 164.70 feet; thence in Millers Lane and along the West line of W. Wilson, Vol. 1048, Page 182 the next two (2) courses and distances, South 8° 42' 40" West 222.70 feet to a point and South 15° 40' 43" West 319.44 feet to a point thence leaving Millers Lane North 86° 49' 41" West 125.86 feet along 40' 43" West 319.44 feet to a point; G. W. Arnold, Vol. 324, Page 162, to the place of beginning, passing an iron pin set at 43.36 feet, containing 27.91 acres more or less.

Bearings are based on the East Line of Section 10 bearing South 3° 10' 19" West.

73-15-06-39-000 Being all of Auditor's Parcel Numbers 73-27-01-01-000. 73-30-01-55-000 Iron pins set are No. 5 reinforcing bars 30 inches long with plastic I. D. caps.

Reference: Deed Volume 929, Page 143.

Survey & Description By: Surveyor No. 5410 DESCRIPTION APPROVED FOR AUDITOR'S TRANSFER

2-21-95

SY



