

www.mcpeeklandsurveying.com email: brian@mcpeeklandsurveying.com
340 Robin Hood Ln.,* Zanesville, Oh 43701 * 740.704.6073

Michael J. Durant & Lucia A. Durant OR 1843-225 +/-0.242 Ac.

Situated in the State of Ohio, County of Muskingum, Township of Wayne and being in the east part of Fractional Section 4, T11, R13, also being part of the lands now owned by Michael J. Durant & Lucia A. Durant as recorded in OR 1843-225 of the Muskingum County Recorders Office and being more particularly described as follows.

Beginning for reference at an iron pin found at the southwest corner of Outlot "A", Millstone Meadows Phase II (Plat Book 20, Page 68), thence N 72°22'22" W a distance of 201.74 feet to an iron pin found:

thence with the west line of the lands now owned by Patrick N. Paul & Teresa A. Paul (DR 921-231) the following two (2) courses:

- 1. S 37°37'20" W a distance of 528.91 feet to an iron pin found;
- 2. S 70°32'08" W a distance of 211.93 feet to an iron pin found on the northeast corner of the lands now owned by Michael J. Durant & Lucia A. Durant (OR 1843-225) and the principal place of beginning;

thence going throug said Michael J. Durant & Lucia A. Durant's lands the following two (2) courses:

- 1. N 59°26'26" W a distance of 311.15 feet to an iron pin set;
- 2. S 69°38'49" W a distance of 169.00 feet to a point in the center of Frick Drive, passsing an iron pin set at 134.35 feet;

thence with the center of said Frick Drive, N 01°52'17" W a distance of 47.33 feet to a point on the southeast corner of said Adam N. Durant & Kristin J. Durant's lands;

thence leaving the center of said Frick Drive and going with the common line of said Durant/Durant the following four (4) courses:

- 1. N 68°52'24" E a distance of 180.64 feet to a point;
- 2. N 59°12'40" E a distance of 23.43 feet to point;
- 3. S 18°15'12" W a distance of 60.77 feet to a point;
- 4. S 57°15'34" E 307.14 feet to the principal place of beginning, containing 0.242 acres more or less, subject to all legal highways and easements of record.

All bearings described herein are based on the Ohio State Plane Grid Coordinates, NAD83, Ohio South per GPS Observation.

Not to be used as a separte building site or transferred as an independent parcel in the future without planning commission approval in accordance with applicable subdivision regulations.

All iron pins set are 5/8 inch by 30 inch steel rebar with plastic identification caps marked MCPEEK PS8517.

The above described 0.242 acre parcel is based on a field survey made by McPeek Land Surveying, LLC on February 7th, 2018.