

BOWMAN AND ASSOCIATES  
91 BASIN STREET  
FRAZEYSEBURG OHIO 43822  
614-828-2204

PARCEL  
#73-73-54-01-03-000 ALL *PS*

SURVEY DESCRIPTION  
FOR  
Hilda K. Paul

Situated in the Northeast Quarter of Section #3, T-11, R-13, Congress lands, Wayne Township, Muskingum County, Ohio. Being the lands of Hilda K. Paul as conveyed in Deed Book 914 page 119 of the Muskingum County Deed records and being more particularly described as follows:

Beginning at a stone found on the Northeast corner of section #3; thence, S.00° 09'43"E. a distance of 774.14 feet along the East line of said section to a set iron pipe; thence, S.89°50'17"W. a distance of 574.20 feet along the North line of C. & P. Hayes (977/211) to a set iron pipe; thence, S.00°20'05"W. a distance of 192.13 feet along the West line of said Hayes lands to a set iron pipe; thence, S.89°32'57"W. a distance of 544.80 feet along the North line of D. & B. Paul (651/335) to a set iron pipe; thence, S.00°27'16"E. a distance of 605.69 feet along the West line of said Paul lands and the West line of J. & C. Wicker (956/074) to a point in the center of Deitz Lane, passing a found iron pin at 590.69 feet; thence, S.89°32'59"W. a distance of 650.84 feet along said lane to a set railroad spike; thence, continuing along the centerline of Deitz Lane the following eight courses and distances, N.10°39'14"W. a distance of 573.78 feet to a point; thence, N.09°58'05"W. a distance of 239.74 feet to a point; thence, N.20°24'03"W. a distance of 68.77 feet to a point; thence, N.73° 09'21"W. a distance of 111.44 feet to a point; thence, S.83°43'37"W. a distance of 49.49 feet to a point; thence, S.79°12'52"W. a distance of 217.67 feet to a point; thence, N.86°39'24"W. a distance of 208.83 feet to a point; thence, N.77°35'31"W. a distance of 146.86 feet to a point on the West line of the Northeast quarter; thence, N.00°00'00"E. a distance of 418.12 feet along said quarter section line to a found iron pin on the Southwest corner of H. & G. Paul (915/133 & 927/199), passing a set iron pipe at 20.00 feet; thence, S.89°08'56"E. a distance of 418.87 feet along said Paul lands to a found iron pin; thence, S.61°27'23"E. a distance of 292.00 feet along said Paul lands to a point in the center of Lawhead Road, passing a found iron pin at 274.46 feet; thence, N.14°05'01"E. a distance of 187.24 feet along said road to a point; thence, N.19°18'08"E. a distance of 76.91 feet along said road to a point on the Southwest corner of a parcel of ground now or formerly owned by K. Millfell (8/550); thence, N.89° 56'45"E. a distance of 352.29 feet along the South line of said Millfell lands to a set iron pipe, passing a set iron pipe at 30.00 feet; thence, N.00°03'15"W. a distance of 17.85 feet along said Millfell lands to a set iron pipe on the Southwest corner of T. Paul (708/023); thence, N.89°56'45"E. a distance of 937.20 feet along the South line of said Paul lands to a set iron pipe; thence, N.00°03'15"W. a distance of 142.36 feet along said Paul lands to a set iron pipe on the North line of section #3; thence, N.89° 56'45"E. a distance of 821.26 feet along said section line to the point of beginning.

The above described parcel contains 52.522 acres, more or less and is subject to all legal easements and right of ways. North is based upon an assumed meridian. All set iron pipes are 3/4" x 30" pipes with I.D. caps.

Description prepared from actual field survey by Bowman & Associates,  
Stephen M. Bowman P.S. #7135, December 12, 1991

OFFICE COPY  
NOT RECORDABLE

DESCRIPTION APPROVED  
FOR AUDITOR'S TRANSFER

BY *J. L. Paul*  
12-01-91