

DESCRIPTION OF SURVEY FOR C & M WHITMIRE

JOB#1143-1

Situated in the State of Ohio, County of Muskingum, Township of Wayne:

Being part of the East Half, of the Northeast Quarter, of Section #1, Township #11, Range #13, of the Congress Lands East of the Scioto River, **being part of** the C & M Whitmire property recorded in Deed Book Volume 317, Page 364 of said county's deed records, known as Muskingum County **Auditor's Parcel Number 73-60-01-18-000**, and more particularly described as follows;

Beginning at the Southeast corner of said Northeast Quarter of Section #1, also being the Northeast corner of the Southeast Quarter of Section #1, and in the roadbed of Millers Lane (County Road #73), also being on the common line for Ranges #12 & #13 of said Congress Lands;

- #1- THENCE North 87 degrees 37 minutes 10 seconds West 1184.98 feet leaving said road and along the common line for said Southeast and Northeast Quarters of Section #1 to a wood post (found) at the Southwest corner of the East Half of said Southeast Quarter, passing iron pins (found) at 25.00 feet, 499.89 feet, and 1179.98 feet;
- #2- THENCE North 02 degrees 13 minutes 10 seconds East 679.73 feet along the common line for the East and West Halves of said Southeast Quarter of Section #1, to an iron pin (set);
- #3- THENCE South 85 degrees 53 minutes 40 seconds East 607.84 feet into said East Helf and through seid Whitmire property to an iron pin (set);
- #4- THENCE South 01 degrees 10 minutes 20 seconds West 477.27 feet continuing through said Whitmire property to an iron pin (set);
- #5- THENCE South 13 degrees 26 minutes 30 seconds East 149.95 feet continuing through said Whitmire property to an iron pin (set);
- #6- THENCE South 87 degrees 37 minutes 10 seconds East 528.26 feet continuing through said Whitmire property to the East line of said Section #1, also being in the roadbed of said Millers Lane, passing an iron pin (set) at 497.79 feet;
- #7- THENCE South 02 degrees 13 minutes 10 seconds West 40.00 feet along the East line of said Section #1, common line for said Ranges #12 & #13, and within said roadbed to the place of beginning, containing 10.03 acres.

The bearings within this description are based on State Plane Coordinate Grid derived from a Solar Observation (Local Hour Angle Method). Iron pins (set) are 5/8" rebar with identification caps (C.R.Harkness P.L.S.6885).

This description was written by Charles R. Harkness Professional Land Surveyor #6885 from an ectual survey completed on October 13, 2001, in accordance with Chapter 4733-37 of the Administrative Code, and is intended to be used for the legal transfer of the property described and does not intend to describe all or any easements of record, nor encroachments unless otherwise indicated.

Charles HVG-kness PLS #6885

DESCRIPTION APPROVED
FOR AUDITOR'S TRANSFE

10-22-2001

