EXHIBIT A

Page 1 of 2

RX 250 WD

Rev. 06/09

Ver. Date 05/03/11

PID 86719

PARCEL 12-WD MUS-60-8.03 ALL RIGHT, TITLE AND INTEREST IN FEE SIMPLE IN THE FOLLOWING DESCRIBED PROPERTY WITHOUT LIMITATION OF EXISTING ACCESS RIGHTS

Grantor/Owner, for himself and his heirs, executors, administrators, successors and assigns, reserves all existing rights of ingress and egress to and from any residual area (as used herein, the expression "Grantor/Owner" includes the plural, and words in the masculine include the feminine or neuter).

[Surveyor's description of the premises follows]

The lands herein described are situated in State of Ohio, Muskingum County, Ohio; Township of Wayne, Section 30, Range 12 West, Township 13 North, in Buckingham's First Addition and being a part of Lot 1 as shown in Deed Book 14 Page 441 and being more particularly described as follows:

PARCEL NO. 12-WD

Being a parcel of land lying on the right side of the centerline of survey of S.R. 60 made by the Ohio Department of Transportation, as shown on file in plans Mus-60-8.03, District 5 office of the Ohio Department of Transportation, Jacksontown, OH and being located within the following described points in the boundary thereof:

Commencing at the Southeast Corner of Lot Number 1 of Buckingham's 1st Addition to Duncan Falls as recorded in Deed Book 14, Page 441; said point being located 30.00 feet right of centerline station 501+77.00 of the centerline of survey & construction, S.R. 60; Thence North 71 degrees 37 minutes 57 seconds West a distance of 58.00 feet along the existing Right of Way line to a point, said point being located 30.00 feet right of centerline station 502+35 of the centerline of survey & construction, S.R. 60 and being the **TRUE POINT OF BEGINNING**:

Thence, along the existing Right of way line, North 71 degrees 37 minutes 57 seconds

West a distance of 8.00 feet to a point on the existing Right of Way line of Mill Street, said point being located 30.00 feet right of centerline station 502+43 of the centerline of survey & construction, S.R. 60;

EXHIBIT A

Page 2 of 2 Rev. 06/09

RX 250 WD

Thence, along said existing Right of Way line, North 18 degrees 22 minutes 03 seconds East a distance of 3.00 feet to a set iron pin on the proposed Right of Way line, said pin being located 33.00 feet right of centerline station 502+43 of the centerline of survey & construction, S.R. 60;

Thence, along said proposed Right of Way, South 51 degrees 04 minutes 36 seconds East a distance of 8.54 feet to the POINT OF BEGINNING.

It is understood that the above described area contains a total of <u>0.0003</u> acres more or less, including the present road which occupies <u>0.0003</u> acres, more or less, which is to be deleted from Auditors Parcel Number <u>73-90-02-24-000</u>.

All set iron pins are 3/4" x 30" rebars with aluminum caps inscribed "O.D.O.T. R/W District 5". All bearings shown are for project use only and are from the Ohio State Plane Coordinate System, South Zone, N.A.D. 83 as established by GPS measurements in 2010.

Said stations being the Station numbers as stipulated in the hereinbefore mentioned survey and as shown by plans on file in the Ohio Department of Transportation, Columbus Ohio.

Description prepared from an actual field survey by The Ohio Department of Transportation under the supervision of Charles W. Price, Jr. P.S. 7825.

Prior Instrument Reference as of the date of this survey was prepared: Deed Volume 2266, Page 213 of Muskingum County, Ohio.

Charles W. Price, Jr. P.S. 7825

Date

DESCRIPTION

APPROVED (6) 8/2011

The horizontal coordinates expressed herein are based on the Ohio State Plane Coordinates system, NAD 83, South Zone.

As a part of this project I have reestablished the locations of the existing property lines and centerline of existing Right of Way for property takes contained herein.

As a part of this project I have established the proposed property lines, calculated the Gross Take, present roadway occupied (PRO), Net Take and Net Residue; as well as prepared the legal descriptions necessary to acquire the parcels as shown herein.

As a part of this work I have set monuments at the proposed property corners, and other points shown herein.

The iron pins and caps will be 3/4" x 30" rebar with aluminum cap stamped 'Odot R/W District 5". All of my work contained herein was conducted in accordance with Ohio Administrative Code 4733-37 commonly known as "A Minimum Standards for Boundary Surveys in the State of

The words I and my as used herein are to mean that either myself or someone working under my direct supervision.

les W. Price, Jr., Professional Land Surveyor * 7825

STA. 502+45.29 0 101 47.00' LT. (9-WD WILLIAMS GRCCERY & CARRYOUT LLC, AN OHIO CORPORATION DV 2111 PG. 520 73-90-03-13-000 0.004 ACRES (PART) S71°37′57″ E 22.80° (LEAD IN 9-WD) N 71°37'57" W 37.20 STA. 501+85.80 STA. 502+45 30.00'LT. 30.00' LT. POB 9-WD — STA. 502+23 30.00' LT.

N 71°37 57

PAGE 441

TOWN OF DUNCAN FALLS PLAT BOOK 2, PAGE 67 SOUARE 6

TOWN OF DUNCAN FALLS PLAT BOOK 2, PAGE 67 SOUARE 7 HARTLEY COMPANY 16-WD DV 850 PG. 90 73-84-08-01-000 0.001 ACRES (PART) STA. 502+95.73 | 35.50' LT. N 47°28'47" W 13.44' S !6°38′57′ 5.50′ PEx R/W-POB 16-WD STA. 503+08 STA. 502+95.90 30.00' LT. 30.00' LT. S 71°37'57" E 12.10 - @ SUFVEY & CONSTRUCTION, S.R. 60

ST4. 502+70.50 -(12-WD 14-WD) N 71°37'57" W STA. 503+10 POB 12-WD -STA. 502+35 30.00' RT. N 71°37′57" W 8.00' 30.00' RT. STA. 501+77 -30.00' RT. STA. 502+43 POB 14-WD (LEAD IN 12-WD) STA. 503+02.80 30.00' RT. 30.00' RT. N 71°37'57" W 58.00' `— N 85°44′05″ E 7.80′ 18°22'03" E S 51°04'36" 1 8.54' S 18°16'54" 3.00 3.00' SHERRY L. BROOKS STA. 502+43 33.00' RT. REBECCA L. SANDERS STA. 503+02.80 33.00' RT. & CLINTON M. COX DV 2332 PG. 602 107 DV 2266 PG. 213 73-90-04-20-000 73-90-02-24-000 0.0002 ACRES (PART) IST PARCEL 0.0003 ACRES (PART) 101 BUCKINGHAM'S BUCKINGHAM'S IST ADDITION 2ND ADDITION DEED BOOK 16 DEED BOOK 14 PAGE 215

PLAT OF SURVEY

LEGEND

- S EXISTING R/W MONUMENT
- I.P. FOUND (IRON PIN/REBAR/IRON PIPE/AXLE)
- - ¾ " X 30" REBAR W!TH ALUM!NUM CAP STAMPED "ODOT R/W DISTRICT 5"

THE LANDS HEREIN DESCRIBED ARE SITUATED IN STATE OF OHIO, MUSKINGUM COUNTY, OHIO; TOWNSHIP OF WAYNE, SECTION 30, RANGE 12 WEST, TOWNSHIP 13 NORTH.


ALL BEARINGS SHOWN ARE FOR PROJECT USE ONLY AND ARE FROM THE OHIO STATE PLANE COORDINATE SYSTEM, SOUTH ZONE, N.A.D. 83 AS ESTABLISHED BY GPS MEASUREMENTS IN 2010.

SEE RECORDED CENTERLINE PLAT: PLAT BOOK II PAGES 26 & 27 RECORDED IN MUSKINGUM COUNTY AUG. 3, 1964.

THE EXISTING RIGHT OF WAY WIDTH AND LOCATION WERE DETERMINED USING DOCUMENTATION ON FILE FROM THE OHIO DEPARTMENT OF TRANSPORTATION, DISTRICT 5 OFFICE, JACKSONTOWN, OHIO.

MUS-60-(8.11,13.08)

CO. RD. AND TWP RD. RIGHT OF WAY DETERMINED FROM THE MUSKINGUM COUNTY ENGINEERS OFFICE MUSKINGUM COUNTY, OHIO



△ 9

₹ 4 ₹ 12

≥

တ

Ш

URV

S

0

⋖ 03 $\boldsymbol{\omega}$

0 Θ S \supset Σ