EXHIBIT A

Page 1 of 2

RX 250 WD

Rev. 06/09

Ver. Date 05/03/11

PID 86719

PARCEL 9-WD MUS-60-8.03 ALL RIGHT, TITLE AND INTEREST IN FEE SIMPLE IN THE FOLLOWING DESCRIBED PROPERTY WITHOUT LIMITATION OF EXISTING ACCESS RIGHTS

Grantor/Owner, for himself and his heirs, executors, administrators, successors and assigns, reserves all existing rights of ingress and egress to and from any residual area (as used herein, the expression "Grantor/Owner" includes the plural, and words in the masculine include the feminine or neuter).

[Surveyor's description of the premises follows]

The lands herein described are situated in State of Ohio, Muskingum County, Ohio; Township of Wayne, Section 30, Range 12 West, Township 13 North, in the Town of Duncan Falls, Square 6, being a part of Lot 1, as shown in Plat Book 2 Page 67 and being more particularly described as follows:

PARCEL NO. 9-WD

Being a parcel of land lying on the left side of the centerline of survey of S.R. 60 made by the Ohio Department of Transportation, as shown on file in plans Mus-60-8.03, District 5 office of the Ohio Department of Transportation, Jacksontown, OH and being located within the following described points in the boundary thereof:

Commencing at the Northeast Corner of Lot Number 1 of Square Number 6 in the Town of Duncan Falls as recorded in Plat Book 2, Page 67; said point being located 30.00 feet left of centerline station 501+85.80 of the centerline of survey & construction, S.R. 60; Thence North 71 degrees 37 minutes 57 seconds West a distance of 37.20 feet along the existing Right of Way line to a set iron pin on the existing Right of Way line, said iron pin being located 30.00 feet left of centerline station 502+23 of the centerline of survey & construction, S.R. 60 and being the **TRUE POINT OF BEGINNING**:

Thence, leaving said existing Right of Way line, South 71 degrees 02 minutes 08 seconds

West a distance of 28.03 feet to a set iron pin on the existing Right of Way line of Mill

Street, said pin being located 47.00 feet left of centerline station 502+45.29 of the
centerline of survey & construction, S.R. 60;

Thence, along said existing Right of Way line, North 16 degrees 38 minutes 57 seconds East a distance of 17.01 feet to a point, said point being located 30.00 feet left of centerline station 502+45 of the centerline of survey & construction, S.R. 60;

Thence, South 71 degrees 37 minutes 57 seconds East a distance of 22.80 feet to the POINT OF BEGINNING.

It is understood that the above described area contains a total of 0.004 acres more or less, including the present road which occupies 0.000 acres, more or less, which is to be deleted from of Auditors Parcel Number 73-90-03-13-000.

All set iron pins are 3/4" x 30" rebars with aluminum caps inscribed "O.D.O.T. R/W District 5". All bearings shown are for project use only and are from the Ohio State Plane Coordinate System, South Zone, N.A.D. 83 as established by GPS measurements in 2010.

Said stations being the Station numbers as stipulated in the hereinbefore mentioned survey and as shown by plans on file in the Ohio Department of Transportation, Columbus Ohio.

Description prepared from an actual field survey by The Ohio Department of Transportation under the supervision of Charles W. Price, Jr. P.S. 7825.

Prior Instrument Reference as of the date of this survey was prepared: Deed Volume 2111, Page 620 of Muskingum County, Ohio.

Charles W. Price Jr. P.S. 7825

Doto

Date

DESCRIPTION
APPROVED
By: 6 7 20 1

The horizontal coordinates expressed herein are based on the Ohio State P ane Coordinates system, NAD 83, South Zone.

As a part of this project I have reestablished the locations of the existing property lines and centerline of existing Right of Way for property takes contained herein.

As a part of this project I have established the proposed property lines, calculated the Gross Take, present roadway occupied (PRO), Net Take and Net Residue; as well as prepared the legal descriptions necessary to acquire the parcels as shown herein.

As a part of this work I have set monuments at the proposed property corners, and other points shown herein.

The iron pins and caps will be $3/4^{\prime\prime} \times 30^{\prime\prime}$ rebar with aluminum cap stomped "Odot R/W District 5". All of my work contained herein was conducted in accordance with Ohio Administrative Code 4733-37 commonly known as "A Minimum Standards for Boundary Surveys in the State of Ohio" unless so noted.

The words I and my as used herein are to mean that either myself or sameone working under my direct supervision.

Charles W. Price, Jr., Professional Land Surveyor # 7825

COUNTY\86719_9-WD_12-WD_14-WD_16-WD_PLATS.dgn

_WAY\PLAN_SHEETS\PLATS FOR

Ы. П

30.00' LT.

STA. 501+77 -

30.00' RT.

101 107 9-WD WILLIAMS GROCERY & CARRYOUT LLC, AN OHIO CORPORATION
DV 2111 PG. 620 73-90-03-13-000 0.004 ACRES (PART) (LEAD IN 9-WD) N 71°37'57" W 37.20 STA. 501+85.80 STA. 502+23 30.00' LT.

502

(LEAD IN 12-WD)

N 71°37'57" W 58.00'

- STA. 502+45.29 47.00' LT. 571°37′57″ E 22.80° STA. 502+45 30.00' LT.

TOWN OF DUNCAN FALLS

PLAT BOOK 2, PAGE 67 SQUARE 6

(12-WD POB 12-WD STA. 502+35 N 71°37'57" W 8.00' 30.00' RT. ST4: 502+43 30.00' RT.

ST4. 502+70.50 -

S 51°04′36″ E 8.54′ N 18°22'03" E 3.00'

SHERRY L. BROOKS STA. 502+43 33.00' RT. & CLINTON M. COX DV 2266 PG. 213 73-90-02-24-000 IST PARCEL 0.0003 ACRES (PART)

> BUCKINGHAM'S IST ADDITION DEED BOOK 14 PAGE 441

TOWN OF DUNCAN FALLS PLAT BOOK 2, PAGE 67

SOUARE 7

16-WD)

— € SUREEY & CONSTRUCTION, S.R. 60

14-WD

STA. 502+95.73-

S 16°38'57" W

POB 16-WD -

30.00' LT.

12.10

POB 14-₩D

30.00' RT.

S 18°16'54" W

3.00'

5

STA. 503+02.80

STA, 503+02.80

33.00' RT.

STA. 502+95.90

S 71°37′57" E

N 71°37′57" W 7.20

35.50' LT.

5.50'

HARTLEY COMPANY

DV 850 PG. 90

73-84-08-01-000

0.001 ACRES (PART)

N 47°28'47" W 13.44'

STA. 503+10 30.00' RT.

- N 85°44'05" E 7.80'

BUCKINGHAM'S 2ND ADDITION

DEEO BOOK 16 PAGE 215

REBECCA L. SANDERS

DV 2332 PG. 602

73-90-04-20-000

0.0002 ACRES (PART)

Ex R/W-

STA. 503+08

30.00' LT.

- O EXISTING R/W MONUMENT
- I.P. FOUND (IRON PIN/REBAR/IRON PIPE/AXLE)

THE LANDS HEREIN DESCRIBED ARE SITUATED IN STATE OF OHIO, MUSKINGUM COUNTY, OHIO; TOWNSHIP OF WAYNE, SECTION 30, RANGE 12 WEST, TOWNSHIP 13 NORTH.

ALL BEARINGS SHOWN ARE FOR PROJECT USE ONLY AND ARE FROM THE OHIO STATE PLANE COORDINATE SYSTEM, SOUTH ZONE, N.A.D. 83 AS ESTABLISHED BY GPS MEASUREMENTS IN 2010.

P:\MUS\86719\DESIGN\RIGHT. SEE RECORDED CENTERLINE PLAT: PLAT BOOK 11 PAGES 26 & 27 RECORDED IN MUSKINGUM COUNTY AUG. 3, 1964.

107

WERE DETERMINED USING DOCUMENTATION ON FILE FROM THE OHIO DEPARTMENT OF TRANSPORTATION, DISTRICT 5 OFFICE, JACKSONTOWN, OHIO.

MUS-60-(8.11,13.08)

CO. RD. AND TWP RD. RIGHT OF WAY DETERMINED FROM THE MUSKINGUM COUNTY ENGINEERS OFFICE MUSKINGUM COUNTY, OHIO

PLAT OF SURVEY

ဖွ


4


≥ S

တ ш > α \supset S 0

0 ∞ 0

9 S \supset







LEGEND

● - ¾" X 30" REBAR WITH ALUMINUM CAP STAMPED "ODOT R/W DISTRICT 5"

THE EXISTING RIGHT OF WAY WIDTH AND LOCATION