

**EXHIBIT A**

RX 250 WD

Page 2 of 2

Rev. 06/09

Thence, along said existing Right of Way line, **North 17 degrees 40 minutes 31 seconds East** a distance of **17.40 feet** to a set iron pin on the proposed Right of Way line, said pin being located 50.00 feet right of centerline station 508+21.47 of the centerline of survey & construction, S.R. 60;

Thence, along the proposed Right of Way line, **South 11 degrees 18 minutes 35 seconds East** a distance of **15.90 feet** to a set iron pin, said pin being located 36.00 feet right of centerline station 508+14 of the centerline of survey & construction, S.R. 60;

Thence, continuing along said proposed Right of Way line, **South 53 degrees 41 minutes 35 seconds East** a distance of **12.79 feet** to the **POINT OF BEGINNING**.

It is understood that the above described area contains a total of 0.002 acres more or less, including the present road which occupies 0.000 acres, more or less, which is to be deleted from Auditors Parcel Number 73-90-04-09-000.


All set iron pins are 3/4" x 30" rebars with aluminum caps inscribed "O.D.O.T. R/W District 5". All bearings shown are for project use only and are from the Ohio State Plane Coordinate System, South Zone, N.A.D. 83 as established by GPS measurements in 2010.

Said stations being the Station numbers as stipulated in the hereinbefore mentioned survey and as shown by plans on file in the Ohio Department of Transportation, Columbus Ohio.

Description prepared from an actual field survey by The Ohio Department of Transportation under the supervision of Charles W. Price, Jr. P.S. 7825.

Prior Instrument Reference as of the date of this survey was prepared: Deed Volume 2208, Page 116 of Muskingum County, Ohio.

 P.S.  
Charles W. Price, Jr. P.S. 7825  
5-9-11  
Date

DESCRIPTION  
APPROVED  
By:  6/8/2011

